



ENVIVA

suspended


EN Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 45 x 15 mm); no visible screws; surface raw or powder coated; pendant fitting with cable suspension; can be adjusted to any height; incl. feeder cable; linear light inset made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with symmetrical light distribution; direct / indirect light distribution; canopy for through wiring; converter included in canopy; optionally with sensor

ES Cuerpo de perfil de aluminio con diseño angular; forma extremadamente esbelta (solo 45 x 15 mm); sin tornillos visibles; superficie sin tratar o recubierta por pulverización; suspendido con cable; ajuste de altura continuo; incl. cable de alimentación; inserto luminoso lineal de plástico; equipado con puntos de luz LED individuales; buen control del deslumbramiento mediante plano de punto de luz retranqueado; se ha incrementado la eficiencia debido al uso de la última tecnología en el diseño de lentes; lentes aplicadas con característica de proyección wide flood; o reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; precisa característica de emisión con distribución de luz simétrica; característica de emisión directa / indirecta; baldaquino para cableado pasante; convertidor integrado en el baldaquino; opcionalmente con sensor

Quickinfo

3000 K, 4000 K
 CRI ≥ 80, CRI ≥ 90, 3 SDCM
 up to 202lm/W
 UGR ≤ 16 / 65° ≤ 1500 cd/m²
 L90 @ 50 000 h
 DALI-2, DALI-2 ESSENTIAL sensor
 louver, spotlight, lense

Types



Colours



Light distribution



up to 202lm/W
(high efficiency)



DIN EN 12464-1
UGR ≤ 19



sensor
integrated

Order options

COLOUR TEMPERATURE

| | |
|------------------------|---|
| 3000 K (CRI \geq 80) | 5 |
| 4000 K (CRI \geq 80) | 6 |
| 3000 K (CRI \geq 90) | 0 |
| 4000 K (CRI \geq 90) | 1 |

CONTROL

| | |
|--|---|
| DALI-2 | 1 |
| DALI-2 ESSENTIAL sensor (brightness & presence)* | B |

*DALI-2 application controller needed

MATERIAL COLOUR

| | |
|---|---|
| <input type="radio"/> traffic white RAL 9016 | 7 |
| <input checked="" type="radio"/> jet black RAL 9005 | 8 |
| <input type="radio"/> aluminium raw/white* | 0 |
| <input type="radio"/> aluminium raw/black** | 1 |

*feeder cable white/cable susp. chrome

**feeder cable black/cable susp. black

LIGHT OPTIC

| | |
|-------------------------------|--|
| louver (super wide flood 74°) | |
| spotline (wide flood 67°) | |
| lense (wide flood 67°) | |

LOUVER COLOUR


| | |
|---|---|
| <input checked="" type="radio"/> chrome reflector | 4 |
| <input type="radio"/> black reflector | 8 |

SPOTLINE COLOUR

| | |
|---|---|
| <input type="radio"/> traffic white RAL 9016 | 7 |
| <input checked="" type="radio"/> jet black RAL 9005 | 8 |
| <input checked="" type="radio"/> chrome | 4 |
| <input type="radio"/> gold | 9 |

CANOPY COLOUR

| | |
|---|---|
| <input type="radio"/> traffic white RAL 9016 | 7 |
| <input checked="" type="radio"/> jet black RAL 9005 | 8 |



ENVIVA suspended



LOUVER direct/indirect

| INSET POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|-------------|--------------|--------------------|--------|-----------------|
| 36 W 850 mA | 3000 K | ↓ 3180 / ↑ 3080 lm | 1204* | 067-0214:::☑☑■X |
| | 4000 K | ↓ 3620 / ↑ 3500 lm | | |
| 36 W 850 mA | 3000 K | ↓ 3230 / ↑ 3100 lm | 1504* | 067-0215:::☑☑■X |
| | 4000 K | ↓ 3680 / ↑ 3520 lm | | |

*sensor version +41mm; order canopy separately

SPOTLINE direct/indirect

| INSET POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|-------------|--------------|--------------------|--------|-----------------|
| 38 W 900 mA | 3000 K | ↓ 3340 / ↑ 3280 lm | 1204* | 067-1214:::☑☑■W |
| | 4000 K | ↓ 3800 / ↑ 3730 lm | | |
| 38 W 900 mA | 3000 K | ↓ 3340 / ↑ 3250 lm | 1504* | 067-1215:::☑☑■W |
| | 4000 K | ↓ 3810 / ↑ 3700 lm | | |

*sensor version +41mm; order canopy separately

LENSE direct/indirect

| INSET POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|-------------|--------------|--------------------|--------|-----------------|
| 37 W 900 mA | 3000 K | ↓ 2800 / ↑ 3280 lm | 1204* | 067-2214:::☑☑0W |
| | 4000 K | ↓ 3020 / ↑ 3730 lm | | |
| 37 W 900 mA | 3000 K | ↓ 3340 / ↑ 3250 lm | 1504* | 067-2215:::☑☑0W |
| | 4000 K | ↓ 3810 / ↑ 3700 lm | | |

*sensor version +41mm; order canopy separately

Electrical accessories

CANOPY CEILING 220-240 V AC, 50-60Hz, ☐ PC II

| TYPE | EFFICIENCY | L-W-H (mm) | ORDER CODE |
|-----------------|------------|------------|--------------|
| 850 mA DALI-2 | η 89 % | 112-112-35 | 005-261103 ☐ |
| 900 mA DALI-2 | η 89 % | 112-112-35 | 005-261113 ☐ |

INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI \geq 80, reflector colour chrome and spotline colour traffic white