



FRAME 40

recessed with trim


EN Luminaire housing made of extruded aluminium; recessed luminaire with trim; suitable for ceiling thickness of 8-25 mm; surface powder coated; luminaire profile can be pre-mounted; remaining luminaire components mounted without tools; light inset consisting of highly reflective coated extruded profile for improved thermal management; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering

FR Corps de luminaire en profil extrudé en aluminium ; luminaire encastré avec bord continu ; convient aux épaisseurs de plafond de 8-25 mm ; surface thermolaquée ; profilé de luminaire pouvant être monté à l'avance ; composants restants du luminaire montable sans outil ; élément lumineux composé de profilé extrudé laqué hautement réfléchissant pour une gestion thermique améliorée ; cache HPO (High Performance Opal) pour éclairage homogène ; LED économes en énergie à restitution de couleur élevée

Quickinfo

3000 K, 4000 K
 CRI ≥ 90, 3 SDCM
 up to 116 lm/W
 L90 @ 50000 h
 DALI-2
 opal

Types



Colours




Light distribution




DiiA® standards
 251, 252, 253



system
 solution



tunable white
 2700-6500 K



CRI ≥ 98
 XPECTRUM

Order options

COLOUR TEMPERATURE	☑☑
3000K	0
4000K	1

CONTROL

DALI-2

MATERIAL COLOUR

<input type="checkbox"/> traffic white RAL 9016	7
<input type="checkbox"/> white aluminium RAL 9006	G
<input checked="" type="checkbox"/> jet black RAL 9005	8

LIGHT OPTIC COVER

opal high performance

Options on request

COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE

tunable white 2700–6500K



DALI-2 DT8

LIGHT OPTIC COVER

microprismatic



FRAME 40 trim



MID LUMEN

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
12.4W	3000K	1370lm	1019	0 4 2 - 7 1 1 2 :: 3 ☑ H
	4000K	1430lm		
24.8W	3000K	2730lm	2019	0 4 2 - 7 1 1 4 :: 3 ☑ H
	4000K	2860lm		
37W	3000K	4100lm	3019	0 4 2 - 7 1 1 6 :: 3 ☑ H
	4000K	4300lm		

HIGH LUMEN

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
20.1W	3000K	2140lm	1019	0 4 2 - 7 1 2 2 :: 3 ☑ H
	4000K	2240lm		
40W	3000K	4270lm	2019	0 4 2 - 7 1 2 4 :: 3 ☑ H
	4000K	4470lm		
60W	3000K	6410lm	3019	0 4 2 - 7 1 2 6 :: 3 ☑ H
	4000K	6710lm		

Mounting accessories

CONCRETE INSTALLATION HOUSING

L (mm)	W-H (mm)	ORDER CODE
1038	57-87	0 4 2 - 7 1 9 5 2 1 0
2038	57-87	0 4 2 - 7 1 9 5 4 1 0
3038	57-87	0 4 2 - 7 1 9 5 6 1 0

