

## LED Strips

recessed/surface

**EN** High quality extruded aluminium channel, angular design; surface anodised or powder coated; available in 3 different light colours; flexible use in recessed or surface mounting; in combination with 3 different covers and compatible with 3 different LED or 2 COB strips


**DE** Hochwertiges Aluminiumstrangpressprofil, kantige Ausführung; Oberfläche eloxiert bzw. pulverbeschichtet; erhältlich in 3 verschiedenen Farben; flexibel einsetzbar in Einbau- oder Anbaumontage; in Kombination mit 3 verschiedenen Abdeckungen und kompatibel mit 3 verschiedenen LED- bzw. 2 COB-Stripes

### Quickinfo


2700 K, 3000 K, 4000 K  
CRI  $\geq$  90, 2 SDCM  
up to 136 lm/W  
IP 20

### Types

Channel



LED/COB Strips



### Colours



### Light distribution




## Order options

COLOUR TEMPERATURE	
2700K	9
3000K	0
4000K	1


MATERIAL COLOUR	
● white aluminium RAL 9006	6
○ white RAL 9003	7
● black RAL 9005	8

## Channels




### LED CHANNEL RECESSED WITH TRIM

TYPE	L-W-H (mm)	ORDER CODE
recessed with trim	2500-25-13	0 1 1 - 7 3 2 1 1 1



### LED CHANNEL RECESSED/SURFACE TRIMLESS S

TYPE	L-W-H (mm)	ORDER CODE
recessed/surface trimless	2500-16-7	0 1 1 - 7 3 0 1 1 1



### LED CHANNEL RECESSED/SURFACE TRIMLESS M


TYPE	L-W-H (mm)	ORDER CODE
recessed/surface trimless	2500-16-13	0 1 1 - 7 3 1 1 1 1

## LED/COB Strips

max. cable length to power supply: 5000 mm




### LED STRIP LOW POWER




INSET POWER	LUMINOUS FLUX	CUTTING UNIT	ORDER CODE
9.6W/m	1090lm/m	62.5mm	0 1 1 - 7 0 0 1

### LED STRIP MID POWER




INSET POWER	LUMINOUS FLUX	CUTTING UNIT	ORDER CODE
14.3W/m	1585lm/m	50mm	0 1 1 - 7 0 1 1

### LED STRIP HIGH POWER free-cutting




INSET POWER	LUMINOUS FLUX	CUTTING UNIT	ORDER CODE
18.5W/m	2285lm/m	5mm	0 1 1 - 7 0 2 1

### COB STRIP MID POWER



INSET POWER	LUMINOUS FLUX	CUTTING UNIT	ORDER CODE
11.2W/m	830lm/m	55.5mm	0 1 1 - 7 0 3 1

### COB STRIP HIGH POWER



INSET POWER	LUMINOUS FLUX	CUTTING UNIT	ORDER CODE
16.8W/m	1350lm/m	29.41mm	0 1 1 - 7 0 4 1

## Optical accessories

### LIGHT OPTIC COVER

TYPE	EFFICIENCY	L (mm)	ORDER CODE
opal	η 60%	2500	0 1 1 - 7 3 8 1 1 1 0 O
microprismatic	η 65%	2500	0 1 1 - 7 3 8 1 1 1 0 P
transparent	η 90%	2500	0 1 1 - 7 3 8 1 1 1 0 T

## Mounting accessories

### END CAPS

TYPE	PCS	ORDER CODE
LED channel recessed with trim	2	0 1 1 - 7 3 2 9 1 1
LED channel recessed/surface trimless S	2	0 1 1 - 7 3 0 9 1 1
LED channel recessed/surface trimless M	2	0 1 1 - 7 3 1 9 1 1

### MOUNTING CLIPS

TYPE	PCS	ORDER CODE
recessed with trim	4	0 1 1 - 7 3 2 9 2 1 6
surface trimless	4	0 1 1 - 7 3 0 9 2 1 6
surface trimless 0-180° adjustable	4	0 1 1 - 7 3 0 9 3 1 6

## Electrical accessories

### EASY-CLIP CONNECTOR

TYPE	PCS	L-W-H (mm)	ORDER CODE
wire to board	2	12-10-5	0 1 1 - 7 0 9 1 1 1 0
board to board	2	14-10-5	0 1 1 - 7 0 9 1 2 1 0
board to board L	2	20-16-5	0 1 1 - 7 0 9 1 3 1 0



## LED Strips

surface

**EN** High quality extruded aluminium channel, angular design; surface anodised or powder coated; available in 3 different light colours; flexible use in recessed or surface mounting; compatible with 3 different LED or 2 COB strips

**DE** Hochwertiges Aluminiumstrangpressprofil, kantige Ausführung; Oberfläche eloxiert bzw. pulverbeschichtet; erhältlich in 3 verschiedenen Farben; flexibel einsetzbar in Einbau- oder Anbaumontage; kompatibel mit 3 verschiedenen LED- bzw. 2 COB-Stripes

### Quickinfo


2700 K, 3000 K, 4000 K  
CRI  $\geq$  90, 2 SDCM  
up to 136 lm/W  
IP 20

### Types

Channel



LED/COB Strips



### Colours




### Light distribution



### Order options

COLOUR TEMPERATURE	
2700K	9
3000K	0
4000K	1

MATERIAL COLOUR	
● white aluminium RAL 9006	6
○ white RAL 9003	7
● black RAL 9005	8




### Channel incl. opal cover


LED CHANNEL SURFACE		L-W-H (mm)	ORDER CODE
TYPE	corner	2500-18-18	0 1 1 - 7 3 3 1 1 1 <input checked="" type="checkbox"/> 0

### LED/COB Strips


max. cable length to power supply: 5000 mm




INSET POWER	LUMINOUS FLUX	CUTTING UNIT	ORDER CODE
9.6 W/m	1090 lm/m	62.5 mm	0 1 1 - 7 0 0 1 <input checked="" type="checkbox"/> 1 0




INSET POWER	LUMINOUS FLUX	CUTTING UNIT	ORDER CODE
14.3 W/m	1585 lm/m	50 mm	0 1 1 - 7 0 1 1 <input checked="" type="checkbox"/> 1 0



INSET POWER	LUMINOUS FLUX	CUTTING UNIT	ORDER CODE
18.5 W/m	2285 lm/m	5 mm	0 1 1 - 7 0 2 1 <input checked="" type="checkbox"/> 1 0




INSET POWER	LUMINOUS FLUX	CUTTING UNIT	ORDER CODE
11.2 W/m	830 lm/m	55.5 mm	0 1 1 - 7 0 3 1 <input checked="" type="checkbox"/> 1 0



INSET POWER	LUMINOUS FLUX	CUTTING UNIT	ORDER CODE
16.8 W/m	1350 lm/m	29.41 mm	0 1 1 - 7 0 4 1 <input checked="" type="checkbox"/> 1 0

### Electrical accessories



EASY-CLIP CONNECTOR		PCS	L-W-H (mm)	ORDER CODE
TYPE	wire to board	2	12-10-5	0 1 1 - 7 0 9 1 1 1 0
	board to board	2	14-10-5	0 1 1 - 7 0 9 1 2 1 0
	board to board L	2	20-16-5	0 1 1 - 7 0 9 1 3 1 0


### Mounting accessories

END CAPS		PCS	ORDER CODE
TYPE	LED channel corner	2	0 1 1 - 7 3 3 9 1 1 <input checked="" type="checkbox"/>

MOUNTING CLIPS		PCS	ORDER CODE
TYPE	surface	4	0 1 1 - 7 3 3 9 2 1 6

**Power supplies 24V DC, IP 20**

max. cable length to LED Strips: 5000mm

**non DIM**

TYPE		L-W-H (mm)	ORDER CODE
18 W	non DIM	127-43-30	0 1 1 - 7 9 0 0 0 1 0
30 W linear	non DIM	246-30-16	0 1 1 - 7 9 0 0 1 1 0
35 W	non DIM	142-43-30	0 1 1 - 7 9 0 0 2 1 0
60 W	non DIM	225-43-30	0 1 1 - 7 9 0 0 3 1 0
60 W linear	non DIM	298-30-16	0 1 1 - 7 9 0 0 4 1 0
100 W	non DIM	250-43-30	0 1 1 - 7 9 0 0 5 1 0
100 W linear	non DIM	298-30-17	0 1 1 - 7 9 0 0 6 1 0
200 W	non DIM	325-43-30	0 1 1 - 7 9 0 0 7 1 0

**DALI-2**

TYPE		L-W-H (mm)	ORDER CODE
18 W	DALI-2	175-43-30	0 1 1 - 7 9 0 0 0 3 0
35 W	DALI-2	195-43-30	0 1 1 - 7 9 0 0 1 3 0
60 W	DALI-2	225-43-30	0 1 1 - 7 9 0 0 2 3 0
100 W	DALI-2	295-43-30	0 1 1 - 7 9 0 0 3 3 0
150 W	DALI-2	325-43-30	0 1 1 - 7 9 0 0 4 3 0

**CASAMBI**

TYPE		L-W-H (mm)	ORDER CODE
35 W	Casambi	195-43-30	0 1 1 - 7 9 0 0 0 9 0
100 W	Casambi	295-43-30	0 1 1 - 7 9 0 0 1 9 0

**DIN RAIL**

TYPE		L-W-H (mm)	ORDER CODE
100 W	DIN Rail	70-55-90	0 1 1 - 7 9 1 0 0 1 0
150 W	DIN Rail	105-55-90	0 1 1 - 7 9 1 0 1 1 0

**Power supplies 24V DC, IP 65, IP 67**

max. cable length to LED Strips: 5000mm

**non DIM | IP65**

TYPE		L-W-H (mm)	ORDER CODE
60 W IP 65	non DIM	171-62-37	0 1 1 - 7 9 2 0 0 1 0
100 W IP 65	non DIM	220-68-39	0 1 1 - 7 9 2 0 1 1 0
150 W IP 65	non DIM	228-68-39	0 1 1 - 7 9 2 0 2 1 0
240 W IP 65	non DIM	244-68-39	0 1 1 - 7 9 2 0 3 1 0
320 W IP 65	non DIM	252-90-44	0 1 1 - 7 9 2 0 4 1 0

**DALI-2 | IP67**

TYPE		L-W-H (mm)	ORDER CODE
150 W IP 67	DALI-2	219-63-36	0 1 1 - 7 9 2 0 0 3 0
240 W IP 67	DALI-2	244-71-38	0 1 1 - 7 9 2 0 1 3 0