

HAUFE
DECKENSYSTEME

MILA system

ceiling

EN Luminaire housing from extruded aluminium profile, angular design; designed for continuous lighting systems; suitable for installation in the HAUFÉ slat ceiling system; optionally for slat height 40 mm or 60 mm; surface powder coated; HPO (High Performance Opal) cover or microprismatic cover in the length of the light inset or continuous cover (both separately available); optional high gloss reflector with faceted design; converter flexible positionable on the luminaire profile; converter suitable for through-wiring; energy-efficient LEDs with very good colour rendering; optionally sensor inset (ESSENTIAL or SENSE) available as accessory


ES Cuerpo de perfil de aluminio con diseño angular; diseñado para la creación de sistemas continuos; apta para integr. en sistema de techo de lamas HAUFÉ; opcionalmente para lamas de 40 mm o 60 mm de altura; superficie con recubrimiento de pintura en polvo; difusor HPO (High Performance Opal) o microprismático en la longitud del inserto luminoso o difusor continuo (deben encargarse por separado); opcional reflector de alto brillo con óptica facetada; driver de libre posicionamiento en el perfil de la luminaria; driver apto para cableado continuo; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; inserto de sensor (ESSENTIAL o SENSE) disponible como accesorio

Quickinfo


3000 K, 4000 K
CRI ≥ 90 , 3 SDCM
UGR ≤ 19 / $65^\circ \leq 1500$ cd/m²
up to 122 lm/W
up to 3280 lm/m
L90 @ 50 000 h
DALI-2
opal, microprismatic
reflector (UGR ≤ 19)

Types

opal / microprismatic



reflector



Colours



Light distribution




direct



DiiA® standards
251, 252, 253



suitable for
HAUFÉ ceilings



continuous
lighting system




sensor for
single mounting




DIN EN 12464-1
UGR ≤ 19



up to 115 lm/W
(high efficiency)



tunable white
2700–6500 K



CRI ≥ 98
XPECTRUM

Order options

SLAT HEIGHT	H
40 mm	2
60 mm	5


COLOUR TEMPERATURE	::
3000 K	0
4000 K	1

CONTROL	
DALI-2	

MATERIAL COLOUR	☒
○ traffic white RAL 9016	7
● jet black RAL 9005	8

LIGHT OPTIC COVER	☒
opal	H
microprismatic	Z
reflector (UGR ≤ 19)	

LIGHT OPTIC COLOUR	☒
chrome reflector	R
dark chrome reflector	B



MILA opal / microprismatic ceiling




SYSTEM LUMINAIRE incl. end caps | for HAUFCE ceiling U-slat system module 50

SYSTEM POWER	L (mm)	ORDER CODE
15.8 W	750	0 4 5 - 9 0 H 2 :: 3 ☒
21 W	1000	0 4 5 - 9 0 H 3 :: 3 ☒
25 W	1250	0 4 5 - 9 0 H 4 :: 3 ☒
31 W	1500	0 4 5 - 9 0 H 5 :: 3 ☒

LIGHT OPTIC COVER 40

TYPE	L (mm)	ORDER CODE
linear	750	0 0 6 - 4 2 0 7 5 1 0 ☒
linear	1000	0 0 6 - 4 2 1 0 0 1 0 ☒
linear	1250	0 0 6 - 4 2 1 2 5 1 0 ☒
linear	1500	0 0 6 - 4 2 1 5 0 1 0 ☒
continuous linear	6000	0 0 6 - 2 2 0 6 0 1 0 ☒
continuous linear	25000	0 0 6 - 2 2 2 5 0 1 0 ☒

LIGHT OPTIC COVER	COLOUR TEMPERATURE	SYSTEM POWER	DELIVERED LUMENS	EFFICACY
opal	3000 K	21 W/m	2200 lm/m	105 lm/W
	4000 K		2420 lm/m	115 lm/W
microprismatic	3000 K	21 W/m	2090 lm/m	100 lm/W
	4000 K		2300 lm/m	110 lm/W



MILA reflector ceiling



SYSTEM LUMINAIRE incl. end caps | for HAUFCE ceiling U-slat system module 50

SYSTEM POWER	L (mm)	ORDER CODE
13.4 W	504	0 4 5 - 9 1 H 1 :: 3 ☒ ☒
26.8 W	1004	0 4 5 - 9 1 H 3 :: 3 ☒ ☒


LIGHT OPTIC COVER	COLOUR TEMPERATURE	SYSTEM POWER	DELIVERED LUMENS	EFFICACY
reflector	3000 K	26.8 W/m	3130 lm/m	117 lm/W
(UGR ≤ 19)	4000 K		3280 lm/m	122 lm/W

Accessories



END CAPS

TYPE	ORDER CODE
end caps (pair)	0 4 5 - 9 0 9 0 0 1 ☒



LINEAR CONNECTOR

TYPE	ORDER CODE
mechanical linear connector sensor	0 4 5 - 9 0 9 1 0 1 0
mechanical linear connector luminaires	0 4 5 - 9 0 9 1 1 1 0

SENSOR DALI-2

TYPE	H (mm)	ORDER CODE
ESSENTIAL (brightness & presence)	40	0 4 5 - 9 0 9 6 0 1 ☒
ESSENTIAL (brightness & presence)	60	0 4 5 - 9 0 9 6 1 1 ☒
SENSE (brightness, presence, temperature, sound pressure, humidity, CO ₂)	40	0 4 5 - 9 0 9 6 0 2 ☒
SENSE (brightness, presence, temperature, sound pressure, humidity, CO ₂)	60	0 4 5 - 9 0 9 6 1 2 ☒