



MINO 25

suspended


EN Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 25 x 25 mm); no visible screws; surface raw or powder coated; pendant fitting with height-adjustable cable suspension; incl. flat cable for power supply; high quality reflector with micro-faceted, aluminum-vaporised surface; or fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; precise radiation characteristic with symmetrical light distribution; or completely homogeneously illuminated, opal cover; converter integrated into luminaire housing; energy-efficient LEDs with very good colour rendering; canopy for through wiring

DE Leuchtenkörper aus Aluminiumstrangpressprofil, kantige Ausführung; extrem schlanke Bauform (nur 25 x 25 mm); keine sichtbaren Schrauben; Oberfläche roh oder pulverbeschichtet; abgependelt mit höhenverstellbarer Seilabhängung; inkl. Flachkabel zur Einspeisung; hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; oder bestückt mit LED Einzellichtpunkten; gute Entblendung durch zurückversetzte Lichtpunktebene; trotzdem erhöhte Effizienz durch spezielle Linsentechnik; eingesetzte Linsen mit wide flood Abstrahlcharakteristik; präzise Abstrahlcharakteristik mit symmetrischer Lichtverteilung; oder absolut homogen ausgeleuchtete, opale Abdeckung; Konverter im Leuchtenkörper integriert; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Baldachin für Weiterverdrahtung


Quickinfo

3000 K, 4000 K
 CRI ≥ 80, CRI ≥ 90, 3 SDCM
 UGR ≤ 19 / 65° ≤ 1500 cd/m²
 up to 1630 lm/m | 168 lm/W
 L90@50 000 h
 DALI-2
 louver, spotline

Types



Colours



Light optics




Light distribution



black & chrome
louver



high efficiency
up to 168 lm/W



super slim
design

Order options

COLOUR TEMPERATURE

| | |
|------------------------|---|
| 3000 K (CRI \geq 90) | 0 |
| 4000 K (CRI \geq 90) | 1 |
| 3000 K (CRI \geq 80) | 5 |
| 4000 K (CRI \geq 80) | 6 |

CONTROL

DALI-2

MATERIAL COLOUR

| | |
|---|---|
| <input type="radio"/> traffic white RAL 9016 | 7 |
| <input checked="" type="radio"/> jet black RAL 9005 | 8 |
| <input type="radio"/> aluminium raw/white* | 0 |
| <input type="radio"/> aluminium raw/black** | 1 |

*feeder cable white

**feeder cable black

LOUVER COLOUR

| | |
|---|---|
| <input checked="" type="radio"/> chrome | 4 |
| <input checked="" type="radio"/> black | 8 |

SPOTLINE COLOUR


| | |
|--|---|
| <input type="radio"/> white | 7 |
| <input checked="" type="radio"/> black | 8 |

LIGHT OPTIC

louver super wide flood 74°

spotline wide flood 67°

MINO 25 suspended



LOUVER

| SYS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|--|
| 10.7W | 3000K | 1630lm | 1004 | 0 4 3 - 0 2 0 1 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> |
| | 4000K | 1730lm | | |
| 20.6W | 3000K | 3260lm | 2004 | 0 4 3 - 0 2 0 2 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> |
| | 4000K | 3470lm | | |
| 27.5W | 3000K | 4350lm | 2754 | 0 4 3 - 0 2 0 3 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> |
| | 4000K | 4630lm | | |

SPOTLINE

| SYS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|---|
| 10.7W | 3000K | 1600lm | 1004 | 0 4 3 - 0 2 1 1 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> W |
| | 4000K | 1710lm | | |
| 20.6W | 3000K | 3210lm | 2004 | 0 4 3 - 0 2 1 2 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> W |
| | 4000K | 3410lm | | |
| 27.5W | 3000K | 4280lm | 2754 | 0 4 3 - 0 2 1 3 :: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> W |
| | 4000K | 4560lm | | |