

## MITA square

recessed with trim


**EN** Square luminaire housing in die-cast aluminium; extremely slim design; recessed luminaire with trim; optional: blind cover to cover the cut-out available as an accessory; suitable for ceiling thickness of 2-25 mm; surface powder coated; high-gloss reflector with faceted design; energy-efficient LEDs with very good colour rendering

**FR** Corps de luminaire carré en aluminium moulé ; forme extrêmement élancée ; luminaire encastré avec bord continu ; en option : cache à insérer dans l'encoche intérieure disponible comme accessoire ; convient aux épaisseurs de plafond de 2-25 mm ; surface thermolaquée ; réflecteur ultra-brillant avec optique à facettes ; LED économes en énergie à restitution de couleur élevée

### Quickinfo

3000 K, 4000 K, TW  
 CRI ≥ 80, 3 SDCM  
 UGR ≤ 19 / 65° ≤ 1500 cd/m<sup>2</sup>  
 up to 155 lm/W  
 L95 @ 50 000 h  
 DALI-2  
 reflector (UGR ≤ 19)

### Types



### Colours




### Light distribution



suitable for plaster-board or grid ceilings



DIN EN 12464-1  
 UGR ≤ 19



tunable white  
 2700-6500K

## Order options

### COLOUR TEMPERATURE

3000K	5
4000K	6
tunable white 2700–6500K*	D

\*DALI-2 DT8

### CONTROL

DALI-2

### MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

### LIGHT OPTIC COLOUR

chrome reflector	R
black reflector	B

### LIGHT OPTIC COVER

reflector (UGR ≤ 19)





## Options on request

### COLOUR RENDERING INDEX

CRI ≥ 90

### GRID CEILING MOUNTING

installed in module 600 × 600 mm  
installed in module 625 × 625 mm



## MITA square 200 trim



### DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
13.9 W	3000 K	1950 lm	074-8314::3■
	4000 K	2160 lm	

## MITA square 360 trim



### DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
30 W	3000 K	4220 lm	074-8316::3■
	4000 K	4650 lm	
41 W*	3000 K	5490 lm	074-8326::3■
	4000 K	6060 lm	


\*not for tunable white

## Accessories

### BLIND COVER

TYPE	ORDER CODE
MITA 200 square recessed	074-891341■
MITA 360 square recessed	074-891361■

## Light distribution



reflector (UGR ≤ 19)  
direct

LUMINOUS FLUX value calculated for  
CRI ≥ 80, colour white, reflector chrome