

## MOVE IN round

recessed


**EN** Round spotlight element in aluminium, available in 2 sizes; powder coated; installation without tools in mounting set (trimless or with trim) with ball catch system; special mounting tool for easy installation of the trimless housing available as an accessory; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; high-quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristic; good glare reduction due to recessed light point plane; optical attachments as accessories

**FR** Élément de spot rond en aluminium, disponible dans 2 tailles ; thermolaquée ; montage sans outil en kit de montage (sans bord ou avec bord continu) par système à déclic à bille ; outil de montage spécial pour faciliter la mise en place du boîtier sans rebord proposé comme accessoire ; élément de spot réglable en hauteur sans outil : affleurant avec le plafond, dépassant de 25 mm ou 35 mm ; Technologie COB (Chip on Board) pour efficacité maximale ; pas de formation d'ombres multiples ; LED économes en énergie à restitution de couleur élevée ; réflecteur de grande qualité, métallisée à l'aluminium avec optique facette ; caractéristique de rayonnement précise ; bon anti-éblouissement grâce aux points lumineux en retrait ; éléments optiques comme accessoires

### Quickinfo

2700 K, 3000 K  
 CRI ≥ 90, 2 SDCM  
 MOVE IN 32 up to 86lm/W  
 MOVE IN 45 up to 95lm/W  
 L80 @ 50 000 h  
 non DIM, DALI-2

### Types




### Inset colours



### Housing colours



### Light distributions



tool-free height adjustment



trimless installation in plasterboard

### Order options

<b>COLOUR TEMPERATURE</b>	☑☑
2700K	4
3000K	5

<b>INSET COLOUR</b>	☑
○ traffic white RAL 9016	7
● jet black RAL 9005	8
● brushed aluminium	6
● chrome	4

<b>HOUSING COLOUR</b>	☑
○ traffic white RAL 9016	7
● jet black RAL 9005	8

<b>BEAM ANGLE</b>	▲
<b>MOVE IN 32/45</b>	
super spot 8°*	V
spot 18°/14°	S
medium 23°/24°	M
flood 37°/39°	F







\*only for MOVE IN 45

### Options on request

<b>INSET COLOUR</b>	
● gun metal	_____
● brushed brass	_____

<b>HOUSING COLOUR</b>	
special colours	_____

<b>POWER SUPPLY</b>	
DIM 1-10V	_____



### MOVE IN 32 round



**SPOTLIGHT** incl. connection cable 600 mm

<b>INSET POWER</b>	<b>LUMINOUS FLUX</b>	<b>ORDER CODE</b>
8.8 W 36 Vf 250 mA	755 lm	063-81111 ☑☑▲

### MOVE IN 45 round



**SPOTLIGHT** incl. connection cable 600 mm

<b>INSET POWER</b>	<b>LUMINOUS FLUX</b>	<b>ORDER CODE</b>
12.8 W 37 Vf 350 mA	spot 1010 lm	063-81211 ☑☑S
13.5 W 36 Vf 400 mA	1280 lm	063-81211 ☑☑▲
6.9 W 11 Vf 600 mA	super spot 356 lm	063-81211 ☑☑V

### Mounting accessories

**MOUNTING HOUSING TRIMLESS**  
for installation in plasterboard ceilings 9-25 mm

<b>TYPE</b>	<b>Ø-H (mm)</b>	<b>ORDER CODE</b>
MOVE IN 32	63-93	063-8811117
MOVE IN 45	75-106	063-8812117

**MOUNTING HOUSING WITH TRIM**  
for installation in ceilings from 2-25 mm

<b>TYPE</b>	<b>Ø-H (mm)</b>	<b>ORDER CODE</b>
MOVE IN 32	65-93	063-8821111 ☑
MOVE IN 45	77-107	063-8822111 ☑

### SPECIAL MOUNTING TOOL

<b>TYPE</b>	<b>Ø-H (mm)</b>	<b>ORDER CODE</b>
MOVE IN 32	83-9	063-8911110
MOVE IN 45	100-9	063-8912110

necessary to install mounting housing trimless

### Electrical accessories

**POWER SUPPLY 220-240 V AC, 50-60 Hz, □ PC II**

<b>TYPE</b>	<b>EFFICIENCY</b>	<b>L-W-H (mm)</b>	<b>ORDER CODE</b>
250 mA   non DIM	η 80%	65-39-20	002-90742
250 mA   DALI-2	η 82%	147-33-23	002-90743
350 mA   non DIM	η 85%	180-30-21	002-90722
350 mA   DALI-2	η 85%	197-29-21	002-90720
400 mA   non DIM	η 88%	180-30-21	002-90724
400 mA   DALI-2	η 86%	197-29-21	002-90728
600 mA   non DIM	η 87%	180-30-21	002-90726
600 mA   DALI-2	η 88%	197-29-21	002-90729

MOVE IN 32 trimless revision opening required; \*insert before mounting set with trim

### DIN RAIL COMPONENTS

<b>TYPE</b>	<b>W-H-D (mm)</b>	<b>ORDER CODE</b>
POWER SUPPLY 220-240 V AC	72-90-63	005-6520210
160 W   48 V DC constant voltage		
LED DRIVER DALI-2 DT6 1-2 addr.	36-88-59	005-6121030
200-1050 mA settable const. current		
2 × 42 W   48 V DC   U <sub>OUT</sub> 10-40 V		

for more details and components see page Seite 981

### Optical accessories

#### HONEYCOMB LOUVER

<b>TYPE</b>	<b>Ø-H (mm)</b>	<b>ORDER CODE</b>
MOVE IN 32	30-3	007-1965168
MOVE IN 45	42-3	007-1965188

**INSET POWER** is the current consumption excluding any ballast  
**LUMINOUS FLUX** value calculated for 3000K, CRI ≥90, colour white, reflector flood 2700K -6%