

MOVE IN round

recessed


EN Round spotlight element in aluminium, available in 2 sizes; powder coated; installation without tools in mounting set (trimless or with trim) with ball catch system; special mounting tool for easy installation of the trimless housing available as an accessory; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; high-quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristic; good glare reduction due to recessed light point plane; optical attachments as accessories

IT Elemento faretto rotondo in alluminio, due misure; verniciatura a polvere; set di fissaggio con cuscinetto a sfera, senza bisogno di utensili (con o senza bordo perimetrale); utensile di montaggio speciale per una facile installazione dell'housing senza bordi disponibile come accessorio; faretto regolabile in altezza senza utensili: a filo soffitto o sporgente di 25 mm o 35 mm; tecnologia COB (Chip on Board) per la massima efficienza; assenza di ombre multiple; LED ad efficienza energetica con elevata resa cromatica; riflettore d'alta qualità con ottica sfaccettata in alluminio applicato a vapore; emissione precisa; ottima schermatura con superficie di emissione arretrata; unità ottiche come accessori

Quickinfo

2700 K, 3000 K
 CRI ≥ 90, 2 SDCM
 MOVE IN 32 up to 86lm/W
 MOVE IN 45 up to 95lm/W
 L80 @ 50 000 h
 non DIM, DALI-2

Types




Inset colours



Housing colours



Light distributions



tool-free height adjustment



trimless installation in plasterboard

Order options

COLOUR TEMPERATURE	☑☑
2700K	4
3000K	5

INSET COLOUR	☑
○ traffic white RAL 9016	7
● jet black RAL 9005	8
● brushed aluminium	6
● chrome	4

HOUSING COLOUR	☑
○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE	▲
MOVE IN 32/45	
super spot 8°*	V
spot 18°/14°	S
medium 23°/24°	M
flood 37°/39°	F






*only for MOVE IN 45

Options on request

INSET COLOUR	
● gun metal	_____
● brushed brass	_____

HOUSING COLOUR	
special colours	_____

POWER SUPPLY	
DIM 1-10V	_____



MOVE IN 32 round



SPOTLIGHT incl. connection cable 600 mm

INSET POWER	LUMINOUS FLUX	ORDER CODE
8.8 W 36 Vf 250 mA	755 lm	063-81111:1☑▲

MOVE IN 45 round



SPOTLIGHT incl. connection cable 600 mm

INSET POWER	LUMINOUS FLUX	ORDER CODE
12.8 W 37 Vf 350 mA	spot 1010 lm	063-81211:1☑S
13.5 W 36 Vf 400 mA	1280 lm	063-81211:1☑▲
6.9 W 11 Vf 600 mA	super spot 356 lm	063-81211:1☑V

Mounting accessories

MOUNTING HOUSING TRIMLESS
for installation in plasterboard ceilings 9-25 mm

TYPE	Ø-H (mm)	ORDER CODE
MOVE IN 32	63-93	063-8811117
MOVE IN 45	75-106	063-8812117

MOUNTING HOUSING WITH TRIM
for installation in ceilings from 2-25 mm

TYPE	Ø-H (mm)	ORDER CODE
MOVE IN 32	65-93	063-882111■
MOVE IN 45	77-107	063-882211■

SPECIAL MOUNTING TOOL

TYPE	Ø-H (mm)	ORDER CODE
MOVE IN 32	83-9	063-8911110
MOVE IN 45	100-9	063-8912110

necessary to install mounting housing trimless

Electrical accessories

POWER SUPPLY 220-240 V AC, 50-60 Hz, ☐ PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
250 mA non DIM	η 80%	65-39-20	002-90742
250 mA DALI-2	η 82%	147-33-23	002-90743
350 mA non DIM	η 85%	180-30-21	002-90722
350 mA DALI-2	η 85%	197-29-21	002-90720
400 mA non DIM	η 88%	180-30-21	002-90724
400 mA DALI-2	η 86%	197-29-21	002-90728
600 mA non DIM	η 87%	180-30-21	002-90726
600 mA DALI-2	η 88%	197-29-21	002-90729

MOVE IN 32 trimless revision opening required; *insert before mounting set with trim

DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240 V AC	72-90-63	005-6520210
160 W 48 V DC constant voltage		
LED DRIVER DALI-2 DT6 1-2 addr.	36-88-59	005-6121030
200-1050 mA settable const. current		
2 × 42 W 48 V DC U _{OUT} 10-40 V		

for more details and components see page Seite 981

Optical accessories

HONEYCOMB LOUVER

TYPE	Ø-H (mm)	ORDER CODE
MOVE IN 32	30-3	007-1965168
MOVE IN 45	42-3	007-1965188

INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for 3000K, CRI ≥90, colour white, reflector flood 2700K -6%