



reddot winner 2024

DESIGN
AWARD
2024

Quickinfo

DALI-2

Types

recessed
trimless

Colours



MOVE IT PRO system

trimless

EN Extruded aluminium profile with 45 mm width and 55 mm height; for trimless installation in 12.5 mm plasterboard ceilings; designed for continuous lighting systems; with integrated 3-phase copper conductors + 4 emergency lighting copper conductors (2 emergency lighting circuits) + 2 DALI copper conductors for take off of supply voltage, emergency lighting power supply and DALI signal; customcut possible; surface powder coated; insets, incl. high power adapter + converter can be installed flexibly and without tools; light inserts with different patterns of light distribution, emergency light inserts (escape sign and emergency luminaires) for operation on a central battery system and sensor inserts can be integrated

ES Perfil de aluminio extrusionado de 45 mm de ancho por 55 mm de alto; para encastre sin bordes en planchas cartón yeso 12,5 mm; diseñado para sistemas de iluminación continuos; con conductores de cobre trifásicos integrados + 4 conductores de cobre para luz de emergencia (2 circuitos de luz de emergencia) + 2 conductores de cobre DALI para la toma de suministro eléctrico, el suministro eléctrico de emergencia y la señal DALI; corte a medida bajo petición; superficie con recubrimiento de pintura en polvo; montaje flexible y sin herramienta de los insertos, incluyendo adaptador de alta potencia y alimentador; insertos luminosos con distintos modos de proyección, elementos de luz de emergencia (luces de seguridad y de señalización de rutas de rescate) para el funcionamiento con un sistema de baterías centralizado e insertos de sensor incorporables

up to 192lm/W
(high efficiency)

Order options


CONTROL

DALI-2

MATERIAL COLOUR

● jet black RAL 9005	8
○ traffic white RAL 9016	7


Pole positions



— Position of the neutral conductor



MOVE IT PRO emergency trimless



INSTALLATION TRACK 220 V–250 V/440 V | EM 220 V–250 V

L (mm)		ORDER CODE
1000	channel	086-512113
2000	channel	086-512213
3000	channel	086-512313
4000	channel	086-512413
custom cut	channel	E83810

Accessories

END CAPS



TYPE	ORDER CODE
end cap	086-522011

BLIND COVER




L (mm)		ORDER CODE
1000	blind cover (aluminium)	086-601000
2000	blind cover (aluminium)	086-603000
3000	blind cover (aluminium)	086-605000



25000	blind cover	086-608250
-------	-------------	------------

POWER FEEDER WITH EMERGENCY CONDUCTORS


supply 220-250V/440V | EM 220-250V



TYPE	ORDER CODE
end feed poles right	086-522313
end feed poles left	086-522413
middle feed	086-522323

POWER FEEDER WITHOUT EMERGENCY CONDUCTORS

supply 220-250V/440V



TYPE	ORDER CODE
intrack feed (incl. cable 3000 mm)	086-5213338

CONNECTOR




TYPE	ORDER CODE
linear connector electrical	086-5211138

MOUNTING ACCESSORIES



TYPE	ORDER CODE
mechanical linear connector (pair)	050-2011110




conductors cutting tool	086-5219110
-------------------------	-------------


Quickinfo

DALI-2

Types



connectors



Colours



reddot winner 2024

DESIGN
AWARD
2024

MOVE IT PRO system


surface/suspended

EN Extruded aluminium profile with 45mm width and 59mm height; for ceiling surface mounting or suspended mounting (cable suspension); height adjustment without tools; designed for continuous lighting systems, L / T / X connectors for flexible system design; with integrated 3-phase copper conductors + 4 emergency lighting copper conductors (2 emergency lighting circuits) + 2 DALI copper conductors for take off of supply voltage, emergency lighting power supply and DALI signal; customcut possible; surface powder coated; insets, incl. high power adapter + converter can be installed flexibly and without tools; light inserts with different patterns of light distribution, emergency light inserts (escape sign and emergency luminaires) for operation on a central battery system and sensor inserts can be integrated

ES Perfil de aluminio extrusionado de 45mm de ancho por 59mm de alto; para montaje superpuesto en el techo o para montaje suspendido (suspensión de cable); altura regulable sin herramientas; diseñado para sistemas de iluminación continuos, conectores en L, T y X para un montaje flexible del sistema; con conductores de cobre trifásicos integrados + 4 conductores de cobre para luz de emergencia (2 circuitos de luz de emergencia) + 2 conductores de cobre DALI para la toma de suministro eléctrico, el suministro eléctrico de emergencia y la señal DALI; corte a medida bajo petición; superficie con recubrimiento de pintura en polvo; montaje flexible y sin herramienta de los insertos, incluyendo adaptador de alta potencia y alimentador; insertos luminosos con distintos modos de proyección, elementos de luz de emergencia (luces de seguridad y de señalización de rutas de rescate) para el funcionamiento con un sistema de baterías centralizado e insertos de sensor incorporables



up to 192 lm/W
(high efficiency)


Rev. 009/2025-10

Quickinfo

DALI-2

Types

surface suspended



connector



L-connector

Colours



reddot winner 2024

DESIGN
AWARD
2024

MOVE IT PRO emergency SELV system

surface/suspended

EN Extruded aluminium profile with 45 mm width and 59 mm height; for ceiling surface mounting or suspended mounting (cable suspension); height adjustment without tools; designed for continuous lighting systems, L connectors for flexible system design; with integrated 3-phase copper conductors + 4 emergency lighting copper conductors (2 emergency lighting circuits SELV) + 2 DALI copper conductors for take off of supply voltage, emergency lighting power supply and DALI signal; customcut possible; surface powder coated; insets, incl. high power adapter + converter can be installed flexibly and without tools; light inserts with different patterns of light distribution, emergency light inserts (escape sign and emergency luminaires) for operation on a central battery system and sensor inserts can be integrated

ES Perfil de aluminio extrusionado de 45 mm de ancho por 59 mm de alto; para montaje superpuesto en el techo o para montaje suspendido (suspensión de cable); altura regulable sin herramientas; diseñado para sistemas de iluminación continuos, conectores en L para un montaje flexible del sistema; con conductores de cobre trifásicos integrados + 4 conductores de cobre para luz de emergencia (2 circuitos de luz de emergencia SELV) + 2 conductores de cobre DALI para la toma de suministro eléctrico, el suministro eléctrico de emergencia y la señal DALI; corte a medida bajo petición; superficie con recubrimiento de pintura en polvo; montaje flexible y sin herramienta de los insertos, incluyendo adaptador de alta potencia y alimentador; insertos luminosos con distintos modos de proyección, elementos de luz de emergencia (luces de seguridad y de señalización de rutas de rescate) para el funcionamiento con un sistema de baterías centralizado e insertos de sensor incorporables

up to 192 lm/W
(high efficiency)

Order options

CONTROL

DALI-2


MATERIAL COLOUR

● jet black RAL 9005	8
○ traffic white RAL 9016	7

MATERIAL COLOUR CABLE SUSPENSION

black	8
chrome	0

Pole options



— Position of the neutral conductor



MOVE IT PRO emergency SELV surface/suspended



INSTALLATION TRACK 220 V–250 V/440 V | EM 0–60 V

L (mm)		ORDER CODE
1000	channel	086-531113
2000	channel	086-531213
3000	channel	086-531313
4000	channel	086-531413
custom cut	channel	E83840

Accessories

END CAPS

TYPE	ORDER CODE
end cap	086-521011

BLIND COVER

L (mm)		ORDER CODE
1000	blind cover (aluminium)	086-601000
2000	blind cover (aluminium)	086-603000
3000	blind cover (aluminium)	086-605000
25000	blind cover	086-608250

POWER FEEDER WITH EMERGENCY CONDUCTORS

supply 220-250V/440V | EM 0-48V

TYPE	ORDER CODE
end feed poles right	086-541413
end feed poles left	086-541313
middle feed	086-541323

POWER FEEDER WITHOUT EMERGENCY CONDUCTORS

supply 220-250V/440V

TYPE	ORDER CODE
intrack feed (incl. cable 3000 mm)	086-521333

CONNECTORS

TYPE	ORDER CODE
linear connector electrical	086-541113
L-connector poles external	086-541133
L-connector poles internal	086-541233
L-connector mechanical	086-521230






MOUNTING ACCESSORIES

TYPE	ORDER CODE
ceiling fastener	086-521511
suspension bracket	086-521521
linear suspension connector (mechanical)	086-521531
linear connector (mechanical)	086-521110

conductors cutting tool	086-521911
drilling template for indirect inset	086-521951

CABLE SUSPENSION

TYPE	L (mm)	ORDER CODE
cable suspension	1500	086-521711
cable suspension	3000	086-521721
cable suspension	6000	086-521731
connector cable suspension	1500	058-301811
connector cable suspension	3000	058-301821
connector cable suspension	6000	058-301831
tool for connector cable suspension		050-204921




Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
 CRI ≥ 80 , CRI ≥ 90 , 3 SDCM
 UGR ≤ 19 / $65^\circ \leq 1500$ cd/m²
 up to 187 lm/W
 up to 2940 lm/m
 L90 @ 50 000 h
 DALI-2

Types

louver



Colours



Light distribution



super
wide
flood



reddot winner 2024




LOUVER

linear inset

^{EN} Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with symmetrical light distribution; for use in schools and offices; energy-efficient LEDs with very good colour rendering

^{ES} Inserto luminoso lineal de plástico; inserto luminoso con adaptador de alta potencia y alimentador, introducción y desplazamiento sin necesidad de herramienta; enrasado en el sistema de perfiles; reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; precisa característica de emisión con distribución de luz simétrica; para el uso en escuelas y en oficinas; LEDS de alta eficiencia que proporcionan una alta reproducción cromática



DIN EN 12464-1
 UGR ≤ 19



up to 187 lm/W
 (high efficiency)


Order options

COLOUR TEMPERATURE	
2700 K (CRI≥90)	9
3000 K (CRI≥90)	0
3500 K (CRI≥90)	2
4000 K (CRI≥90)	1
2700 K (CRI≥80)	4
3000 K (CRI≥80)	5
3500 K (CRI≥80)	7
4000 K (CRI≥80)	6

CONTROL
DALI-2

LIGHT OPTIC
super wide flood 74°

MATERIAL COLOUR	
chrome reflector	4
black reflector	8



LOUVER inset




REFLECTOR WIDE				
SYSTEM POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
18.4 W	2700 K	2580 lm	1000	0 8 6 - 6 4 1 0 :: 3 X
	3000 K	2580 lm		
	3500 K	2760 lm		
	4000 K	2940 lm		
26.7 W	2700 K	3870 lm	1500	0 8 6 - 6 4 2 0 :: 3 X
	3000 K	3870 lm		
	3500 K	4140 lm		
	4000 K	4400 lm		
34 W	2700 K	5160 lm	2000	0 8 6 - 6 4 3 0 :: 3 X
	3000 K	5160 lm		
	3500 K	5520 lm		
	4000 K	5870 lm		
41 W	2700 K	6450 lm	2500	0 8 6 - 6 4 4 0 :: 3 X
	3000 K	6450 lm		
	3500 K	6890 lm		
	4000 K	7340 lm		
47 W	2700 K	7740 lm	3000	0 8 6 - 6 4 5 0 :: 3 X
	3000 K	7740 lm		
	3500 K	8270 lm		
	4000 K	8810 lm		

LUMINOUS FLUX value calculated for
CRI≥80, CRI≥90 -16 %

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
 CRI ≥ 80 , CRI ≥ 90 , 3 SDCM
 UGR ≤ 19
 up to 189 lm/W
 up to 2900 lm/m
 L90@50 000 h
 DALI-2

Types



Colour



Light distributions



reddot winner 2024



LENS

linear inset

EN Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; equipped with specially computed wallwasher / wide beam lenses; precise radiation characteristic with different light distributions (symmetric / asymmetric); for use in schools and offices; energy-efficient LEDs with very good colour rendering

ES Inserto luminoso lineal de plástico; inserto luminoso con adaptador de alta potencia y alimentador, introducción y desplazamiento sin necesidad de herramienta; enrasado en el sistema de perfiles; equipado con lentes wallwasher / wide beam de diseño especial; proyección precisa con distribuciones de la luz distintas (simétrica/asimétrica); para el uso en escuelas y en oficinas; LEDS de alta eficiencia que proporcionan una alta reproducción cromática



DIN EN 12464-1
 UGR ≤ 19



up to 189 lm/W
 (high efficiency)

Order options

COLOUR TEMPERATURE



2700 K (CRI ≥ 90)	9
3000 K (CRI ≥ 90)	0
3500 K (CRI ≥ 90)	2
4000 K (CRI ≥ 90)	1
2700 K (CRI ≥ 80)	4
3000 K (CRI ≥ 80)	5
3500 K (CRI ≥ 80)	7
4000 K (CRI ≥ 80)	6


CONTROL

DALI-2

LIGHT OPTIC

wide flood 68°

wallwasher



LENS inset



LENS WIDE

SYSTEM POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
18.2W	2700K	2570lm	1000	0 8 6 - 6 7 1 0 :: 3 0 W
	3000K	2570lm		
	3500K	2750lm		
	4000K	2900lm		
26.4W	2700K	3860lm	1500	0 8 6 - 6 7 2 0 :: 3 0 W
	3000K	3860lm		
	3500K	4120lm		
	4000K	4350lm		
33W	2700K	5140lm	2000	0 8 6 - 6 7 3 0 :: 3 0 W
	3000K	5140lm		
	3500K	5500lm		
	4000K	5800lm		
41W	2700K	6430lm	2500	0 8 6 - 6 7 4 0 :: 3 0 W
	3000K	6430lm		
	3500K	6870lm		
	4000K	7240lm		
46W	2700K	7720lm	3000	0 8 6 - 6 7 5 0 :: 3 0 W
	3000K	7720lm		
	3500K	8250lm		
	4000K	8690lm		


LENS WALLWASHER

SYSTEM POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
18.2W	2700K	2190lm	1000	0 8 6 - 6 7 1 0 :: 3 0 A
	3000K	2190lm		
	3500K	2340lm		
	4000K	2470lm		
26.4W	2700K	3280lm	1500	0 8 6 - 6 7 2 0 :: 3 0 A
	3000K	3280lm		
	3500K	3510lm		
	4000K	3700lm		
33W	2700K	4380lm	2000	0 8 6 - 6 7 3 0 :: 3 0 A
	3000K	4380lm		
	3500K	4680lm		
	4000K	4930lm		
41W	2700K	5470lm	2500	0 8 6 - 6 7 4 0 :: 3 0 A
	3000K	5470lm		
	3500K	5850lm		
	4000K	6170lm		
46W	2700K	6570lm	3000	0 8 6 - 6 7 5 0 :: 3 0 A
	3000K	6570lm		
	3500K	7020lm		
	4000K	7400lm		

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI $\geq$ 80, CRI $\geq$ 90, 3 SDCM
up to 173 lm/W
up to 7930 lm/m
L90 @ 50 000 h
DALI-2

Types



Colour



Light distributions



reddot winner 2024



LENS SHELF

linear inset

EN Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; equipped with specially computed shelf floor washer / wide shelf floor washer lenses; precise radiation characteristic with different light distributions (symmetric); for use in retail; energy-efficient LEDs with very good colour rendering

ES Inserto luminoso lineal de plástico; inserto luminoso con adaptador de alta potencia y alimentador, introducción y desplazamiento sin necesidad de herramienta; enrasado en el sistema de perfiles; equipado con lentes shelf floor washer / wide shelf floor washer de diseño especial; proyección precisa con distribuciones de la luz distintas (simétrica); para el uso en tiendas y; LEDs de alta eficiencia que proporcionan una alta reproducción cromática



up to 173 lm/W
(high efficiency)

Order options

COLOUR TEMPERATURE

2700 K (CRI $\geq$ 90)	9
3000 K (CRI $\geq$ 90)	0
3500 K (CRI $\geq$ 90)	2
4000 K (CRI $\geq$ 90)	1
2700 K (CRI $\geq$ 80)	4
3000 K (CRI $\geq$ 80)	5
3500 K (CRI $\geq$ 80)	7
4000 K (CRI $\geq$ 80)	6

CONTROL


DALI-2

LIGHT OPTIC

shelf floor washer 20°	S
wide shelf floor washer 30°	W



LENS SHELF inset



LOW POWER

SYSTEM POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
22.2W	2700K	3270lm	1000	0 8 6 - 6 9 1 0 :: 3 0 ▲
	3000K	3270lm		
	3500K	3490lm		
	4000K	3720lm		
33W	2700K	4900lm	1500	0 8 6 - 6 9 2 0 :: 3 0 ▲
	3000K	4900lm		
	3500K	5240lm		
	4000K	5580lm		
43W	2700K	6540lm	2000	0 8 6 - 6 9 3 0 :: 3 0 ▲
	3000K	6540lm		
	3500K	6990lm		
	4000K	7440lm		

MID POWER

SYSTEM POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
33W	2700K	4840lm	1000	0 8 6 - 6 9 1 3 :: 3 0 ▲
	3000K	4840lm		
	3500K	5170lm		
	4000K	5510lm		
47W	2700K	7260lm	1500	0 8 6 - 6 9 2 3 :: 3 0 ▲
	3000K	7260lm		
	3500K	7760lm		
	4000K	8260lm		

HIGH POWER


SYSTEM POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
33W	2700K	6970lm	1000	0 8 6 - 6 9 1 6 :: 3 0 ▲
	3000K	6970lm		
	3500K	7450lm		
	4000K	7930lm		

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
 CRI ≥ 80 , CRI ≥ 90 , 3 SDCM
 UGR $\leq 16, 19 / 65^\circ \leq 1500 \text{ cd/m}^2$
 up to 183 lm/W
 up to 2870 lm/m
 L90 @ 50 000 h
 DALI-2

Types

spot line



Colours



Light distributions



reddot winner 2024




SPOT LINE

linear inset

EN Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with medium or wide flood radiation characteristic; for use in schools, retail and offices; energy-efficient LEDs with very good colour rendering

ES Inserto luminoso lineal de plástico; inserto luminoso con adaptador de alta potencia y alimentador, introducción y desplazamiento sin necesidad de herramienta; enrasado en el sistema de perfiles; equipado con puntos de luz LED individuales; buen control del deslumbramiento mediante plano de punto de luz retranqueado; se ha incrementado la eficiencia debido al uso de la última tecnología en el diseño de lentes; lentes aplicadas con característica de proyección media o wide flood; para el uso en escuelas, en tiendas y en oficinas; LEDS de alta eficiencia que proporcionan una alta reproducción cromática



DIN EN 12464-1
 UGR ≤ 16



up to 183 lm/W
 (high efficiency)

Order options

COLOUR TEMPERATURE

2700 K (CRI ≥ 90)	9
3000 K (CRI ≥ 90)	0
3500 K (CRI ≥ 90)	2
4000 K (CRI ≥ 90)	1
2700 K (CRI ≥ 80)	4
3000 K (CRI ≥ 80)	5
3500 K (CRI ≥ 80)	7
4000 K (CRI ≥ 80)	6

CONTROL


DALI-2

LIGHT OPTIC

medium 28°	M
wide flood 67°	W

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8
● gold	9



SPOT LINE inset




SPOT LINE

SYSTEM POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
18.4 W	2700 K	2460 lm	1000	0 8 6 - 6 3 1 0 :: 3 
	3000 K	2460 lm		
	3500 K	2630 lm		
	4000 K	2800 lm		
26.7 W	2700 K	3700 lm	1500	0 8 6 - 6 3 2 0 :: 3 
	3000 K	3700 lm		
	3500 K	3950 lm		
	4000 K	4210 lm		
34 W	2700 K	4930 lm	2000	0 8 6 - 6 3 3 0 :: 3 
	3000 K	4930 lm		
	3500 K	5270 lm		
	4000 K	5610 lm		
41 W	2700 K	6160 lm	2500	0 8 6 - 6 3 4 0 :: 3 
	3000 K	6160 lm		
	3500 K	6580 lm		
	4000 K	7010 lm		
47 W	2700 K	7390 lm	3000	0 8 6 - 6 3 5 0 :: 3 
	3000 K	7390 lm		
	3500 K	7900 lm		
	4000 K	8410 lm		

Quickinfo

2700K, 3000K, 3500K, 4000K
CRI ≥ 80, CRI ≥ 90, 3 SDCM
up to 152lm/W
up to 2330lm/m
L90 @ 50 000h
DALI-2

Types



Colours



Light distribution



reddot winner 2024



DESIGN
AWARD
2024

OPAL

linear inset

EN Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush or 12mm protruding in the profile system; equipped with specially computed lenses; homogeneously illuminated, satinised PMMA cover; energy-efficient LEDs with very good colour rendering


ES Inserto luminoso lineal de plástico; inserto luminoso con adaptador de alta potencia y alimentador, introducción y desplazamiento sin necesidad de herramienta; montaje empotrado o 12 mm sobresaliente en el sistema de perfiles; equipado con lentes de diseño especial; tapa PMMA iluminada homogéneamente con acabado satinado; LEDS de alta eficiencia que proporcionan una alta reproducción cromática



opal



opal jut-out



continuous
cover



up to 152 lm/W
(high efficiency)

Order options

COLOUR TEMPERATURE

2700 K (CRI ≥ 90)	9
3000 K (CRI ≥ 90)	0
3500 K (CRI ≥ 90)	2
4000 K (CRI ≥ 90)	1
2700 K (CRI ≥ 80)	4
3000 K (CRI ≥ 80)	5
3500 K (CRI ≥ 80)	7
4000 K (CRI ≥ 80)	6

CONTROL


DALI-2

LIGHT OPTIC


opal

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8



OPAL inset



LIGHT INSET

SYSTEM POWER	COLOUR TEMP.	LUM. FLUX (flush)	LUM. FLUX (jut-out)	L (mm)	ORDER CODE
18.2W	2700K	2050lm	2210lm	1000	0 8 6 - 6 1 1 0 :: 30
	3000K	2050lm	2210lm		
	3500K	2190lm	2360lm		
	4000K	2330lm	2510lm		
26.4W	2700K	3070lm	3310lm	1500	0 8 6 - 6 1 2 0 :: 30
	3000K	3070lm	3310lm		
	3500K	3280lm	3540lm		
	4000K	3490lm	3770lm		
33W	2700K	4090lm	4420lm	2000	0 8 6 - 6 1 3 0 :: 30
	3000K	4090lm	4420lm		
	3500K	4370lm	4720lm		
	4000K	4660lm	5030lm		
41W	2700K	5110lm	5520lm	2500	0 8 6 - 6 1 4 0 :: 30
	3000K	5110lm	5520lm		
	3500K	5470lm	5900lm		
	4000K	5820lm	6280lm		
46W	2700K	6140lm	6630lm	3000	0 8 6 - 6 1 5 0 :: 30
	3000K	6140lm	6630lm		
	3500K	6560lm	7080lm		
	4000K	6980lm	7540lm		

Accessories

END CAPS

TYPE	ORDER CODE
opal	0 8 6 - 6 0 9 1 1 1 ■
opal jut-out	0 8 6 - 6 0 9 1 3 1 ■

COVER


TYPE	L (mm)	ORDER CODE
continuous opal cover	6000	0 8 6 - 6 0 8 0 6 0 0 0
continuous opal cover	25000	0 8 6 - 6 0 8 2 5 0 0 0
opal cover	999	0 8 6 - 6 0 1 0 0 0 0 0
opal cover	1499	0 8 6 - 6 0 2 0 0 0 0 0
opal cover	1999	0 8 6 - 6 0 3 0 0 0 0 0
opal cover	2498	0 8 6 - 6 0 4 0 0 0 0 0
opal cover	2998	0 8 6 - 6 0 5 0 0 0 0 0
opal jut-out cover	999	0 8 6 - 6 0 5 0 0 0 0 J
opal jut-out cover	1499	0 8 6 - 6 0 2 0 0 0 0 J
opal jut-out cover	1999	0 8 6 - 6 0 3 0 0 0 0 J
opal jut-out cover	2498	0 8 6 - 6 0 4 0 0 0 0 J
opal jut-out cover	2998	0 8 6 - 6 0 5 0 0 0 0 J

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
 CRI ≥ 80 , CRI ≥ 90 , 3 SDCM
 UGR ≤ 19 / $65^\circ \leq 3000$ cd/m²
 up to 129 lm/W
 up to 1940 lm/m
 L90 @ 50 000 h
 DALI-2

Types

microprismatic



Colours



Light distribution



micropr.



reddot winner 2024




DESIGN
AWARD
2024

MICROPRISMATIC

linear inset

^{EN} Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; completely homogeneously illuminated, microprismatic PMMA cover; for use in offices; energy-efficient LEDs with very good colour rendering

^{ES} Inserto luminoso lineal de plástico; inserto luminoso con adaptador de alta potencia y alimentador, introducción y desplazamiento sin necesidad de herramienta; enrasado en el sistema de perfiles; difusor microprismático de PMMA de iluminación totalmente homogénea; para el uso en oficinas; LEDS de alta eficiencia que proporcionan una alta reproducción cromática



continuous
cover



up to 129 lm/W
(high efficiency)

Order options

COLOUR TEMPERATURE

2700 K (CRI $\geq$ 90)	9
3000 K (CRI $\geq$ 90)	0
3500 K (CRI $\geq$ 90)	2
4000 K (CRI $\geq$ 90)	1
2700 K (CRI $\geq$ 80)	4
3000 K (CRI $\geq$ 80)	5
3500 K (CRI $\geq$ 80)	7
4000 K (CRI $\geq$ 80)	6

CONTROL



DALI-2

LIGHT OPTIC

microprismatic

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8



MICROPRISMATIC inset

LIGHT INSET UGR $\leq$ 22

SYSTEM POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
18.2 W	3000K	1710lm	1000	0 8 6 - 6 1 1 0 : 3 0
	4000K	1940lm		
26.4 W	3000K	2560lm	1500	0 8 6 - 6 1 2 0 : 3 0
	4000K	2910lm		
33 W	3000K	3420lm	2000	0 8 6 - 6 1 3 0 : 3 0
	4000K	3890lm		
41 W	3000K	4270lm	2500	0 8 6 - 6 1 4 0 : 3 0
	4000K	4860lm		
46 W	3000K	5120lm	3000	0 8 6 - 6 1 5 0 : 3 0
	4000K	5830lm		

LIGHT INSET UGR $\leq$ 19

SYSTEM POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
8 W	3000K	768lm	1000	0 8 6 - 6 2 1 0 : 3 0
	4000K	873lm		
11.6 W	3000K	1150lm	1500	0 8 6 - 6 2 2 0 : 3 0
	4000K	1310lm		
14.7 W	3000K	1540lm	2000	0 8 6 - 6 2 3 0 : 3 0
	4000K	1750lm		
17.9 W	3000K	1920lm	2500	0 8 6 - 6 2 4 0 : 3 0
	4000K	2180lm		
20.3 W	3000K	2300lm	3000	0 8 6 - 6 2 5 0 : 3 0
	4000K	2620lm		

Accessories

END CAPS

TYPE

end caps pair for microprismatic

ORDER CODE

0 8 6 - 6 0 9 1 1 1

COVER

TYPE

continuous microprismatic cover
continuous microprismatic cover
microprismatic cover
microprismatic cover
microprismatic cover
microprismatic cover
microprismatic cover

L (mm)

6000
25000
999
1499
1999
2498
2998

ORDER CODE


0 8 6 - 6 0 8 0 6 0 0 P
0 8 6 - 6 0 8 2 5 0 0 P
0 8 6 - 6 0 1 0 0 0 0 P
0 8 6 - 6 0 2 0 0 0 0 P
0 8 6 - 6 0 3 0 0 0 0 P
0 8 6 - 6 0 4 0 0 0 0 P
0 8 6 - 6 0 5 0 0 0 0 P

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
 CRI $\geq$ 80, CRI $\geq$ 90, 3 SDCM
 up to 162 lm/W
 up to 3400 lm/m
 L90 @ 50 000 h
 DALI-2

Types

indirect



Colour



Light distribution



indirect



reddot winner 2024




DESIGN
AWARD
2024

INDIRECT

linear inset

EN Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; with indirect light component for additional accentuation of the ceiling; high quality lens system for maximum, homogeneous ceiling illumination; energy-efficient LEDs with very good colour rendering

ES Inserto luminoso lineal de plástico; inserto luminoso con adaptador de alta potencia y alimentador, introducción y desplazamiento sin necesidad de herramienta; enrasado en el sistema de perfiles; con componentes de luz indirectos para el realce adicional del techo; óptica de lente exclusiva para una iluminación máxima y homogénea del techo; LEDS de alta eficiencia que proporcionan una alta reproducción cromática



170° indirect
illumination

Order options

COLOUR TEMPERATURE


2700 K (CRI $\geq$ 90)	9
3000 K (CRI $\geq$ 90)	0
3500 K (CRI $\geq$ 90)	2
4000 K (CRI $\geq$ 90)	1
2700 K (CRI $\geq$ 80)	4
3000 K (CRI $\geq$ 80)	5
3500 K (CRI $\geq$ 80)	7
4000 K (CRI $\geq$ 80)	6

CONTROL

DALI-2

LIGHT OPTIC

batwing



INDIRECT inset



INDIRECT BATWING LOW POWER

SYSTEM POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
17.7 W	2700 K	2240 lm	1472	0 8 6 - 6 8 2 0 :: 30 B
	3000 K	2240 lm		
	3500 K	2400 lm		
	4000 K	2550 lm		
32 W	2700 K	4480 lm	2942	0 8 6 - 6 8 5 0 :: 30 B
	3000 K	4480 lm		
	3500 K	4790 lm		
	4000 K	5100 lm		
47 W	2700 K	6720 lm	4412	0 8 6 - 6 8 8 0 :: 30 B
	3000 K	6720 lm		
	3500 K	7190 lm		
	4000 K	7650 lm		

INDIRECT BATWING HIGH POWER

SYSTEM POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
24.3 W	2700 K	2990 lm	982	0 8 6 - 6 8 1 5 :: 30 B
	3000 K	2990 lm		
	3500 K	3190 lm		
	4000 K	3400 lm		
43 W	2700 K	5980 lm	1962	0 8 6 - 6 8 3 5 :: 30 B
	3000 K	5980 lm		
	3500 K	6390 lm		
	4000 K	6800 lm		

Accessories



MOUNTING ACCESSORIES

TYPE	ORDER CODE
drilling template for indirect inset	0 8 6 - 5 2 1 9 5 1 0


INDIRECT EXTENSION

SYSTEM POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
2.6 W low power	2700 K	374 lm	245	0 8 6 - 6 8 0 0 :: 30 B
	3000 K	374 lm		
	3500 K	399 lm		
	4000 K	425 lm		
5.4 W high power	2700 K	747 lm	245	0 8 6 - 6 8 0 5 :: 30 B
	3000 K	747 lm		
	3500 K	799 lm		
	4000 K	850 lm		

max. inset length per driver: low power 4500 mm, high power 2000 mm
without power supply

Example for extension

1500 mm Scope of delivery low power PCBA




Extension by 250 mm PCBA (new total length 1750 mm)

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90, 2 SDCM
up to 111lm/W
L80 @ 50 000 h
DALI-2

Types



Colours



Light distribution



reddot winner 2024




NOBA

decorative inset

EN Decorative pendant light inset made of aluminium; choice of single lamp, double lamps or triple lamp; light inset, incl. high power adapter + converter can be installed flexibly and without tools; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

ES Elemento de luz decorativo de aluminio para luminarias de suspensión; disponible con flujo de luz simple, doble o triple; inserto luminoso con adaptador de alta potencia y alimentador, introducción y desplazamiento sin necesidad de herramienta; superficie de cromo pulido, aluminio cepillado o recubierta por pulverización; suspendido con pendular, incl. cable de alimentación (negro); se puede acortar; lente de cristal plano-convexa alta calidad; no sombras múltiples; LEDs de alta eficiencia que proporcionan una alta reproducción cromática; anillos de montaje en techo disponibles opcionalmente para el posicionamiento múltiple de la luminaria en la sala



free positioning
by cable and hook



high quality
glass lens

Order options

MOUNTING

suspension 2000 mm

COLOUR TEMPERATURE

2700K	9
3000K	0
3500K	2
4000K	1

CONTROL

DALI-2

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8
● brushed aluminium	6
● chrome	4
● gun metal	5
● brushed brass	3
● rose gold	9

MATERIAL COLOUR


ACCESSORIES / DRIVER

○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE


wide flood 67°

NOBA 60




DOWNLIGHT 1 LAMP

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
14.1W	2700K	1040lm	086-7110033W
	3000K	1090lm	
	3500K	1140lm	
	4000K	1170lm	



DOWNLIGHT 2 LAMPS

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
28.2W	2700K	2080lm	086-711033W
	3000K	2180lm	
	3500K	2280lm	
	4000K	2340lm	



DOWNLIGHT 3 LAMPS

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
41W	2700K	3120lm	086-712033W
	3000K	3270lm	
	3500K	3410lm	
	4000K	3510lm	

Mounting accessories



HOOK ceiling mounted

TYPE	Ø-H (mm)	ORDER CODE
hook	16-30	030-100001



reddot winner 2024



ARY

decorative inset


EN Decorative pendant light inset made of aluminium; choice of single lamp, double lamps or triple lamp; light inset, incl. high power adapter + converter can be installed flexibly and without tools; surface powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; good glare reduction due to recessed light point plane; incl. high quality lens system; precise radiation characteristics with different beam angles; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

ES Elemento de luz decorativo de aluminio para luminarias de suspensión; disponible con flujo de luz simple, doble o triple; inserto luminoso con adaptador de alta potencia y alimentador, introducción y desplazamiento sin necesidad de herramienta; superficie con recubrimiento de pintura en polvo; suspendido con pendular, incl. cable de alimentación (negro o blanco); se puede acortar; buen control del deslumbramiento mediante plano de punto de luz retranqueado; incluida óptica de alta calidad; característica de emisión precisa con diferentes ángulos de emisión; pantallas en colores RAL velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white o signal black disponibles como accesorio; con tecnología COB (Chip on Board) para proporcionar una máxima eficiencia; no sombras múltiples; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; anillos de montaje en techo disponibles opcionalmente para el posicionamiento múltiple de la luminaria en la sala

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90, 3 SDCM
up to 86 lm/W
L90 @ 50 000 h
non DIM, DALI-2


Types



Colours



Light distributions



free positioning
by ring and hook

Order options

MOUNTING

suspension 2000 mm

COLOUR TEMPERATURE

2700 K	9
3000 K	0
3500 K	2
4000 K	1

CONTROL

DALI-2

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8
● special colours*	X

*cable and driver always in black

MATERIAL COLOUR ACCESSORIES / DRIVER

○ traffic white RAL 9016	7
● jet black RAL 9005	8


BEAM ANGLE

medium 25°	M
flood 44°	F

SHADE COLOUR


● velvet beige RAL 085 80 10	C
● madeira brown RAL 050 40 40	T
● kingfisher grey RAL 230 60 10	L
● woodpecker olive RAL 10 50 20	G
○ signal white RAL 9003	W
● signal black RAL 9004	B

ARY




DOWNLIGHT 1 LAMP

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
14.1 W	2700 K	1390 lm	086-7300:3
	3000 K	1450 lm	
	3500 K	1520 lm	
	4000 K	1560 lm	



DOWNLIGHT 2 LAMPS

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
28.2 W	2700 K	2780 lm	086-7310:3
	3000 K	2910 lm	
	3500 K	3040 lm	
	4000 K	3130 lm	



DOWNLIGHT 3 LAMPS


INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
41 W	2700 K	4170 lm	086-7320:3
	3000 K	4360 lm	
	3500 K	4560 lm	
	4000 K	4690 lm	

Mounting accessories



TYPE	Ø-H (mm)	ORDER CODE
ring ceiling mounted	50-88	050-051021
hook	18-58	050-051031

Optical accessories



SHADE

TYPE	Ø-H (mm)	ORDER CODE
cone 300	300-188	049-593311
cone 400	400-253	049-593411
cone 500	500-318	049-593511

only for one lamp


LUMINOUS FLUX value calculated for
medium

Quickinfo

sensor
ESSENTIAL, SENSE
DALI-2

Type

sensor



Inset colours



Sensors



essen- sense
tial



reddot winner 2024



SENSOR

inset

^{EN} Sensor inset; choice of ESSENTIAL or SENSE; ESSENTIAL: brightness and presence sensor; SENSE: brightness, presence, temperature, humidity, air quality and noise level sensor; flush with profile system

^{ES} Inserto de sensor; ESSENTIAL o SENSE a elegir; ESSENTIAL: sensor de luminosidad y presencia; SENSE: sensor de luminosidad, presencia, temperatura, humedad/calidad del aire y nivel de ruido; enrasado en el sistema de perfiles

Order options


CONTROL

DALI-2

INSET COLOUR

- ☐ traffic white RAL 9016
- ☐ jet black RAL 9005

7
8



SENSOR inset



ESSENTIAL SENSOR

TYPE
brightness & presence

ORDER CODE
086-521811



SENSE SENSOR

TYPE
brightness, presence, temperature,
sound pressure, humidity, CO₂

ORDER CODE
086-521812