




NOBA

multi linear suspended


EN Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; linear ceiling surface mounted canopy (black or white) optionally for two to five lamps fittings; high quality plano-convex glass lens; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

ES Luminaria suspendida decorativa fabricada en aluminio; superficie de cromo pulido, aluminio cepillado o recubierta por pulverización; suspendido con pendular, incl. cable de alimentación (negro o blanco); se puede acortar; base de techo lineal (blanca o negra) de montaje en superficie para la instalación de dos a cinco lámparas; lente de cristal plano-convexa alta calidad; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; baldaquino para cableado pasante; convertidor integrado en el baldaquino; anillos de montaje en techo disponibles opcionalmente para el posicionamiento múltiple de la luminaria en la sala

Quickinfo

2700 K, 3000 K, 4000 K
CRI ≥ 90
up to 158 lm/W
L90 @ 50 000 h
DALI-2, Casambi

Type



Canopy colours



standard


Luminaire colours



Light distribution



direct



free positioning by
cable and hook



high quality
glass lens

Order options

COLOUR TEMPERATURE

2700 K	9
3000 K	0
4000 K	1

CONTROL

DALI-2	3
Casambi	9

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8
● brushed aluminium	6
● chrome	4
● gun metal	5
● brushed brass	3
● rose gold	9

CABLE COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8





MATERIAL COLOUR

CANOPY/ACCESSORIES

○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE

wide flood 67°




NOBA multi linear suspended

CANOPY 220-240 V AC, 50-60 Hz, ⚡ PC I

TYPE	INSETS	L-W-H (mm)	ORDER CODE
300 mA	2-5 insets	1000-34-50	0 0 5 - 2 6 9 2 0

NOBA 40



DIRECT

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
2.4 W	2700 K	326 lm	0 4 9 - 5 4 1 0
	3000 K	322 lm	1 7 1 W
	4000 K	352 lm	

NOBA 50



DIRECT

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
2.4 W	2700 K	345 lm	0 4 9 - 5 4 1 3
	3000 K	342 lm	1 7 1 W
	4000 K	374 lm	

NOBA 60



DIRECT

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
2.4 W	2700 K	356 lm	0 4 9 - 5 4 1 6
	3000 K	352 lm	1 7 1 W
	4000 K	385 lm	

Mounting accessories

HOOK ceiling mounted

TYPE	Ø-H (mm)	ORDER CODE
hook	16-30	0 3 0 - 1 0 0 0 1

INSET POWER is the current consumption excluding any ballast

LUMINOUS FLUX value calculated for CRI ≥ 90, colour white



NOBA

multi round suspended


EN Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; round ceiling surface mounted canopy (black or white) optionally for two to five lamps or two to ten lamps fittings; high quality plano-convex glass lens; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

ES Luminaria suspendida decorativa fabricada en aluminio; superficie de cromo pulido, aluminio cepillado o recubierta por pulverización; suspendido con pendular, incl. cable de alimentación (negro o blanco); se puede acortar; base de techo redonda (blanca o negra) de montaje en superficie para la instalación de dos a cinco o de dos a diez lámparas; lente de cristal plano-convexa alta calidad; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; baldaquino para cableado pasante; convertidor integrado en el baldaquino; anillos de montaje en techo disponibles opcionalmente para el posicionamiento múltiple de la luminaria en la sala

Quickinfo

2700 K, 3000 K, 4000 K
CRI ≥ 90
up to 158 lm/W
L90 @ 50 000 h
DALI-2, Casambi

Type



Canopy colours



standard


Luminaire colours



Light distribution



direct



free positioning by
cable and hook



high quality
glass lens

Order options

COLOUR TEMPERATURE

2700 K	9
3000 K	0
4000 K	1

CONTROL

DALI-2	3
Casambi	9

COVER

with slots	0
without slots	1

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8
● brushed aluminium	6
● chrome	4
● gun metal	5
● brushed brass	3
● rose gold	9

CABLE COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8


MATERIAL COLOUR

CANOPY/ACCESSORIES

○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE

wide flood 67°




NOBA multi round suspended

CANOPY 220-240 V AC, 50-60 Hz, PC I


TYPE	INSETS	Ø-H (mm)	ORDER CODE
300 mA	2-5 insets	380-43	0 0 5 - 2 6 9 0
2×300 mA	2-10 insets	380-43	0 0 5 - 2 6 9 1

*1 DALI address; **2 converter a 300 mA, 2 DALI addresses




DIRECT

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
2.4 W	2700 K	326 lm	0 4 9 - 5 4 1 0
	3000 K	322 lm	1 7 4 W
	4000 K	352 lm	



DIRECT

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
2.4 W	2700 K	345 lm	0 4 9 - 5 4 1 3
	3000 K	342 lm	1 7 4 W
	4000 K	374 lm	



DIRECT

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
2.4 W	2700 K	356 lm	0 4 9 - 5 4 1 6
	3000 K	352 lm	1 7 4 W
	4000 K	385 lm	

Mounting accessories

HOOK ceiling mounted

TYPE	Ø-H (mm)	ORDER CODE
hook	16-30	0 3 0 - 1 0 0 0 1



INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour white