



## NOBA

multi linear suspended


<sup>EN</sup> Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; linear ceiling surface mounted canopy (black or white) optionally for two to five lamps fittings; high quality plano-convex glass lens; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

Apparecchio a sospensione decorativo in alluminio; superficie cromata lucida, alluminio spazzolato o verniciata a polvere; sospeso con cavo a sospensione, incl. cavo di alimentazione (nero o bianco); accorciabile a piacere; rosone lineare per montaggio a soffitto (nero o bianco) a scelta per apparecchi da due a cinque luci; lente di vetro piano-convesso di qualità; LED ad efficienza energetica con elevata resa cromatica; rosone per cablaggio passante; convertitore integrato nel rosone; anelli di montaggio a soffitto per posizionare la lampada in più punti dell'ambiente disponibili come accessori

### Quickinfo

2700 K, 3000 K, 4000 K  
CRI ≥ 90  
up to 158 lm/W  
L90 @ 50 000 h  
DALI-2, Casambi

### Type



### Canopy colours



standard


### Luminaire colours



### Light distribution



direct



free positioning by  
cable and hook



high quality  
glass lens

## Order options

## COLOUR TEMPERATURE

|        |   |
|--------|---|
| 2700 K | 9 |
| 3000 K | 0 |
| 4000 K | 1 |

## CONTROL

|         |   |
|---------|---|
| DALI-2  | 3 |
| Casambi | 9 |

## MATERIAL COLOUR

|                          |   |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005     | 8 |
| ● brushed aluminium      | 6 |
| ● chrome                 | 4 |
| ● gun metal              | 5 |
| ● brushed brass          | 3 |
| ● rose gold              | 9 |

## CABLE COLOUR

|                          |   |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005     | 8 |


## MATERIAL COLOUR

## CANOPY/ACCESSORIES

|                          |   |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005     | 8 |

## BEAM ANGLE


wide flood 67°



## NOBA multi linear suspended

CANOPY 220-240 V AC, 50-60 Hz, ⚡ PC I

| TYPE   | INSETS     | L-W-H (mm) | ORDER CODE          |
|--------|------------|------------|---------------------|
| 300 mA | 2-5 insets | 1000-34-50 | 0 0 5 - 2 6 9 2 0 ▢ |




## NOBA 40



## DIRECT

| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE                 |
|-------------|--------------|---------------|----------------------------|
| 2.4 W       | 2700 K       | 326 lm        | 0 4 9 - 5 4 1 0 :: 1 ▢ ▢ W |
|             | 3000 K       | 322 lm        |                            |
|             | 4000 K       | 352 lm        |                            |




## NOBA 50



## DIRECT

| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE                 |
|-------------|--------------|---------------|----------------------------|
| 2.4 W       | 2700 K       | 345 lm        | 0 4 9 - 5 4 1 3 :: 1 ▢ ▢ W |
|             | 3000 K       | 342 lm        |                            |
|             | 4000 K       | 374 lm        |                            |



## NOBA 60



## DIRECT

| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE                 |
|-------------|--------------|---------------|----------------------------|
| 2.4 W       | 2700 K       | 356 lm        | 0 4 9 - 5 4 1 6 :: 1 ▢ ▢ W |
|             | 3000 K       | 352 lm        |                            |
|             | 4000 K       | 385 lm        |                            |

## Mounting accessories



HOOK ceiling mounted

| TYPE | Ø-H (mm) | ORDER CODE          |
|------|----------|---------------------|
| hook | 16-30    | 0 3 0 - 1 0 0 0 1 ▢ |

**INSET POWER** is the current consumption excluding any ballast  
**LUMINOUS FLUX** value calculated for CRI ≥ 90, colour white



## NOBA

multi round suspended


**EN** Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; round ceiling surface mounted canopy (black or white) optionally for two to five lamps or two to ten lamps fittings; high quality plano-convex glass lens; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

**IT** Apparecchio a sospensione decorativo in alluminio; superficie cromata lucida, alluminio spazzolato o verniciata a polvere; sospeso con cavo a sospensione, incl. cavo di alimentazione (nero o bianco); accorciabile a piacere; rosone rotondo per montaggio a soffitto (nero o bianco) a scelta per apparecchi da due a cinque luci o da due a dieci luci; lente di vetro piano-convesso di qualità; LED ad efficienza energetica con elevata resa cromatica; rosone per cablaggio passante; convertitore integrato nel rosone; anelli di montaggio a soffitto per posizionare la lampada in più punti dell'ambiente disponibili come accessori

### Quickinfo

2700 K, 3000 K, 4000 K  
CRI ≥ 90  
up to 158 lm/W  
L90 @ 50 000 h  
DALI-2, Casambi

### Type



### Canopy colours



standard


### Luminaire colours



### Light distribution



direct



free positioning by  
cable and hook



high quality  
glass lens

## Order options

## COLOUR TEMPERATURE

|        |   |
|--------|---|
| 2700 K | 9 |
| 3000 K | 0 |
| 4000 K | 1 |

## CONTROL

|         |   |
|---------|---|
| DALI-2  | 3 |
| Casambi | 9 |

## COVER

|               |   |
|---------------|---|
| with slots    | 0 |
| without slots | 1 |

## MATERIAL COLOUR

|                          |   |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005     | 8 |
| ● brushed aluminium      | 6 |
| ● chrome                 | 4 |
| ● gun metal              | 5 |
| ● brushed brass          | 3 |
| ● rose gold              | 9 |

## CABLE COLOUR

|                          |   |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005     | 8 |

## MATERIAL COLOUR


## CANOPY/ACCESSORIES

|                          |   |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005     | 8 |

## BEAM ANGLE

wide flood 67°

ø 380 43




## NOBA multi round suspended

CANOPY 220-240 V AC, 50-60 Hz, PC I


| TYPE     | INSETS      | Ø-H (mm) | ORDER CODE        |
|----------|-------------|----------|-------------------|
| 300 mA   | 2-5 insets  | 380-43   | 0 0 5 - 2 6 9 0 1 |
| 2×300 mA | 2-10 insets | 380-43   | 0 0 5 - 2 6 9 1 1 |

\*1 DALI address; \*\*2 converter a 300 mA, 2 DALI addresses




## DIRECT

| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE          |
|-------------|--------------|---------------|---------------------|
| 2.4 W       | 2700 K       | 326 lm        | 0 4 9 - 5 4 1 0 1 1 |
|             | 3000 K       | 322 lm        |                     |
|             | 4000 K       | 352 lm        |                     |



## DIRECT

| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE          |
|-------------|--------------|---------------|---------------------|
| 2.4 W       | 2700 K       | 345 lm        | 0 4 9 - 5 4 1 3 1 1 |
|             | 3000 K       | 342 lm        |                     |
|             | 4000 K       | 374 lm        |                     |



## DIRECT

| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE          |
|-------------|--------------|---------------|---------------------|
| 2.4 W       | 2700 K       | 356 lm        | 0 4 9 - 5 4 1 6 1 1 |
|             | 3000 K       | 352 lm        |                     |
|             | 4000 K       | 385 lm        |                     |

## Mounting accessories

HOOK ceiling mounted

| TYPE | Ø-H (mm) | ORDER CODE          |
|------|----------|---------------------|
| hook | 16-30    | 0 3 0 - 1 0 0 0 1 1 |



**INSET POWER** is the current consumption excluding any ballast  
**LUMINOUS FLUX** value calculated for CRI ≥ 90, colour white