




REVO

wall surface

EN Rectangular wall surface mounted luminaire made from aluminium, available in different sizes; surface raw or powder coated; converter integrated into luminaire housing; with high quality lens system with precise radiation characteristic; homogeneous wall or ceiling illumination through uniform light distribution; energy-efficient high power LEDs with very good colour rendering; luminaire for through wiring

ES Luminaria rectangular de aluminio en distintos tamaños para montaje sobre pared; superficie sin tratar o recubierta por pulverización; convertidor integrado en el cuerpo luminoso; sistema óptico de lentes de alta calidad con precisa característica de emisión; iluminación homogénea de la pared o bien del techo mediante distribución uniforme de la luz; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; luminaria para cableado pasante



slim design




homogeneous ceiling illumination

Quickinfo

2700K, 3000K, 3500K, 4000K
 CRI ≥ 90, 2 SDCM
 up to 3900lm | up to 130lm/W
 L90@50000h
 non DIM, DALI-2

Types



Colours



Light distribution




Order options

COLOUR TEMPERATURE	
2700K	9
3000K	0
3500K	2
4000K	1

CONTROL	
non DIM	1
DALI-2	3


MATERIAL COLOUR	
○ traffic white RAL 9016	7
● jet black RAL 9005	1
● raw aluminium	0

REVO 150 wall surface



INDIRECT		ORDER CODE	
SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	
23.6W	2700K	2260lm	058-71110
	3000K	2330lm	
	3500K	2260lm	
	4000K	2450lm	

REVO 180 wall surface



INDIRECT		ORDER CODE	
SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	
30.1W	2700K	3680lm	058-71140
	3000K	3680lm	
	3500K	3830lm	
	4000K	3910lm	

LUMINOUS FLUX value calculated for CRI ≥ 90, colour white