



REVO

xal.com/revo




REVO

wall surface

EN Rectangular wall surface mounted luminaire made from aluminium, available in different sizes; surface raw or powder coated; converter integrated into luminaire housing; with high quality lens system with precise radiation characteristic; homogeneous wall or ceiling illumination through uniform light distribution; energy-efficient high power LEDs with very good colour rendering; luminaire for through wiring

FR Applique murale rectangulaire en aluminium, disponible en différentes tailles ; surface brute ou thermolaquée ; convertisseur intégré dans le corps de luminaire ; avec une optique de lentilles de haute qualité présentant des caractéristiques de rayonnement précises ; éclairage homogène du mur ou du plafond par une distribution de lumière uniforme ; High-Power-LED à grande efficacité énergétique, très bon rendu des couleurs ; luminaire pour câblage continu



slim design




homogeneous ceiling illumination

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90, 2 SDCM
up to 3900 lm | up to 130 lm/W
L90 @ 50 000 h
non DIM, DALI-2

Types



Colours



Light distribution



indirect

Order options

COLOUR TEMPERATURE	
2700 K	9
3000 K	0
3500 K	2
4000 K	1

CONTROL	
non DIM	1
DALI-2	3


MATERIAL COLOUR	
○ traffic white RAL 9016	7
● jet black RAL 9005	1
● raw aluminium	0

REVO 150 wall surface



INDIRECT			
SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
23.6 W	2700 K	2260 lm	0 5 8 - 7 1 1 0 :: ▢ ▢
	3000 K	2330 lm	
	3500 K	2260 lm	
	4000 K	2450 lm	

REVO 180 wall surface



INDIRECT			
SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
30.1 W	2700 K	3680 lm	0 5 8 - 7 1 4 0 :: ▢ ▢
	3000 K	3680 lm	
	3500 K	3830 lm	
	4000 K	3910 lm	

LUMINOUS FLUX value calculated for CRI ≥ 90, colour white