



SASSO 140 round

suspended


EN Cylindrical spotlight made of aluminium; surface light inset lacquered; surface housing powder coated; pendant fitting with cable suspension; incl. feed (black or white); can be individually shortened; symmetric radiation characteristic - precise due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy

DE Zylindrischer Strahler aus Aluminium; Oberfläche Lichteinsatz lackiert; Oberfläche Gehäuse pulverbeschichtet; abgedandelt mit Seilabhängung; inkl. Einspeiseleitung (schwarz oder weiß); beliebig kürzbar; symmetrische Abstrahlcharakteristik - präzise durch hochwertige Linsenoptik; COB (Chip on Board) Technologie für höchste Effizienz; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe; Baldachin für Weiterverdrahtung; Konverter im Baldachin enthalten

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
 CRI ≥ 90, 2 SDCM
 up to 5120 lm | 128 lm/W
 L80 @ 50000 h
 non DIM, DALI-2

Type



Housing colours



Inset colours



Light distributions



high lumen
output for high
ceilings

Order options

COLOUR TEMPERATURE

2700 K	9
3000 K	0
3500 K	2
4000 K	1

CONTROL

non DIM	1
DALI-2	3

HOUSING COLOUR


<input type="radio"/> traffic white RAL 9016	7
<input checked="" type="radio"/> jet black RAL 9005	1

INSET COLOUR

<input type="radio"/> traffic white RAL 9016	7
<input type="radio"/> matt silver	4
<input checked="" type="radio"/> jet black RAL 9005	1
<input type="radio"/> gold dust RAL 260-M	9

BEAM ANGLE

super spot 10°	V
spot 18°	S
medium 33°	M
flood 39°	F
wide flood 62°	W



SASSO 140 round suspended



DOWNLIGHT

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
15 W	1470 lm	0 4 8 - 6 3 2 1 ::    V
36 W	4048 lm	0 4 8 - 6 3 2 1 ::    S
35 W	4548 lm	0 4 8 - 6 3 2 1 ::    ▲