


Quickinfo

3000K, 4000K
 CRI ≥ 90, 3 SDCM
 up to 112lm/W
 L80 @ 50000h
 non DIM, DALI-2
 opal cover
 IP 44

Types



Luminaire colours



End caps colours



Light distribution




STRETTA

surface

EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile can be pre-mounted; end cap galvanically chromed or in same colour as housing (chromed border); suitable for wall or ceiling mounting; with three sided light beam; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering


DE Leuchtenkörper aus Aluminiumstrangpressprofil, kantige Ausführung; keine sichtbaren Schrauben; Oberfläche pulverbeschichtet; Leuchtenprofil vorab montierbar; Enddeckel galvanisch verchromt oder in Leuchtenfarbe pulverbeschichtet (Umrandung verchromt); geeignet für Wand- oder Deckenmontage; mit dreiseitiger Lichtabstrahlung; HPO (High Performance Opal) Abdeckung für homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe



wall illumination



splash water protection (IP 44)



CRI ≥ 98 XPECTRUM

Order options


COLOUR TEMPERATURE	☼☼
3000K	5
4000K	6

CONTROL	⬆️⬆️
non DIM	1
DALI-2	3

MATERIAL COLOUR	☑️
○ pure white RAL 9010*	7
○ pure white/☉ chrome**	C
● jet black RAL 9005*	8

*end caps in housing colour with chromed boarder

**end caps completely in chrome




LIGHT OPTIC COVER

opal high performance

Options on request

COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM




STRETTA surface



LUMINAIRE

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
13W	3000K	1370lm	600	057-0132:☼☼☑️H
	4000K	1460lm		
19.5W	3000K	2050lm	900	057-0133:☼☼☑️H
	4000K	2190lm		
26.1W	3000K	2740lm	1200	057-0134:☼☼☑️H
	4000K	2920lm		

Light distribution



opal high performance

LUMINOUS FLUX value calculated for
CRI ≥ 90, colour white, cover opal