



## TASK

wall


**EN** Rectangular housing made of aluminium with rounded edges; ultra low-profile design (only 15 mm); surface powder coated; suitable for wall mounting; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; indirect component with special PCBs with asymmetrical light distribution; for optimum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering

**IT** Corpo illuminante rettangolare in alluminio con bordi arrotondati; forma ultrapiatta (solo 15 mm); verniciatura a polvere; montaggio a parete; distribuzione della luce diretta con sistema LGP-Body (Light Guiding Prism); luce convogliata lateralmente e direzionata in basso tramite incisione laser; direzionamento della luce con materiale del riflettore altamente riflettente; percentuale indiretta con piastre dedicate a distribuzione asimmetrica della luce; per un'illuminazione ottimale del soffitto; illuminazione assolutamente omogenea; LED ad efficienza energetica con elevata resa cromatica

### Quickinfo

3000 K, 4000 K  
 CRI  $\geq$  90, 3 SDCM  
 up to 125 lm/W  
 L90 @ 50 000 h  
 DALI-2  
 microprismatic (UGR  $\leq$  16)

### Type



### Colours



### Light distribution



asymmetrical ceiling  
illumination

## Order options

<b>COLOUR TEMPERATURE</b>	☑
3000K	0
4000K	1

## CONTROL

DALI-2

## MATERIAL COLOUR

<input type="checkbox"/> pure white RAL 9010	7
<input checked="" type="checkbox"/> jet black RAL 9005	8


## LIGHT OPTIC COVER

microprismatic (UGR ≤ 16)

## Options on request

## COLOUR RENDERING INDEX

CRI ≥ 80




## TASK wall



## DIRECT/INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
46 W	3000 K	↓ 1850 / ↑ 3530 lm	0 5 9 - 2 0 3 2 ☑ 3 ☑ Z
	4000 K	↓ 1970 / ↑ 3760 lm	

## Technical data



**TASK wall**  
46 W, 4000 K, direct/indirect power

### ROOM VALUES

Room dimensions	5.4 × 4.0 × 2.8 m
Reflection factor	0.7   0.5   0.2
Maintenance factor	0.8
Mounting height	2.25 m

### CALCULATION SURFACE


Surface dimensions	Floor
Surface height	0 m

### GLARE EVALUATION

Table Classification	X=4H   Y=8H   S=0.25H
UGR transversal	≤ 19
UGR axial	≤ 19



## Light distribution



microprismatic  
direct/indirect power

**LUMINOUS FLUX** value calculated for  
CRI ≥ 90, colour white, cover microprismatic