




### Quickinfo

3000 K, 4000 K  
 CRI  $\geq$  80, 3 SDCM  
 up to 3160 lm/m  
 up to 114 lm/W  
 L90 @ 50 000 h  
 non DIM, DALI-2  
 opal

### Types



### Colours



### Light distributions



## TUBO 60 system


surface / suspended

<sup>EN</sup> Supporting profile in extruded aluminium; end cap in aluminium; for continuous lighting systems; surface powder coated; surface mounted or suspended luminaire with cable suspension; height adjustment without tools; with transparent feeder cable; electrical connection of the luminaires via plug / socket system; no separate wiring required; light control via high-quality lens system for maximum, homogeneous illumination; completely homogeneously illuminated, cylindrical HPO (High Performance Opal) cover; energy-efficient LEDs with very good colour rendering

<sup>IT</sup> Binario portante in profilo di alluminio estruso; testata di chiusura in alluminio; per file continue; verniciatura a polvere; corpo illuminante a plafone o sospensione con fune; regolazione altezza senza utensili; con cavo di alimentazione trasparente; collegamento elettrico degli apparecchi tramite sistema presa / spina; senza cablaggio separato; controllo della luce con ottica lenticolare di alta qualità per un'illum. omogenea; cover cilindrica HPO (High Performance Opal) illuminata in modo perfett. omogeneo; LED ad efficienza energetica con elevata resa cromatica



single luminaire  
(p. 572)



uniform  
illumination

## Order options



<b>COLOUR TEMPERATURE</b>	☐☐
3000K	5
4000K	6

<b>CONTROL</b>	⬆️⬆️
non DIM	1
DALI-2	3

<b>MATERIAL COLOUR</b>	☑️
○ pure white RAL 9010	7
● jet black RAL 9005	8

<b>MATERIAL COLOUR</b>	■
<b>CABLE SUSPENSION</b>	■
chrome	0
black	8

## TUBO 60 surface/suspended



## INSTALLATION CHANNEL + LIGHT INSET + LIGHT OPTIC COVER

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
16.5 W	3000K	1780lm	595	058-3022☐☐☑️☑️☐
	4000K	1880lm		
33 W	3000K	3560lm	1181	058-3024☐☐☑️☑️☐
	4000K	3760lm		
66 W	3000K	7110lm	2351	058-3028☐☐☑️☑️☐
	4000K	7530lm		
82 W	3000K	8890lm	2936	058-3029☐☐☑️☑️☐
	4000K	9410lm		


## Accessories surface

## END CAP / POWER FEEDER



TYPE	ORDER CODE
end cap	058-301001☑️
end cap power feeder	058-301021☑️
middle power feeder	058-301121☑️

## LINEAR CONNECTOR



TYPE	ORDER CODE
mechanical	058-301311☑️
mechanical & electrical	058-301312☑️
incl. opal cover connector	


## CEILING MOUNTING SET



TYPE	L (mm)	ORDER CODE
ceiling mounting set	75	058-301411☑️

## Accessories suspended

## END CAP / POWER FEEDER incl. feeder cable




TYPE	ORDER CODE
end cap	058-301001☑️
end cap power feeder 5×1.5mm <sup>2</sup>	058-301041☑️
middle power feeder* 5×1.5mm <sup>2</sup>	058-301131☑️
middle power feeder angular** 5×1.5mm <sup>2</sup>	058-301132☑️

\*incl. cable suspension 1500 mm

\*\*incl. cable suspension angular max. 60° 1500 mm

## LINEAR CONNECTOR




TYPE	ORDER CODE
mechanical*	058-301321☑️
mechanical angular**	058-301331☑️
mechanical & electrical*	058-301322☑️
mechanical & electrical angular**	058-301332☑️

incl. opal cover connector

\*incl. cable suspension 1500 mm


\*\*incl. cable suspension angular max. 60° 1500 mm

## CABLE SUSPENSION



TYPE	L (mm)	ORDER CODE
cable suspension	1500	058-301421■
cable suspension angular max. 60°	1500	058-301431■

## CANOPY



TYPE	Ø-H (mm)	ORDER CODE
non DIM / DALI-2	90-22	005-260003☑️

for electrical system configuration see luminaire data sheet at xal.com

LUMINOUS FLUX value calculated for  
CRI ≥ 80, colour white, cover opal