



## TULA

suspended


**EN** Decorative suspended luminaire in aluminium; surface polished chrome or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; good glare reduction due to recessed light point plane; incl. high quality lens system; COB (Chip on Board) technology or high power LEDs for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy, either recessed or surface mounted version; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

**ES** Luminaria suspendida decorativa de aluminio; superficie cromada pulida o con recubrim. de pintura en polvo; suspensión pendular con cable de alim. (negro o blanco); acortable; buena prevenc. del deslumbram. con plano de punto de luz retranq.; óptica de alta calidad; proyec. precisa con distintos ángulos de apertura; tecnología COB (Chip on Board) para máxima eficiencia; sin sombras múltiples; LEDs eficientes de muy buena reproducción cromática; remate de techo para cableado; convert. integrado en remate, opcional. como variante empotrada o de superficie; anillos de montaje en techo opcionales para posicionam. múltiple de la luminaria en la sala


### Quickinfo

2700 K, 3000 K  
CRI ≥ 90, 3 SDCM  
up to 95 lm/W  
L80 @ 50 000 h  
non DIM, DALI-2, Casambi


### Types



### Colours



### Light distributions



free positioning by  
ring and hook

track version  
available

## Order options

### HOUSING HEIGHT

300 mm	5
500 mm	7

### SUSPENSION

cable 1500 mm	
---------------	--

### COLOUR TEMPERATURE

2700 K	4
3000 K	5

### MATERIAL COLOUR

● chrome	4
○ traffic white RAL 9016	7
● jet black RAL 9005	8
● special colours*	X

\*cable always in white

### BEAM ANGLE

medium 25°	M
flood 44°	F






### ACCESSORY COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

## Options on request

### COLOUR TEMPERATURE

4000 K	
--------	--



## TULA nano suspended



<b>INSET POWER</b>	<b>LUMINOUS FLUX</b>	<b>ORDER CODE</b>
9 W 18 Vf 500 mA	732 lm	0 4 9 - 5 L 1 0 :: 1 ▣ ▲

## TULA micro suspended



<b>INSET POWER</b>	<b>LUMINOUS FLUX</b>	<b>ORDER CODE</b>
8.4 W 18 Vf 500 mA	798 lm	0 4 9 - 5 L 1 5 :: 1 ▣ ▲

## Mounting accessories

### CANOPY CEILING 220-240 V AC, 50-60 Hz, Ⓢ PC II

TYPE	EFFICIENCY	Ø-H (mm)	ORDER CODE
500 mA   non DIM	η 79 %	115-29	0 0 5 - 2 6 0 2 1 1 ▣
500 mA   DALI-2	η 81 %	115-29	0 0 5 - 2 6 0 2 1 3 ▣
500 mA   Casambi	η 85 %	115-29	0 0 5 - 2 6 0 2 1 9 ▣

### MOUNTING SET RECESSED WITH TRIM

for installation in ceilings from 2-25 mm

TYPE	Ø-H (mm)	ORDER CODE
mounting set with trim	77-49	0 0 5 - 3 5 2 1 0 1 ▣

### MOUNTING SET RECESSED TRIMLESS

for installation in plasterboard ceilings 9-25 mm

TYPE	Ø-H (mm)	ORDER CODE
mounting set trimless	75-48	0 0 5 - 3 5 1 1 0 1 7

### SPECIAL MOUNTING TOOL

TYPE	Ø-H (mm)	ORDER CODE
special mounting tool	100-9	0 6 3 - 8 9 1 2 1 1 0

necessary to install mounting set trimless

### RING

TYPE	Ø-H (mm)	ORDER CODE
ceiling mounted	50-88	0 5 0 - 0 5 1 0 2 1 ▣

### HOOK

TYPE	L-W-H (mm)	ORDER CODE
ceiling mounted	18-13-58	0 5 0 - 5 9 0 1 1 1 ▣

## Electrical accessories

### POWER SUPPLY 220-240 V AC, 50-60 Hz, Ⓢ PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
500 mA   non DIM	η 80 %	65-39-20	0 0 2 - 9 0 7 3 2
500 mA   DALI-2	η 82 %	147-33-23	0 0 2 - 9 0 7 3 3

### DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240 V AC 160 W   48 V DC constant voltage	72-90-63	0 0 5 - 6 5 2 0 2 1 0
LED DRIVER DALI-2 DT6 1-2 addr. 200-1050 mA settable const. current 2 × 42 W   48 V DC   U <sub>OUT</sub> 10-40 V	36-88-59	0 0 5 - 6 1 2 1 0 3 0

**INSET POWER** is the current consumption excluding any ballast  
**LUMINOUS FLUX** value calculated for 3000 K, CRI ≥ 90, colour white, lens flood 2700 K -5 %