



TULA

suspended


^{EN} Decorative suspended luminaire in aluminium; surface polished chrome or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; good glare reduction due to recessed light point plane; incl. high quality lens system; COB (Chip on Board) technology or high power LEDs for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy, either recessed or surface mounted version; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

^{IT} Apparecchio a sospensione decorativo in alluminio; superficie lucida cromata, o verniciatura a polvere; sospeso con cavo a sospensione, incl. cavo di alimentazione (nero o bianco); accorciabile a piacere; ottima schermatura con superficie di emissione arretrata; incl. ottica lenticolare di qualità; con tecnologia COB (Chip on Board) o LED high power per la massima efficienza; assenza di ombre multiple; LED ad efficienza energetica con elevata resa cromatica; rosone per cablaggio passante; converter inserito nel rosone, a scelta in variante da incasso o a plafone; anelli di montaggio a soffitto per posizionare la lampada in più punti dell'ambiente disponibili come accessori


Quickinfo

2700 K, 3000 K
 CRI ≥ 90, 3 SDCM
 up to 95 lm/W
 L80 @ 50 000 h
 non DIM, DALI-2, Casambi


Types




Colours



Light distributions



free positioning by
ring and hook



track version
available

Order options

HOUSING HEIGHT	L
300 mm	5
500 mm	7

SUSPENSION	
cable 1500 mm	

COLOUR TEMPERATURE	::
2700 K	4
3000 K	5

MATERIAL COLOUR	■
● chrome	4
○ traffic white RAL 9016	7
● jet black RAL 9005	8
● special colours*	X





*cable always in white

BEAM ANGLE	▲
medium 25°	M
flood 44°	F

ACCESSORY COLOUR	■
○ traffic white RAL 9016	7
● jet black RAL 9005	8

Options on request

COLOUR TEMPERATURE	
4000 K	



TULA nano suspended



INSET POWER	LUMINOUS FLUX	ORDER CODE
9W 18 Vf 500mA	732lm	0 4 9 - 5 L 1 0 :: 1 ▲

TULA micro suspended



INSET POWER	LUMINOUS FLUX	ORDER CODE
8.4W 18 Vf 500mA	798lm	0 4 9 - 5 L 1 5 :: 1 ▲

Mounting accessories

CANOPY CEILING 220-240V AC, 50-60Hz, PC II

TYPE	EFFICIENCY	Ø-H (mm)	ORDER CODE
500 mA non DIM	η 79 %	115-29	0 0 5 - 2 6 0 2 1 1 ■
500 mA DALI-2	η 81 %	115-29	0 0 5 - 2 6 0 2 1 3 ■
500 mA Casambi	η 85 %	115-29	0 0 5 - 2 6 0 2 1 9 ■

MOUNTING SET RECESSED WITH TRIM

for installation in ceilings from 2-25mm

TYPE	Ø-H (mm)	ORDER CODE
mounting set with trim	77-49	0 0 5 - 3 5 2 1 0 1 ■

MOUNTING SET RECESSED TRIMLESS

for installation in plasterboard ceilings 9-25mm

TYPE	Ø-H (mm)	ORDER CODE
mounting set trimless	75-48	0 0 5 - 3 5 1 1 0 1 7

SPECIAL MOUNTING TOOL

TYPE	Ø-H (mm)	ORDER CODE
special mounting tool	100-9	0 6 3 - 8 9 1 2 1 1 0

necessary to install mounting set trimless

RING

TYPE	Ø-H (mm)	ORDER CODE
ceiling mounted	50-88	0 5 0 - 0 5 1 0 2 1 ■

HOOK

TYPE	L-W-H (mm)	ORDER CODE
ceiling mounted	18-13-58	0 5 0 - 5 9 0 1 1 1 ■

Electrical accessories

POWER SUPPLY 220-240V AC, 50-60Hz, PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
500 mA non DIM	η 80 %	65-39-20	0 0 2 - 9 0 7 3 2
500 mA DALI-2	η 82 %	147-33-23	0 0 2 - 9 0 7 3 3

DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240V AC 160W 48V DC constant voltage	72-90-63	0 0 5 - 6 5 2 0 2 1 0
LED DRIVER DALI-2 DT6 1-2 addr. 200-1050 mA settable const. current 2x 42W 48V DC U _{OUT} 10-40V	36-88-59	0 0 5 - 6 1 2 1 0 3 0

INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for 3000K, CRI ≥ 90, colour white, lens flood 2700K -5%