



reddot winner 2020



BETO

free standing


EN Free standing luminaire from extruded aluminium profile in angular design; extremely slim design (only 42 × 42 mm); square downpipe; pedestal with recess for table base; powder coated; direct/indirect light distribution; direct light component with high gloss reflector + faceted design and asymmetric radiation characteristic; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination; energy-efficient LEDs with very good colour rendering; switch installed in the downpipe; presence sensor detection range Ø 4.5 m on the floor (variant brightness & presence sensor); incl. Loxone Air module for easy integration into the Loxone home and building automation system; incl. connection cable (3 m) with safety plug

DE Stehleuchte aus Aluminiumstrangpressprofil in kantiger Ausführung; extrem schlanke Bauform (nur 42 × 42 mm); Standrohr quadratisch; Standfuß mit Ausnehmung für Tischfuß; pulverbeschichtet; direkt/indirekte Abstrahlcharakteristik; Direktlichtanteil mit hochglänzendem Reflektor + Facettenoptik und asymmetrischer Abstrahlcharakteristik; Indirektlichtanteil mit eigenen Platinen und hochwertiger Linsenoptik für maximale, homogene Deckenaufhellung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Schalter im Standrohr verbaut; Anwesenheitssensor-Erfassungsbereich Ø 4,5 m am Fußboden (Variante brightness & presence sensor); inkl. Loxone Air Modul zur einfachen Integration in die Loxone Haus- & Gebäudeautomation; inkl. Anschlussleitung (3 m) mit Schutzkontaktstecker

Quickinfo

3000 K, 4000 K
CRI ≥ 80, 3 SDCM
up to 144 lm/W
L90 @ 50 000 h
Loxone Air
touch DIM
brightness & presence sensor
reflector (UGR ≤ 13)

Type



Colours




Light distributions



lighting control by
Loxone Air



lighting control by
touch DIM on pole




asymmetric
illumination

Order options

BASE PLATE

U-shape	4
T-shape	5



COLOUR TEMPERATURE

3000 K	5
4000 K	6

CONTROL


Loxone Air incl.	T
touch DIM on pole	
Loxone Air incl.	S
ESSENTIAL sensor (brightness & presence)	

MATERIAL COLOUR

○ pure white RAL 9010	7
● jet black RAL 9005	8
● special colours p.992	X

LIGHT OPTIC COLOUR

chrome reflector	R
black reflector	B



BETO free standing



DIRECT / INDIRECT SOFT


SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
52 W	3000 K	↓ 1770 / ↑ 5030 lm	0 7 4 - 6 9 4
	4000 K	↓ 1950 / ↑ 5550 lm	



DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
67 W	3000 K	↓ 2010 / ↑ 6650 lm	0 7 4 - 6 9 5
	4000 K	↓ 2210 / ↑ 7330 lm	

Technical data



BETO free standing, 67 W, 4000 K
direct/indirect power

ROOM VALUES


Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8

CALCULATION SURFACE


Surface dimensions	1.6 × 0.8
Surface height	0.75
Average illuminance (E_m)	> 500 lx
Uniformity (U_o)	> 0.6

GLARE EVALUATION


Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19



Light distributions



reflector (UGR ≤ 13)
direct/indirect



reflector (UGR ≤ 13)
direct/indirect power

LUMINOUS FLUX value calculated for
CRI ≥ 80, colour white, reflector chrome