





Quickinfo

4000 K
 CRI ≥ 90 / 3 SDCM
 UGR ≤ 19
 bis zu $\downarrow$ 15,500 lm / $\uparrow$ 8,050 lm
 bis zu 120 lm/W
 L90 / 50000 h
 DALI-2
 Microprismatic
 IP20

Types



Farbe



Lichtverteilung



TASK angular

suspended

EN Rectangular suspended luminaire, consisting of single L-shaped or rectangular elements; Luminaire housing made of aluminium with rounded edges; ultra low-profile design (only 15 mm); surface powder coated; cable suspension, tool-less height adjustment; convenient quick mounting system without tools; incl. feeder cable; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; canopy for through wiring; optional acoustic elements available


DE Rechteckige Pendelleuchte, bestehend aus einzelnen L-förmigen bzw. rechteckigen Elementen; Leuchtenkörper aus Aluminium mit abgerundeten Kanten; extrem flache Bauform (nur 15 mm); Oberfläche pulverbeschichtet; werkzeuglos höhenverstellbare Seilabhängung; komfortables, werkzeugloses Schnellmontagesystem; inkl. Einspeiseleitung; direkte Lichtverteilung durch LGP-Body (Light-Guiding-Prism); seitlich eingekoppeltes Licht durch Lasergravur nach unten gelenkt; Indirektlichtanteil mit eigenen Platinen für erhöhten Lichtstrom und maximale Deckenaufhellung; absolut homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Baldachin für Weiterverdrahtung; optional Akustikelemente erhältlich




DiiA® standards
 251, 252, 253




clicksystem




microprismatic
 UGR ≤ 19



CRI ≥ 98
 XPECTRUM
 (optional)





TASK angular suspended




DIRECT / INDIRECT POWER DALI-2, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
197.0 W	4000 K	↓15500/↑18050 lm	120 lm/W	0 5 9 - 5 2 8 3 1 3  K




TASK long angular suspended




DIRECT / INDIRECT POWER DALI-2, CRI ≥ 90

COLOUR TEMP.	ORDER CODE
4000 K	0 5 9 - 5 2 8 4 1 3  K



Planning Information



TASK long angular, 280W, 4000K, direct/indirect power

ROOM VALUES	
Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8
Suspension height	2.25 m

CALCULATION SURFACE	
Surface dimensions	3.2 × 1.2 m
Surface height	0.75 m
Average illuminance (E _m)	> 500 lx
Uniformity (U ₀)	> 0.6



GLARE EVALUATION	
Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19

Order options

COLOUR	
pure white RAL 9010	7
jet black RAL 9005	8

Community Windpower, Frodsham


Vereinigtes Königreich

Fotograf

Paul Karalius




Verwendete Produkte



**TASK angular
suspended**



**TASK round
suspended**



**TASK circle
suspended**

