



SONO IP54

surface


EN Round luminaire housing in die-cast aluminium; surface powder coated; suitable for wall or ceiling mounting; completely homogeneously illuminated, satinised PMMA cover; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

DE Runder Leuchtenkörper aus Aluminiumdruckguss; Oberfläche pulverbeschichtet; geeignet für Wand- oder Deckenmontage; absolut homogen ausgeleuchtete, satinierte PMMA-Abdeckung; gleiche Leuchtdichte bei allen Größenvarianten; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Leuchte mit 2 Kabelöffnungen und Steckklemme für Weiterverdrahtung

Quickinfo

3000 K, 4000 K
CRI $\geq$ 80 / 3 SDCM
bis zu 143 lm/W
L90 / 50000 h
DALI-2, nicht dimmbar
Opal
IP54, IK07

Types



Farbe



Lichtverteilung



DiiA® standards
251, 252, 253



easy mounting
by click-
mechanism



dust & insect
protection (IP
54)



tunable white
2700 – 6500 K
(optional)




SONO 260 IP54 surface



OPAL | DIRECT CRI ≥ 80, pure white

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
7.6 W	3000 K	950 lm	125 lm/W	8 7 1 - 9 1 2 6 5 ◆ 7 O
	4000 K	1010 lm	133 lm/W	8 7 1 - 9 1 2 6 6 ◆ 7 O




SONO 350 IP54 surface



OPAL | DIRECT CRI ≥ 80, pure white

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
15.9 W	3000 K	2090 lm	131 lm/W	8 7 1 - 9 1 3 6 5 ◆ 7 O
	4000 K	2210 lm	139 lm/W	8 7 1 - 9 1 3 6 6 ◆ 7 O




SONO 450 IP54 surface



OPAL | DIRECT CRI ≥ 80, pure white

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
23.2 W	3000 K	3060 lm	132 lm/W	8 7 1 - 9 1 4 6 5 ◆ 7 O
	4000 K	3240 lm	140 lm/W	8 7 1 - 9 1 4 6 6 ◆ 7 O



Order options

CONTROL

non DIM

DALI-2




COLOUR

pure white

RAL 9010

1

3



SONO 600 IP54 surface



OPAL | DIRECT CRI ≥ 80, pure white

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
43.0 W	3000 K	5830 lm	136 lm/W	8 7 1 - 9 1 5 6 5 7 0
	4000 K	6170 lm	143 lm/W	8 7 1 - 9 1 5 6 6 7 0

Mounting accessories (optional)

DISMOUNTING TOOL

TYPE	ORDER CODE
vacuum cup	0 8 6 - 3 0 0 0 0

Order options

CONTROL		COLOUR	
non DIM	1	pure white	RAL 9010
DALI-2	3		