



SONO LOOP IP54

surface


EN Round luminaire housing in die-cast aluminium; surface powder coated; fitted bezel in rolled, seamless welded aluminium profile; suitable for wall or ceiling mounting; completely homogeneously illuminated, satinised PMMA cover; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

DE Runder Leuchtenkörper aus Aluminiumdruckguss; Oberfläche pulverbeschichtet; aufgesetzter Ring aus gerolltem und nahtlos verschweißtem Aluminiumprofil; geeignet für Wand- oder Deckenmontage; absolut homogen ausgeleuchtete, satinierte PMMA-Abdeckung; gleiche Leuchtdichte bei allen Größenvarianten; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Leuchte mit 2 Kabelöffnungen und Steckklemme für Weiterverdrahtung

Quickinfo

3000 K, 4000 K
CRI $\geq$ 80 / 3 SDCM
bis zu 133 lm/W
L90 / 50000 h
DALI-2, nicht dimmbar
Opal
IP54, IK07

Types



Farbe



Lichtverteilung




DiiA® standards
251, 252, 253




easy mounting
by click-
mechanism



dust & insect
protection (IP
54)



tunable white
2700 – 6500 K
(optional)




SONO LOOP 260 IP54 surface



OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
7.6 W	3000 K	881 lm	116 lm/W	8 7 1 - 8 1 2 6 5 ☒ ☒ O
	4000 K	933 lm	123 lm/W	8 7 1 - 8 1 2 6 6 ☒ ☒ O




SONO LOOP 350 IP54 surface



OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
15.9 W	3000 K	1940 lm	122 lm/W	8 7 1 - 8 1 3 6 5 ☒ ☒ O
	4000 K	2050 lm	129 lm/W	8 7 1 - 8 1 3 6 6 ☒ ☒ O




SONO LOOP 450 IP54 surface




OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
23.2 W	3000 K	2840 lm	122 lm/W	8 7 1 - 8 1 4 6 5 ☒ ☒ O
	4000 K	3010 lm	130 lm/W	8 7 1 - 8 1 4 6 6 ☒ ☒ O



Order options

CONTROL		COLOUR	
non DIM	1	pure white RAL 9010	7
DALI-2	3	grey aluminium RAL 9007	D



SONO LOOP 600 IP54 surface



OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
43.0 W	3000 K	5410 lm	126 lm/W	8 7 1 - 8 1 5 6 5 O
	4000 K	5730 lm	133 lm/W	8 7 1 - 8 1 5 6 6 O

Order options

CONTROL		COLOUR	
non DIM	1	pure white RAL 9010	7
DALI-2	3	grey aluminium RAL 9007	D