

# BO 55

track  
180-7312537F



Projekt / Typ \_\_\_\_\_

Notizen \_\_\_\_\_

Anzahl / Datum \_\_\_\_\_



<b>Allgemein</b>
Decke , Track
schwenkbar max. 90°
Rotierbarkeit 355°
Weiß , RAL9016 <sup>1</sup>
IP20
2080 lm


<b>LED</b>
3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 100 , R <sub>f</sub> : 91 , R <sub>f1-15</sub> : 88
MR 0.59
MDER 0.53

<b>Optisch</b>
flood
Ausstrahlwinkel 38°
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

<b>Elektrisch</b>
DALI-2
24.7 W
SK2 220-240V
84 lm/W
1 DALI Addr.

<b>Abmessungen</b>
Durchmesser 55 mm
Höhe 140 mm
0.5 kg


## Lichtverteilung



flood 38°

h (m)	E0° (lx)	ø (m)
1	5270	0.70
2	1320	1.40
3	590	2.09
4	330	2.79
5	210	3.49

## Produktskizze



<sup>1</sup> RAL Code  
<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

## Montageanleitung



## Beleuchtungsrechner

