

# UNICO L2 basic

trim

090-7L261E0B21 090-7L2020B



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke, Einbau

Reflektor schwarz, RAL 9005<sup>1</sup>

Montage Set Tiefschwarz

IP20

623 lm

## LED

4000 K

CRI  $\geq 90$

L90 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 102, R<sub>f</sub>: 93, R<sub>f(15)</sub>: 92

MR 0.81

MDER 0.74

## Optisch

medium square

Ausstrahlwinkel 32°

UGR  $\leq 10$ ,  $\geq 65^\circ$   $< 3000$  cd/m<sup>2</sup>

PstLM  $\leq 1.0$ <sup>2</sup>

SVM  $\leq 0.4$ <sup>2</sup>

## Elektrisch

nicht dimmbar

220-240 V

System 7.3 W

System 85 lm/W<sup>3</sup>

SK2

## Abmessungen

mit Rand

Länge 101 mm

Breite 63 mm

Höhe 51 mm

0.35 kg

## Ausschnitt

Länge 90 mm

Breite 50 mm

min. Deckenstärke 2 mm

max. Deckenstärke 25 mm

Einbautiefe 120 mm

<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Volllast (ungedimmt)

<sup>3</sup> inkl. Berücksichtigung von optischen, internen Steuergeräteverlusten & der Effizienz des Betriebsgeräts


## Montageanleitung



## Beleuchtungsrechner



## Lichtverteilung



## Produktskizze

