



Quickinfo

2700 K, 3000 K, 4000 K
 CRI ≥ 90, 3 SDCM
 UGR ≤ 19 / 65° ≤ 1500 cd/m²
 L2 up to 104 lm/W
 L3 up to 111 lm/W
 L4 up to 116 lm/W
 L6 up to 117 lm/W
 L90 @ 50 000 h
 non DIM, DALI-2

Types



Colours



Light optics



UNICO linear


recessed

EN Rectangular recessed multi-downlight made of die-cast aluminium; equipped with two (L2) / three (L3) / four (L4) / six (L6) individually selectable or pre-specified, customised light elements; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; high-quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with different symmetrical light distributions; or with asymmetric light distribution; energy-efficient high power LEDs with very good colour rendering; clank-free

DE Rechteckiger Einbau-Multi-Downlight aus Aluminiumdruckguss; bestückt mit zwei (L2) / drei (L3) / vier (L4) / sechs (L6) individuell wählbaren oder fix definierten, anwendungsspezifischen Optiken; werkzeuglose Montage im Montageset durch Kugelschnappsystem; einfache elektrische Montage durch verpolungssichere Steckverbindung; geeignet für Deckenstärken von 2-25 mm; Oberfläche pulverbeschichtet; Einbau in unterschiedlichen Gehäusen möglich; hochwertiger Reflektor mit mikrofaccettierter, aluminiumbedampfter Oberfläche; präzise Abstrahlcharakteristik mit unterschiedlichen symmetrischen Lichtverteilungen; oder mit asymmetrischer Lichtverteilung; energieeffiziente High-Power-LEDs mit sehr guter Farbwiedergabe; klirrfrei



DiiA® standards
 251, 252, 253



one luminaire
 multiple scenes



plug / socket
 connector



black & gold
 reflector



tunable white
 2700-5000K

Order options

COLOUR TEMPERATURE	☐☐
2700K	4
3000K	5
4000K	6

CONTROL	◆
non DIM	1
DALI-2	3

LIGHT OPTIC	▲
spot round (UGR≤10)	K
narrow medium round (UGR≤10)	N
medium round (UGR≤10)	B
medium square (UGR≤10)	E
flood round (UGR≤16)	C
flood square (UGR≤19)	F
wide flood round	D
wide flood square	G

MATERIAL COLOUR	☑
○ traffic white RAL 9016	W
● jet black RAL 9005	B

LIGHT OPTIC COLOUR	■
chrome reflector	0
black reflector*	B

*not available for spot round, narrow medium round and wallwasher

Options on request

COLOUR TEMPERATURE
tunable white 2700–5000K
DALI-2 DT8

LIGHT OPTIC COLOUR
gold reflector

MOUNTING SET
acoustic soft ceilings

Product configurator



Create your own UNICO PRO
unico.xal.com

Planning information



The icons of the light optics are shown in the reflected ceiling plan (RCP) view.

UNICO L2 basic recessed

FLOOR			
SYSTEM POWER	LUMINOUS FLUX	ORDER CODE	
7.3 W	up to 762lm	090-7L2::▲0■21	
choose one light optic ▲ from the options on the left depending on your room needs			

WALL			
2x wallwasher			
SYSTEM POWER	LUMINOUS FLUX	ORDER CODE	
7.3 W	645lm	090-7L2::▲A0022	

CORRIDOR			
2x rectangular			
SYSTEM POWER	LUMINOUS FLUX	ORDER CODE	
7.3 W	643lm	090-7L2::▲R0■21	

WALL + FLOOR			
2x wallwasher floor			
SYSTEM POWER	LUMINOUS FLUX	ORDER CODE	
7.3 W	672lm	090-7L2::▲W0■22	

UNICO L3 basic recessed

FLOOR			
SYSTEM POWER	LUMINOUS FLUX	ORDER CODE	
9.8 W	up to 1090lm	090-7L3::▲0■21	
choose one light optic ▲ from the options on the left depending on your room needs			

WALL			
3x wallwasher			
SYSTEM POWER	LUMINOUS FLUX	ORDER CODE	
9.8 W	924lm	090-7L3::▲A0021	

Accessories

MOUNTING SET WITH TRIM			
for intermediate ceilings 2–25 mm			
TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
L2	101-63-30	90-50	090-7L2020☑
L3	138-63-30	130-50	090-7L3020☑

TRIMLESS MOUNTING SET			
for installation in plasterboard ceilings 12.5/15/20/25 mm			
TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
L2	85-47-47	90-50	090-7L20100
L3	122-47-47	130-50	090-7L30100

THROUGH WIRING CONNECTION BOX			
TYPE	L-W-H (mm)	ORDER CODE	
non DIM cable ø4–12 mm	105-58-30	005-2531110	
DALI cable ø4–12 mm	105-58-30	005-2551110	
Linect® ready			

LUMINOUS FLUX value calculated for
 3000K, CRI≥90, colour white, reflector chrome
 2700K -6%, 4000K +7%

Order options

COLOUR TEMPERATURE ◆◆

2700K	4
3000K	5
4000K	6

CONTROL ◆

non DIM	1
DALI-2	3

LIGHT OPTIC ▲

spot round (UGR≤10)	K
narrow medium round (UGR≤10)	N
medium round (UGR≤10)	B
medium square (UGR≤10)	E
flood round (UGR≤16)	C
flood square (UGR≤19)	F
wide flood round	D
wide flood square	G

MATERIAL COLOUR ▣

○ traffic white RAL 9016	W
● jet black RAL 9005	B

LIGHT OPTIC COLOUR ■

chrome reflector	0
black reflector*	B

*not available for spot round, narrow medium round and wallwasher

Options on request

COLOUR TEMPERATURE

tunable white 2700–5000K
DALI-2 DT8

LIGHT OPTIC COLOUR

gold reflector

MOUNTING SET

acoustic soft ceilings

Product configurator




Create your own UNICO PRO
unico.xal.com

Planning information



The icons of the light optics are shown in the reflected ceiling plan (RCP) view.

UNICO L4 basic recessed



FLOOR

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
13.1W	up to 1520lm	090-7L4::▲0■21

choose one light optic ▲ from the options on the left depending on your room needs



WALL

4x wallwasher

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
13.1W	1290lm	090-7L4::◆A021



WALL + FLOOR

4x wallwasher floor

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
13.1W	1340lm	090-7L4::◆W0■22

Accessories



MOUNTING SET WITH TRIM

for intermediate ceilings 2–25mm

TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
L4	176-63-30	165-50	090-7L4020



TRIMLESS MOUNTING SET

for installation in plasterboard ceilings 12.5/15/20/25mm

TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
L4	210-47-47	165-50	090-7L40100



THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø4–12mm	105-58-30	005-2531110
DALI cable ø4–12mm	105-58-30	005-2551110

Linect® ready

LUMINOUS FLUX value calculated for
 3000K, CRI≥90, colour white, reflector chrome
 2700K -6%, 4000K +7%

Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL

non DIM	1
DALI-2	3

LIGHT OPTIC

spot round (UGR _{≤10})	K
narrow medium round (UGR _{≤10})	N
medium round (UGR _{≤10})	B
medium square (UGR _{≤10})	E
flood round (UGR _{≤16})	C
flood square (UGR _{≤19})	F
wide flood round	D
wide flood square	G

MATERIAL COLOUR

<input type="radio"/> traffic white RAL 9016	W
<input checked="" type="radio"/> jet black RAL 9005	B

LIGHT OPTIC COLOUR

chrome reflector	0
black reflector*	B

*not available for spot round, narrow medium round and wallwasher

Options on request

COLOUR TEMPERATURE

tunable white 2700–5000K	
DALI-2 DT8	

LIGHT OPTIC COLOUR

gold reflector	
----------------	--

MOUNTING SET

acoustic soft ceilings	
------------------------	--



UNICO L6 basic recessed



FLOOR

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
18.6 W	up to 2180 lm	090-7L6:::▲0■21

choose one light optic ▲ from the options on the left depending on your room needs

WALL

6x wallwasher		
SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
18.6 W	1850 lm	090-7L6:::▲A0021

CORRIDOR

6x rectangular		
SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
18.6 W	1840 lm	090-7L6:::▲R0■21

WALL + FLOOR

6x wallwasher floor		
SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
18.6 W	1930 lm	090-7L6:::▲W0■21

Accessories

MOUNTING SET WITH TRIM

for intermediate ceilings 2–25 mm

TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
L6	251-63-30	240-50	090-7L6020

TRIMLESS MOUNTING SET

for installation in plasterboard ceilings 12.5/15/20/25 mm

TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
L6	285-47-47	240-50	090-7L60100

THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø4–12 mm	105-58-30	005-2531110
DALI cable ø4–12 mm	105-58-30	005-2551110

Linect® ready

LUMINOUS FLUX value calculated for
3000 K, CRI ≥ 90, colour white, reflector chrome
2700 K -6%, 4000 K +7%



UNICO linear high efficient recessed


EN Rectangular recessed multi-downlight made of die-cast aluminium; HIGH EFFICIENT variant; equipped with two (L2) / three (L3) / four (L4) / six (L6) individually selectable, customised light elements; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with different symmetrical light distributions; energy-efficient high power LEDs with very good colour rendering; clank-free

DE Rechteckiger Einbau-Multi-Downlight aus Aluminiumdruckguss; HIGH EFFICIENT Variante; bestückt mit zwei (L2) / drei (L3) / vier (L4) / sechs (L6) individuell wählbaren, anwendungsspezifischen Optiken; werkzeuggesteigerte Montage im Montageset durch Kugelschnappsystem; einfache elektrische Montage durch verpolungssichere Steckverbindung; geeignet für Deckenstärken von 2-25 mm; Oberfläche pulverbeschichtet; Einbau in unterschiedlichen Gehäusen möglich; hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; präzise Abstrahlcharakteristik mit unterschiedlichen symmetrischen Lichtverteilungen; energieeffiziente High-Power-LEDs mit sehr guter Farbwiedergabe; klirrfrei

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
 CRI ≥ 90, 3 SDCM
 UGR ≤ 19 / 65° ≤ 3000 cd/m²
 L2 up to 129 lm/W
 L3 up to 132 lm/W
 L4 up to 134 lm/W
 L6 up to 136 lm/W
 L90 @ 50 000 h
 non DIM, DALI-2

Types



Colours




Light optics



up to 136 lm/W
(high efficiency)



DiiA® standards
251, 252, 253



one luminaire
multiple scenes



plug/socket
connector



black & gold
reflector

Order options

COLOUR TEMPERATURE ◆◆

2700K	9
3000K	0
3500K	2
4000K	1

CONTROL ◆

non DIM	1
DALI-2	3

LIGHT OPTIC ▲

flood round (UGR _{≤16})	C
flood square (UGR _{≤19})	F
wide flood round	D
wide flood square	G

MATERIAL COLOUR ■

○ traffic white RAL 9016	W
● jet black RAL 9005	B

LIGHT OPTIC COLOUR ■

chrome reflector	0
black reflector	B




UNICO L2 basic high efficient recessed



FLOOR

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
6.0W	up to 775lm	090-7L2 ◆◆▲0■31

choose one light optic ▲ from the options on the left depending on your room needs



UNICO L3 basic high efficient recessed



FLOOR

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
8.8W	up to 1160lm	090-7L3 ◆◆▲0■31

choose one light optic ▲ from the options on the left depending on your room needs



UNICO L4 basic high efficient recessed



FLOOR

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
11.6W	up to 1550lm	090-7L4 ◆◆▲0■31

choose one light optic ▲ from the options on the left depending on your room needs



UNICO L6 basic high efficient recessed



FLOOR


SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
17.0W	up to 2320lm	090-7L6 ◆◆▲0■31

choose one light optic ▲ from the options on the left depending on your room needs

Accessories

MOUNTING SET WITH TRIM


for intermediate ceilings 2-25mm



TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
L2	101-63-30	90-50	090-7L2020 ■
L3	138-63-30	130-50	090-7L3020 ■
L4	176-63-30	165-50	090-7L4020 ■
L6	251-63-30	240-50	090-7L6020 ■

TRIMLESS MOUNTING SET

for installation in plasterboard ceilings 12.5/15/20/25mm




TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
L2	135-47-47	90-50	090-7L20100
L3	173-47-47	130-50	090-7L30100
L4	210-47-47	165-50	090-7L40100
L6	285-47-47	240-50	090-7L60100

THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø4-12mm	105-58-30	005-2531110
DALI cable ø4-12mm	105-58-30	005-2551110

Linect® ready



LUMINOUS FLUX value calculated for 4000K, CRI ≥ 90, colour white, reflector chrome
2700K -8%, 3000K -4%, 3500K -4%