

UNICO

wall recessed


EN Recessed wall luminaire in aluminium; installation without tools in mounting set (trimless or with trim) with ball catch system; installation possible in different housings; surface powder coated; incl. external converter; high-quality reflector with micro-faceted, aluminum-vaporised surface; different asymmetrical light distributions; installation optionally for floor or ceiling illumination; energy-efficient high power LEDs with very good colour rendering

DE Wandeinbauleuchte aus Aluminium; werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand) durch Kugelschnappsystem; Einbau in unterschiedlichen Gehäusen möglich; Oberfläche pulverbeschichtet; inkl. externem Konverter; hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; unterschiedliche asymmetrische Lichtverteilungen; Montage wahlweise zur Boden- oder Deckenaufhellung; energieeffiziente High-Power-LEDs mit sehr guter Farbwiedergabe

Quickinfo

2700 K, 3000 K, 4000 K
 CRI ≥ 90, 3 SDCM
 up to 45 lm/W
 L90 @ 50 000 h
 non DIM, DALI-2

Types



Colours




Light distribution



homogeneous floor illumination



safety glass for dust protection



tunable white 2700–5000 K

Order options

COLOUR TEMPERATURE	
2700 K	4
3000 K	5
4000 K	6

CONTROL	
non DIM	1
DALI-2	3

LIGHT OPTIC	
wide floor	


MATERIAL COLOUR	
<input type="radio"/> traffic white RAL 9016	W
<input checked="" type="radio"/> jet black RAL 9005	B

Options on request

COLOUR TEMPERATURE	
tunable white 2700–5000K	

only available for 2 lamps | DALI-2 DT8


Light distribution




microprismatic
direct/indirect power

LUMINOUS FLUX value calculated for
3000K, CRI ≥ 90, colour white, reflector chrome
2700K -6%, 4000K +7%

UNICO wall recessed




1 LAMP	SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
	9.9 W	435 lm	090-6L1::UB001




2 LAMPS	SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
	17.2 W	777 lm	090-6L2::UB001

Accessories



MOUNTING SET WITH TRIM			
for intermediate ceilings 2–25 mm			
TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
1 lamp	101-63-20	90-50	090-7L2020
2 lamps	101-101-30	90-90	090-7Q4020



TRIMLESS MOUNTING SET			
for installation in plasterboard ceilings 12.5/15/20/25 mm			
TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
1 lamp	88-50-47	90-50	090-7L20100
2 lamps	85-85-47	90-90	090-7Q40100

PRIMED CONCRETE MOUNTING SET			
TYPE	L-W-H (mm)	ORDER CODE	
primed concrete ceilings	240-400-130	052-1914320	
order mounting set separately			

EXPOSED CONCRETE MOUNTING SET			
TYPE	ORDER CODE		
1 lamp exposed concrete	090-6L10500		
2 lamps exposed concrete	090-6L20600		
order mounting set separately			

Planning information

