

# UNICO L2 basic

ceiling

090-1L261D9001



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke , Aufbau

Gold , RAL 260-M <sup>1</sup>

Reflektor Chrom

IP20

1170 lm

## LED

4000 K

CRI  $\geq$  90

L90 / 50000 h

initial MacAdam  $\leq$  3 SDCM

R<sub>g</sub>: 102 , R<sub>f</sub>: 93 , R<sub>f(1-5)</sub>: 92

MR 0.81

MDER 0.74

## Optisch

wide flood round

Ausstrahlwinkel 72°

$\geq 65^\circ$  <3000 cd/m<sup>2</sup>

PstLM  $\leq$  1.0 <sup>2</sup>

SVM  $\leq$  0.4 <sup>2</sup>

## Elektrisch

nicht dimmbar

220-240 V

System 12.6 W

System 93 lm/W<sup>3</sup>

SK1

## Abmessungen

Länge 88 mm

Breite 51 mm

Höhe 90 mm

0.35 kg

<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

<sup>3</sup> inkl. Berücksichtigung von optischen, internen

Steuergeräteverlusten & der Effizienz des Betriebsgeräts


## Montage- anleitung



## Beleuchtungs- rechner



## Lichtverteilung



## Produktskizze

