

BETO circle 800 direct

suspended

074-7403D37B



Projekt / Typ

Notizen

Anzahl / Datum



Allgemein

Decke | Abgehängt

Reinweiß | RAL 9010 ¹

Reflektor Chrom dunkel

IP20

4200 lm

LED

tunable white | 2700 K - 6500 K

CRI \geq 90

L90 / 50000 h

initial MacAdam \leq 3 SDCM

R_g: 101 | R_f: 90 | R_{f(1-15)}: 88

MR 0.51 | MDER 0.46

Optisch

Reflector | symmetric

UGR \leq 16 | $\geq 65^\circ$ < 1500 cd/m²

PstLM \leq 1.0 ² | SVM \leq 0.4 ²

Elektrisch

DALI-2 | 2 DALI Addr.

SK1 | 220-240 V

System 50 W

System 84 lm/W ³

Abmessungen

Durchmesser 807 mm | Höhe 42 mm


5,2 kg

¹ RAL Code


² Wert von umgebendem Produkt bei Volllast (ungedimmt)

³ inkl. Berücksichtigung von optischen, internen Steuergeräteverlusten & der Effizienz des Betriebsgeräts

Lichtverteilung



Produktskizze



Montageanleitung



Beleuchtungsrechner

