



## FLOW

surface


**EN** Square aluminium luminaire housing, flat design (luminaire housing 35 mm); surface powder coated; suitable for wall or ceiling mounting, luminaire housing set 11 mm away from wall or ceiling; convenient quick mounting system without tools; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; completely homogeneous illumination; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

**DE** Quadratischer Leuchtenkörper aus Aluminium, flache Bauform (Leuchtenkörper 35 mm); Oberfläche pulverbeschichtet; geeignet für Wand- oder Deckenmontage, Leuchtenkörper 11 mm von Wand bzw. Decke abgesetzt; komfortables, werkzeugloses Schnellmontagesystem; direkte Lichtverteilung durch LGP-Body (Light-Guiding-Prism); seitlich eingekoppeltes Licht durch Lasergravur nach unten gelenkt; Lichtlenkung mittels hochreflektierenden Reflektormaterials; absolut homogene Ausleuchtung; gleiche Leuchtdichte bei allen Größenvarianten; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Leuchte mit 2 Kabelöffnungen und Steckklemme für Weiterverdrahtung

### Quickinfo

3000 K, 4000 K  
 CRI ≥ 80, 3 SDCM  
 up to 146 lm/W  
 L90 @ 50 000 h  
 non DIM, DALI-2  
 opal, IP 40

### Types



### Colours



### Light distribution



**DiiA® standards**  
 251, 252, 253



easy mounting by  
 click-mechanism



insect protection  
 (IP 40)

**Order options**

COLOUR TEMPERATURE	
3000K	5
4000K	6

CONTROL	
non DIM	1
DALI-2	3


MATERIAL COLOUR	
○ pure white RAL 9010	7
● white aluminium RAL 9006	G
● jet black RAL 9005	8
● special colours ● p. 992	X

LIGHT OPTIC COVER
opal


**Options on request**

MOUNTING
1500 mm cable suspension


COLOUR RENDERING INDEX
CRI ≥ 90

**FLOW 320 surface****DIRECT**

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
15.2 W	3000 K	2000 lm	0 7 3 - 0 1 3 1 :: ◆ ◆ □ O
	4000 K	2120 lm	

**FLOW 450 surface****DIRECT**

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
23.9 W	3000 K	3250 lm	0 7 3 - 0 1 4 1 :: ◆ ◆ □ O
	4000 K	3440 lm	

**FLOW 600 surface****DIRECT**

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
44 W	3000 K	6060 lm	0 7 3 - 0 1 5 1 :: ◆ ◆ □ O
	4000 K	6420 lm	

**Accessories**

TYPE	ORDER CODE
dismounting tool	0 7 3 - 0 1 0 0 0 0