

TASK square sensor direct / indirect power

free standing

059-2932176Z



Projekt / Typ

Notizen

Anzahl / Datum



Allgemein

Bodenmontage | Stehend

Grau | RAL 9006 ¹

IP20

indirekt 10700 lm | direkt 2420 lm

gesamt 13120 lm

LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 96 | R_f: 90 | R_{t(1-15)}: 87

MR 0.75 | MDER 0.68

Optisch

Microprismatic | microprismatic

UGR ≤ 10 | ≥65° <3000 cd/m²

PstLM ≤ 1.0 ² | SVM ≤ 0.4 ²

Elektrisch

stand alone ESSENTIAL sensor

brightness & presence

SK1 | 220-240 V

System 92 W

System 143 lm/W ³

Abmessungen

H-Form

Länge 600 mm | Breite 600 mm | Höhe 2000 mm


19.9 kg

¹ RAL Code


² Wert von umgebendem Produkt bei Vollast (ungedimmt)

³ inkl. Berücksichtigung von optischen, internen Steuergeräteverlusten & der Effizienz des Betriebsgeräts

Lichtverteilung



Produktskizze



Montageanleitung

