

# TASK 450 round direct

suspended

059-0241138P



Projekt / Typ

Notizen

Anzahl / Datum



IP 40



## Allgemein

Decke , Abgehängt

Schwarz , RAL 9005 <sup>1</sup>

IP40

1860 lm

## LED

4000 K

CRI  $\geq$  90

L90 / 50000 h

initial MacAdam  $\leq$  3 SDCM

R<sub>g</sub>: 96 , R<sub>f</sub>: 90 , R<sub>(1-15)</sub>: 87

MR 0.75

MDER 0.68

## Optisch

Microprismatic

microprismatic

UGR  $\leq$  19 ,  $\geq 65^\circ$  <3000 cd/m<sup>2</sup>

PstLM  $\leq$  1.0 <sup>2</sup>

SVM  $\leq$  0.4 <sup>2</sup>

## Elektrisch

DALI-2

220-240 V

System 16.0 W

System 116 lm/W<sup>3</sup>

SK1

1 DALI Addr.

## Abmessungen

Kabel 1500 mm

Durchmesser 450 mm

Höhe 40 mm

3.5 kg


<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)


<sup>3</sup> inkl. Berücksichtigung von optischen, internen

Steuergeräteverlusten & der Effizienz des Betriebsgeräts

## Lichtverteilung



## Produktskizze



## Montage- anleitung



## Beleuchtungs- rechner

