

# TASK direct / indirect power

free standing T-shape

059-295205XZ



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Bodenmontage | Stehend

Spezialfarben

IP20

indirekt 7330 lm | direkt 2400 lm

gesamt 9730 lm

## LED

3000 K

CRI  $\geq 90$

L90 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 96 | R<sub>f</sub>: 90 | R<sub>t(1-15)</sub>: 89

MR 0.61 | MDER 0.56

## Optisch

Microprismatic | microprismatic

UGR  $\leq 13$  |  $\geq 65^\circ$   $< 3000$  cd/m<sup>2</sup>

PstLM  $\leq 1.0$ <sup>1</sup> | SVM  $\leq 0.4$ <sup>1</sup>

## Elektrisch

touch DIM an Stange

SK1 | 220-240 V

System 80 W

System 122 lm/W<sup>2</sup>

## Abmessungen


T-Form

Länge 800 mm | Breite 320 mm | Höhe 1920 mm


<sup>1</sup> Wert von umgebendem Produkt bei Volllast (ungedimmt)

<sup>2</sup> inkl. Berücksichtigung von optischen, internen Steuergeräteverlusten & der Effizienz des Betriebsgeräts

## Lichtverteilung



## Produktskizze



## Montageanleitung

