

TASK sensor direct / indirect asymmetric power

free standing T-shape

059-2951178Z



Projekt / Typ

Notizen

Anzahl / Datum



Allgemein

Bodenmontage | Stehend

Schwarz | RAL 9005 ¹

IP20

indirekt 11000 lm | direkt 2030 lm

gesamt 13030 lm

LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 96 | R_f: 90 | R_{t(1-5)}: 87

MR 0.75 | MDER 0.68

Optisch

Microprismatic | microprismatic

UGR ≤ 13 | $\geq 65^\circ$ <3000 cd/m²

PstLM ≤ 1.0 ² | SVM ≤ 0.4 ²

Elektrisch

stand alone ESSENTIAL sensor

brightness & presence

SK1 | 220-240 V

System 95 W

System 137 lm/W ³

Abmessungen

T-Form

Länge 800 mm | Breite 320 mm | Höhe 1920 mm

12.2 kg


¹ RAL Code

² Wert von umgebendem Produkt bei Vollast (ungedimmt)


³ inkl. Berücksichtigung von optischen, internen

Steuergeräteverlusten & der Effizienz des Betriebsgeräts

Lichtverteilung



Produktskizze



Montageanleitung

