



MOVE IT 25 S system

trimless / surface / suspended

EN Thin extruded aluminium profile with 31mm height and 28mm width groove; optionally for trimless installation in plasterboard ceilings (wall or ceiling mounting) with 12.5mm ceiling thickness; or for wall-/ceiling surface mounting or suspended mounting (cable suspension, height adjustment without tools, incl. black feed); optional with indirect light component for additional accentuation of the ceiling; for lighting systems; linear, 90° angle connectors or 90° CURVE segment; with integrated power track profile for take off of supply voltage and DALI signal; surface anodised or powder coated; insets can be installed flexibly and without tools by means of magnetic holders + locking

DE Niedriges Aluminiumstrangpressprofil mit 31mm Höhe und 28mm Fugenbreite; wahlweise für den randlosen Einbau in Gipskartondecken (Wand- oder Deckenmontage) mit 12,5mm Deckenstärke; oder für Wand-/Deckenanbaumontage oder für abgehängte Montage (Seilabhängung, werkzeuglose Höhenverstellung, inkl. schwarzer Einspeiseseitung); optional mit indirekter Lichtkomponente für zusätzliche Akzentuierung der Decke; für Lichtsysteme; linear, 90° Winkelverbinder oder 90° CURVE Element; mit integriertem Stromschieneprofil für Abnahme von Versorgungsspannung und DALI Signal; Oberfläche eloxiert bzw. pulverbeschichtet; flexible und werkzeuglose Montage der Einsätze durch Magnethalterung + Verriegelung

Quickinfo

3000K
CRI ≥ 90, 2 SDCM
up to 118lm/W
L80 @ 50000h
non DIM, DALI-2

Types



connector



corner

curve


Colours



standard



xal.com/colours



custom cut on
building site

Order options

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

● jet black RAL 9005

Options on request

CONNECTOR

T-connector

X-connector

INSTALLATION TRACK

acoustic soft ceilings



MOVE IT 25 S trimless



INSTALLATION TRACK

L (mm)

| L (mm) | | ORDER CODE |
|-----------|-------------------------------------|-------------|
| 617 | channel | 050-72120-8 |
| 1217 | channel | 050-72140-8 |
| 2417 | channel | 050-72180-8 |
| 3622 | channel | 050-72190-8 |
| cust. cut | channel (non DIM) | E83131-8 |
| cust. cut | channel (DALI-2) | E83141-8 |
| 672x645 | channel corner* 90° | 050-72110-8 |
| 661x661 | channel corner* ceiling to wall 90° | 050-72111-8 |

*incl. electrical connector set

Accessories

END CAPS

TYPE

| TYPE | ORDER CODE |
|-----------------|-------------|
| end caps (pair) | 050-72100-8 |

BLIND COVER

L (mm)

| L (mm) | ORDER CODE |
|------------|-------------|
| 1217 | 050-70040-8 |
| 2417 | 050-70080-8 |
| 3622 | 050-70090-8 |
| custom cut | E83000-8B |

blind cover can be shortened as desired

CONNECTOR SET

TYPE

| TYPE | ORDER CODE |
|------------------------------------|--------------|
| linear connector (non DIM, DALI-2) | 050-20311-30 |
| linear connector flexible | 050-20321-0 |
| mechanical linear connector (pair) | 050-20111-10 |

POWER FEEDER UNIT



TYPE

| TYPE | ORDER CODE |
|-------------------------------------|--------------|
| non DIM 2×2,5mm ² | 050-20201-10 |
| DALI-2 2×2,5 + 2×0,5mm ² | 050-20201-30 |

cable length 500 mm

Electrical accessories

see following pages



Order options

| | |
|----------------|---|
| CONTROL | |
| non DIM | 1 |
| DALI-2 | 3 |

| | |
|---|---|
| MATERIAL COLOUR | |
| ● jet black RAL 9005 | 8 |
| ● traffic white 9016 / jet black 9005 P | |
| ● gold dust 260-M / jet black 9005 G | |
| ● special colours* | X |


*inside always in black

| | |
|------------------------------------|---|
| MATERIAL COLOUR ACCESSORIES | |
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |

| | |
|---|---|
| MATERIAL COLOUR CABLE SUSPENSION | |
| chrome | 0 |
| black | 8 |

Options on request

| | |
|------------------|--|
| CONNECTOR | |
| T-connector | |
| X-connector | |



MOVE IT 25 S surface / suspended



INSTALLATION TRACK / BLIND COVER

| L (mm) | | ORDER CODE |
|---------------------------------|-------------------------------------|-------------|
| 620 | channel | 050-73120 |
| 1220 | channel | 050-73140 |
| 2420 | channel | 050-73180 |
| 3625 | channel | 050-73190 |
| cust. cut | channel (non DIM) | E83151 |
| cust. cut | channel (DALI-2) | E83161 |
| 637x610 | channel corner* 90° | 050-73110 |
| 666x666 | channel corner* ceiling to wall 90° | 050-73111 |
| *incl. electrical connector set | | |
| 1217 | blind cover | 050-7004008 |
| 2417 | blind cover | 050-7008008 |
| 3622 | blind cover | 050-7009008 |
| cust. cut | blind cover | E83000 |

CURVE CONNECTOR

| TYPE | ORDER CODE |
|---------------------------------|------------|
| mechanical & electrical R 300mm | 050-731303 |
| mechanical R 300mm | 050-731311 |

Accessories

END CAPS

| TYPE | ORDER CODE |
|-----------------|------------|
| end caps (pair) | 050-731000 |

CONNECTOR SET

| TYPE | ORDER CODE |
|---|-------------|
| mechanical linear conn. incl. 1500 mm cable susp. | 050-201131 |
| mechanical linear connector surface | 050-2011410 |
| mechanical & electrical linear connector | 050-2031230 |

POWER FEEDER UNIT

| TYPE | L (mm) | ORDER CODE |
|-------------------------------------|--------|-------------|
| non DIM 2x2,5mm ² | 2000 | 050-2022110 |
| DALI-2 2x2,5 + 2x0,5mm ² | 2000 | 050-2022130 |
| non DIM 2x2,5mm ² | 4000 | 050-2024110 |
| DALI-2 2x2,5 + 2x0,5mm ² | 4000 | 050-2024130 |

CEILING FASTENER / CABLE SUSPENSION / CANOPY

| TYPE | L (mm) | ORDER CODE |
|------------------|--------|------------|
| ceiling fastener | 10 | 050-204111 |
| cable suspension | 1500 | 005-215211 |
| canopy | | 005-231171 |

*use every 1200 mm

Electrical accessories

see following pages

Order options

COLOUR TEMPERATURE

3000K

CONTROL

non DIM 1
DALI-2 3

MATERIAL COLOUR

● jet black RAL 9005 8
● traffic white 9016 / jet black 9005 P
● gold dust 260-M / jet black 9005 G
● special colours* X

*inside always in black

MATERIAL COLOUR

ACCESSORIES

○ traffic white RAL 9016 7
● jet black RAL 9005 8

MATERIAL COLOUR

CABLE SUSPENSION

chrome 0
black 8

Options on request

COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM




COLOUR TEMPERATURE

2700K
4000K
tunable white 2700–6500K*

*DALI-2 DT8

CONNECTOR

T-connector
X-connector



MOVE IT 25 S suspended indirect



INSTALLATION TRACK INDIRECT

| L (mm) | SYSTEM POWER | LUMINOUS FLUX | ORDER CODE |
|-----------------|--------------|---------------|------------|
| 620 | 6.2W | 648lm | 050-74125 |
| 1220 | 15.3W | 1810lm | 050-74145 |
| 2420 | 33W | 3890lm | 050-74185 |
| 3625 | 51W | 6000lm | 050-74195 |
| 637x610 corner* | 13.1W | 1550lm | 050-74110 |

no custom cut on building side; *incl. electrical connector set

| | | |
|-----------|-------------|----------------|
| 1217 | blind cover | 050-7004008 |
| 2417 | blind cover | 050-7008008 |
| 3622 | blind cover | 050-7009008 |
| cust. cut | blind cover | E83000 ···· 8B |

Accessories

END CAPS

| TYPE | ORDER CODE |
|-----------------|------------|
| end caps (pair) | 050-731000 |

CONNECTOR SET

| TYPE | ORDER CODE |
|---|-------------|
| mechanical linear conn. incl. 1500 mm cable susp. | 050-201131 |
| mechanical & electrical linear connector | 050-2031230 |

POWER FEEDER UNIT

| TYPE | L (mm) | ORDER CODE |
|--|--------|-------------|
| non DIM 2 × 2,5 mm ² | 2000 | 050-2022110 |
| DALI-2 2 × 2,5 + 2 × 0,5 mm ² | 2000 | 050-2022130 |
| non DIM 2 × 2,5 mm ² | 4000 | 050-2024110 |
| DALI-2 2 × 2,5 + 2 × 0,5 mm ² | 4000 | 050-2024130 |

CABLE SUSPENSION / CANOPY

| TYPE | L (mm) | ORDER CODE |
|------------------|--------|------------|
| cable suspension | 1500 | 005-215211 |
| canopy | | 005-231171 |

*use every 1200 mm

Electrical accessories

see following pages




Quickinfo

3000K
CRI ≥ 90, 2 SDCM
up to 118lm/W
L80 @ 50000h
non DIM, DALI-2

Types



connectors



Colours



MOVE IT 25 system

trimless / surface / suspended

EN Extruded aluminium profile with 28 mm width groove; for trimless installation in plasterboard ceilings (wall or ceiling mounting) with 12.5mm ceiling thickness; or for wall/ ceiling surface mounting or suspended mounting (cable suspension, height adjustment without tools, incl. black feed); optional indirect light component for additional accentuation of the ceiling; for lighting systems; linear, 90° angle connectors or 90° CURVE segment; node connectors, up to 6 profile connection options; with power track profile for take off of supply voltage and DALI signal; surf. anod. or powder coated; insets can be installed flexibly and without tools by means of magnetic holders + locking; sound absorbing accessories available

DE Aluminiumstrangpressprofil mit 28 mm Fugenbreite; für randlosen Einbau in Gipskartondecken (Wand- oder Deckenmontage) mit 12,5 mm Deckenstärke; oder für Wand/ Deckenanbaumontage oder für abgehängte Montage (Seilabhängung, werkzeuglose Höhenverstellung, inkl. schwarzer Einspeiseleitung); optional indirekte Lichtkomponente für zusätzliche Akzentuierung der Decke; für Lichtsysteme; linear, 90° Winkelverbinder oder 90° CURVE Element; Knotenverbinder, bis zu 6 Profilanschlussmöglichkeiten; mit Stromschienenprofil für Abnahme von Versorgungsspannung und DALI Signal; Oberfl. elox. bzw. pulverbeschichtet; flexible und werkzeuglose Montage der Einsätze durch Magnethalterung + Verriegelung; schallabsorbierendes Zubehör erhältlich



custom cut on building site



acoustic elements

Order options

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

| |
|----------------------|
| ● jet black RAL 9005 |
|----------------------|

Options on request

CONNECTOR

| |
|-------------|
| T-connector |
| X-connector |

INSTALLATION TRACK

| |
|------------------------|
| acoustic soft ceilings |
|------------------------|



MOVE IT 25 trimless



INSTALLATION TRACK

| L (mm) | | ORDER CODE |
|-----------|-------------------------------------|-------------|
| 617 | channel | 050-72020-8 |
| 1217 | channel | 050-72040-8 |
| 2417 | channel | 050-72080-8 |
| 3622 | channel | 050-72090-8 |
| cust. cut | channel (non DIM) | E83031-8 |
| cust. cut | channel (DALI-2) | E83041-8 |
| 672x645 | channel corner* 90° | 050-72010-8 |
| 661x661 | channel corner* ceiling to wall 90° | 050-72011-8 |

*incl. electrical connector set

Accessories

END CAPS

| TYPE | ORDER CODE |
|-----------------|-------------|
| end caps (pair) | 050-72000-8 |



BLIND COVER

| L (mm) | ORDER CODE |
|------------|-------------|
| 1217 | 050-70040-8 |
| 2417 | 050-70080-8 |
| 3622 | 050-70090-8 |
| custom cut | E83000-8B |



blind cover can be shortened as desired

CONNECTOR SET

| TYPE | ORDER CODE |
|------------------------------------|--------------|
| linear connector (non DIM, DALI-2) | 050-20311-30 |
| linear connector flexible | 050-20321-0 |
| mechanical linear connector (pair) | 050-20111-10 |



POWER FEEDER UNIT

| TYPE | ORDER CODE |
|-------------------------------------|--------------|
| non DIM 2x2,5mm ² | 050-20201-10 |
| DALI-2 2x2,5 + 2x0,5mm ² | 050-20201-30 |



cable length 500 mm

Electrical accessories

see following pages

Order options

| | |
|----------------|---|
| CONTROL | ◆ |
| non DIM | 1 |
| DALI-2 | 3 |

| | |
|---|---|
| MATERIAL COLOUR | ■ |
| INSTALLATION TRACK | ■ |
| ● jet black RAL 9005 | 8 |
| ○ traffic white 9016 / jet black 9005 P | |
| ● gold dust 260-M / jet black 9005 G | |
| ● special colours* | X |

*inside always in black

| | |
|--------------------------|---|
| MATERIAL COLOUR | ■ |
| NODE CONNECTOR | ■ |
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |
| ● special colours | X |

| | |
|---|---|
| MATERIAL COLOUR | ■ |
| NODE LTX/END CAP | ■ |
| ● jet black RAL 9005 | 8 |
| ○ traffic white 9016 / jet black 9005 P | |
| ● special colours | X |

| | |
|--------------------------|---|
| MATERIAL COLOUR | ■ |
| ACCESSORIES | ■ |
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |

| | |
|-------------------------|---|
| MATERIAL COLOUR | □ |
| CABLE SUSPENSION | □ |
| chrome | 0 |
| black | 8 |

| | |
|----------------------------|---|
| NODE CONNECTOR | ⊕ |
| MOUNTING TYPE | ⊕ |
| surface* | 1 |
| 1500 mm cable susp. chrome | 3 |
| 1500 mm cable susp. black | 4 |

*only for L/T/X



MOVE IT 25 surface / suspended



INSTALLATION TRACK / BLIND COVER

| L (mm) | | ORDER CODE |
|---------------------------------|-------------------------------------|----------------|
| 620 | channel | 050-73020 |
| 1220 | channel | 050-73040 |
| 2420 | channel | 050-73080 |
| 3625 | channel | 050-73090 |
| cust. cut | channel (non DIM) | E83051 |
| cust. cut | channel (DALI-2) | E83061 |
| 637x610 | channel corner* 90° | 050-73010 |
| 666x666 | channel corner* ceiling to wall 90° | 050-73011 |
| *incl. electrical connector set | | |
| 1217 | blind cover | 050-7004008 |
| 2417 | blind cover | 050-7008008 |
| 3622 | blind cover | 050-7009008 |
| cust. cut | blind cover | E83000 ···· 8B |

CURVE CONNECTOR

| TYPE | ORDER CODE |
|----------------------------------|------------|
| mechanical & electrical R 300 mm | 050-730303 |
| mechanical R 300 mm | 050-730311 |

Accessories

END CAPS

| TYPE | ORDER CODE |
|-----------------|------------|
| end caps (pair) | 050-730000 |

FLEX NODE CONNECTOR

| TYPE | ORDER CODE |
|--|------------|
| FLEX NODE surface mounted | 050-203333 |
| FLEX NODE surface mounted incl. feeder | 050-202243 |
| FLEX NODE cable suspension 1500 mm | 050-203311 |
| FLEX NODE cable susp. 1500 mm incl. feeder | 050-202222 |
| NODE end cap* incl. electrical connector | 050-730010 |

*order for every node connection (channel to node) 1 end cap

CONNECTOR SET

| TYPE | ORDER CODE |
|---|------------|
| mechanical linear conn. incl. 1500 mm cable susp. | 050-201131 |
| mechanical linear connector surface | 050-201141 |
| mechanical & electrical linear connector | 050-203123 |

POWER FEEDER UNIT

| TYPE | L (mm) | ORDER CODE |
|--------------------------------------|--------|-------------|
| non DIM 2×2,5 mm ² | 2000 | 050-2022110 |
| DALI-2 2×2,5 + 2×0,5 mm ² | 2000 | 050-2022130 |
| non DIM 2×2,5 mm ² | 4000 | 050-2024110 |
| DALI-2 2×2,5 + 2×0,5 mm ² | 4000 | 050-2024130 |

CEILING FASTENER / CABLE SUSPENSION / CANOPY

| TYPE | L (mm) | ORDER CODE |
|--------------------------------|--------|------------|
| ceiling fastener | 10 | 050-204111 |
| cable susp. (use very 1200 mm) | 1500 | 005-215211 |
| canopy | | 005-231171 |

Electrical accessories

see following pages

Acoustic elements

see following pages

Order options

COLOUR TEMPERATURE

3000K

CONTROL

non DIM 1
DALI-2 3

MATERIAL COLOUR INSTALLATION TRACK

● jet black RAL 9005 8
● traffic white 9016 / jet black 9005 P
● gold dust 260-M / jet black 9005 G
● special colours* X

*inside always in black

MATERIAL COLOUR NODE CONNECTOR

○ traffic white RAL 9016 7
● jet black RAL 9005 8
● special colours X

MATERIAL COLOUR NODE LTX/END CAP

● jet black RAL 9005 8
● traffic white 9016 / jet black 9005 P
● special colours X

MATERIAL COLOUR ACCESSORIES

○ traffic white RAL 9016 7
● jet black RAL 9005 8

MATERIAL COLOUR CABLE SUSPENSION

chrome 0
black 8

NODE CONNECTOR MOUNTING TYPE

surface* 1
1500 mm cable susp. chrome 3
1500 mm cable susp. black 4

*only for L/T/X

Options on request

COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE

2700 K
4000 K
tunable white 2700–6500 K*

*DALI-2 DT8

LUMINOUS FLUX value calculated for 3000K, CRI ≥ 90, colour white/black



MOVE IT 25 suspended indirect



INSTALLATION TRACK INDIRECT

| L (mm) | SYSTEM POWER | LUMINOUS FLUX | ORDER CODE |
|-----------------|--------------|---------------|------------|
| 620 | 6.2W | 648lm | 050-74025 |
| 1220 | 15.3W | 1810lm | 050-74045 |
| 2420 | 33W | 3890lm | 050-74085 |
| 3625 | 51W | 6000lm | 050-74095 |
| 637x610 corner* | 13.1W | 1550lm | 050-74010 |

*incl. electrical connector set

| | | |
|-----------|-------------|----------------|
| 1217 | blind cover | 050-7004008 |
| 2417 | blind cover | 050-7008008 |
| 3622 | blind cover | 050-7009008 |
| cust. cut | blind cover | E83000 ···· 8B |

Accessories

END CAPS

| TYPE | ORDER CODE |
|-----------------|------------|
| end caps (pair) | 050-730000 |

FLEX NODE CONNECTOR

| TYPE | ORDER CODE |
|---|------------|
| FLEX NODE cable suspension 1500mm | 050-20331 |
| FLEX NODE cable susp. 1500mm incl. feeder | 050-20222 |
| FLEX NODE end cap* incl. electrical connector | 050-730010 |

*order for every node connection (channel to node) 1 end cap

CONNECTOR SET

| TYPE | ORDER CODE |
|--|-------------|
| mechanical linear conn. incl. 1500mm cable susp. | 050-201131 |
| mechanical & electrical linear connector | 050-2031230 |




POWER FEEDER UNIT

| TYPE | L (mm) | ORDER CODE |
|---|--------|-------------|
| non DIM 2 × 2,5mm ² | 2000 | 050-2022110 |
| DALI-2 2 × 2,5 + 2 × 0,5mm ² | 2000 | 050-2022130 |
| non DIM 2 × 2,5mm ² | 4000 | 050-2024110 |
| DALI-2 2 × 2,5 + 2 × 0,5mm ² | 4000 | 050-2024130 |

CABLE SUSPENSION / CANOPY

| TYPE | L (mm) | ORDER CODE |
|-------------------|--------|------------|
| cable suspension* | 1500 | 005-215211 |
| canopy | | 005-231171 |

*use every 1200 mm



Electrical accessories

see following pages

Acoustic elements

see following pages





Order options

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |



Electrical accessories

POWER SUPPLY INTRACK supply 220-240 V AC, 48 V, 50-60 Hz

| TYPE | EFFICIENCY | MOUNTING | L-W-H (mm) | ORDER CODE |
|--------------------------|------------|----------|------------|-------------|
| 100 W PC II η 92 % | | intrack | 403-26-46 | 050-2071038 |
| 150 W PC II η 92 % | | intrack | 403-26-46 | 050-2071138 |

ENEC approved; DALI-2 SELV device integrated

POWER SUPPLY SURFACE supply 220-240 V AC, 48 V, 50-60 Hz

| TYPE | EFFICIENCY | MOUNTING | L-W-H (mm) | ORDER CODE |
|--------------------------|------------|----------|------------|------------|
| 60 W PC II η 88 % | | surface | 305-144-54 | 050-20551 |
| 100 W PC II η 92 % | | surface | 455-104-40 | 050-20554 |
| 150 W PC II η 92 % | | surface | 455-104-40 | 050-20552 |
| 250 W PC II η 93 % | | surface | 455-104-40 | 050-20555 |
| 320 W PC I η 94 % | | surface | 305-144-54 | 050-20553 |

ENEC approved; DALI-2 SELV device integrated

POWER SUPPLY EXTERNAL supply 220-240 V AC, 48 V, 50-60 Hz

| TYPE | EFFICIENCY | MOUNTING | L-W-H (mm) | ORDER CODE |
|--------------------------|------------|----------|------------|------------|
| 60 W PC II η 88 % | | external | 163-43-32 | 002-62133 |
| 100 W PC II η 92 % | | external | 350-30-18 | 002-62134 |
| 150 W PC II η 92 % | | external | 350-30-18 | 002-62135 |
| 250 W PC II η 93 % | | external | 400-40-22 | 002-62139 |
| 320 W PC I η 94 % | | external | 252-90-44 | 002-60320 |

ENEC approved

POWER SUPPLY BASIC 48 V

220-240 V | 50-60 Hz | PC II | Lifetime @ 120 W, 45° ambient temp. cascable max. 3 devices

| TYPE | EFFICIENCY/LIFETIME | W-H-D (mm) | ORDER CODE |
|---------------------------------|---------------------|------------|-------------|
| 160 W η 94.5% / > 100.000h | | 72-90-63 | 005-6520210 |

DIN RAIL POWER SUPPLY PRO 48 V

220-240 V | 50-60 Hz | PC I | MTBF @ 55° ambient temperature cascable max. 5 devices (240 W) or 3 devices (480 W)

| TYPE | EFFICIENCY/MTBF | W-H-D (mm) | ORDER CODE |
|-------------------------------|-----------------|-------------|-------------|
| 240 W η 92% / > 400.000h | | 60-125-100 | 005-6220110 |
| 480 W η 93% / > 350.000h | | 120-125-100 | 005-6220210 |

DALI-2 SELV DEVICE

| TYPE | L-W-H (mm) | ORDER CODE |
|--------------|------------|-------------|
| control unit | 213-37-25 | 050-2061130 |

necessary to create DALI-2 SELV signal; DALI power supply integrated

DALI SENSOR

| TYPE | L-W-H (mm) | ORDER CODE |
|--|------------|-------------|
| ESSENTIAL sensor (brightness & presence) | 125-28-45 | 050-2063178 |

WIRELESS TO DALI-2 CONTROL DEVICE

| TYPE | L-W-H (mm) | ORDER CODE |
|---------|------------|-------------|
| Casambi | 111-25-45 | 050-2065230 |

DALI-2 SELV device required


WIRELESS TO DALI-2 REPEATER

| TYPE | L-W-H (mm) | ORDER CODE |
|---------|------------|-------------|
| Casambi | 111-25-45 | 050-2066230 |

MIDDLE FEED

| TYPE | ORDER CODE |
|--|-------------|
| DALI-2 2 × 2,5 + 2 × 0,5 mm ² cable length 2000 mm | 050-2038130 |

Blique by Nobis
Stockholm, SE –
by Wingårdhs





JUST

spotlight inset 25/25S

Quickinfo


2700K, 3000K, 4000K, TW, CWD
 CRI ≥ 90, 2 SDCM
 non DIM, DALI-2

L95 @ 50 000h
 JUST 32 focus up to 47lm/W

L80 @ 50 000h
 JUST 45 up to 72lm/W

L90 @ 50 000h
 JUST 55 up to 79lm/W

Types



Colours




Light distributions

JUST 32 focus



JUST 45



JUST 55



Order options

| COLOUR TEMPERATURE | |
|------------------------------|---|
| 2700K | 4 |
| 3000K | 5 |
| 4000K | 6 |
| colour warm dim. 2000–3000K* | |
| tunable white 1800–3000K** | |
| tunable white 2700–6500K** | |

*DALI-2 **DALI-2 DT8

| CONTROL | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

| MATERIAL COLOUR | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |
| 🌈 special colours | X |

| BEAM ANGLE JUST 45 | |
|--------------------|---|
| medium 23° | M |
| flood 44° | F |


| BEAM ANGLE JUST 55 | |
|--------------------|---|
| spot 16° | S |
| medium 23° | M |
| flood 37° | F |

Options on request

OPTICAL ACCESSORIES

| | |
|--|--|
| elliptical sculpture foil | |
| snoot | |
| colour filter (red, blue, green, etc.) | |

only for JUST 32 focus



JUST 32 focus 17–43°



SPOTLIGHT

| INSET POWER | LUMINOUS FLUX | ORDER CODE |
|-------------|---------------|------------|
| 8.3W | 393lm | 050-01111 |

JUST 45



SPOTLIGHT

| INSET POWER | LUMINOUS FLUX | ORDER CODE |
|--------------------|---------------|------------|
| 6.1W super spot 8° | 297lm | 050-01311 |
| 11W | 788lm | 050-01311 |
| 12W CWD 2000–3000K | 430lm | 050-0131E3 |
| 11W TW 1800–3000K | 555lm | 050-0131L3 |
| 11W TW 2700–6500K | 683lm | 050-0131D3 |

JUST 55



SPOTLIGHT

| INSET POWER | LUMINOUS FLUX | ORDER CODE |
|-------------|---------------|------------|
| 15.9W | 1300lm | 050-01433 |
| 25.4W | 1750lm | 050-01423 |

Optical accessories

HONEYCOMB LOUVER

| TYPE | Ø-H (mm) | ORDER CODE |
|---------------|----------|-------------|
| JUST 32 focus | 30·4 | 007-1965178 |
| JUST 45 | 42·3 | 007-1965188 |
| JUST 55 | 50·3 | 007-1965598 |

OVAL LENS

| TYPE | Ø-H (mm) | ORDER CODE |
|-------|----------|-------------|
| BO 45 | 42·3 | 007-1965880 |
| BO 55 | 50·3 | 007-1965890 |

SOFT LENS

| TYPE | Ø-H (mm) | ORDER CODE |
|-------|----------|-------------|
| BO 45 | 42·3 | 007-1965980 |
| BO 55 | 50·3 | 007-1965990 |


WALLWASHER LENS

| TYPE | Ø-H (mm) | ORDER CODE |
|-------|----------|-------------|
| BO 45 | 42·3 | 007-1965780 |
| BO 55 | 50·3 | 007-1965790 |

INSET POWER in watts is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for 3000K, CRI ≥90, colour white, lens flood 2700K -5%, 4000K +5%

Quickinfo

2700 K, 3000 K, TW
 CRI \geq 90, 3 SDCM
 up to 123 lm/W
 L90 @ 50 000 h
 non DIM, DALI-2

Types**Colour****Light distribution**

reddot award 2019
winner




PIVOT

graphic light inset 25/25S



tunable white
1800–4000 K



CRI \geq 98
XPECTRUM

Order options

COLOUR TEMPERATURE

| | |
|----------------------------|---|
| 2700 K | 4 |
| 3000 K | 5 |
| tunable white 1800–4000 K* | L |

*DALI-2 DT8

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

● jet black RAL 9005

Options on request

COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE

4000 K

MATERIAL COLOUR

○ traffic white RAL 9016



LIGHT INSET 25S




PIVOT

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|------------------------|
| 10.6 W | 2700 K | 1190 lm | 610 | 0 5 0 - 1 3 1 2 :: 8 0 |
| | 3000 K | 1260 lm | | |
| 15.9 W | 2700 K | 1780 lm | 910 | 0 5 0 - 1 3 1 3 :: 8 0 |
| | 3000 K | 1890 lm | | |
| 21.2 W | 2700 K | 2380 lm | 1210 | 0 5 0 - 1 3 1 4 :: 8 0 |
| | 3000 K | 2530 lm | | |
| 26.4 W | 2700 K | 2970 lm | 1510 | 0 5 0 - 1 3 1 5 :: 8 0 |
| | 3000 K | 3160 lm | | |
| 32 W | 2700 K | 3570 lm | 1810 | 0 5 0 - 1 3 1 6 :: 8 0 |
| | 3000 K | 3790 lm | | |



PIVOT SUSPENDED

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|------------------------|
| 10.6 W | 2700 K | 1190 lm | 610 | 0 5 0 - 0 3 2 2 :: 8 0 |
| | 3000 K | 1260 lm | | |
| 15.9 W | 2700 K | 1780 lm | 910 | 0 5 0 - 0 3 2 3 :: 8 0 |
| | 3000 K | 1890 lm | | |
| 21.2 W | 2700 K | 2380 lm | 1210 | 0 5 0 - 0 3 2 4 :: 8 0 |
| | 3000 K | 2530 lm | | |
| 26.4 W | 2700 K | 2970 lm | 1510 | 0 5 0 - 0 3 2 5 :: 8 0 |
| | 3000 K | 3160 lm | | |



LIGHT INSET 25



PIVOT

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|------------------------|
| 10.6 W | 2700 K | 1190 lm | 610 | 0 5 0 - 0 3 1 2 :: 8 0 |
| | 3000 K | 1260 lm | | |
| 15.9 W | 2700 K | 1780 lm | 910 | 0 5 0 - 0 3 1 3 :: 8 0 |
| | 3000 K | 1890 lm | | |
| 21.2 W | 2700 K | 2380 lm | 1210 | 0 5 0 - 0 3 1 4 :: 8 0 |
| | 3000 K | 2530 lm | | |
| 26.4 W | 2700 K | 2970 lm | 1510 | 0 5 0 - 0 3 1 5 :: 8 0 |
| | 3000 K | 3160 lm | | |
| 32 W | 2700 K | 3570 lm | 1810 | 0 5 0 - 0 3 1 6 :: 8 0 |
| | 3000 K | 3790 lm | | |



PIVOT SUSPENDED

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|------------------------|
| 10.6 W | 2700 K | 1190 lm | 610 | 0 5 0 - 0 3 2 2 :: 8 0 |
| | 3000 K | 1260 lm | | |
| 15.9 W | 2700 K | 1780 lm | 910 | 0 5 0 - 0 3 2 3 :: 8 0 |
| | 3000 K | 1890 lm | | |
| 21.2 W | 2700 K | 2380 lm | 1210 | 0 5 0 - 0 3 2 4 :: 8 0 |
| | 3000 K | 2530 lm | | |
| 26.4 W | 2700 K | 2970 lm | 1510 | 0 5 0 - 0 3 2 5 :: 8 0 |
| | 3000 K | 3160 lm | | |

LUMINOUS FLUX value calculated for CRI ≥ 90, colour black



FLESTRACK

system extension 25/25S

EN Thin extruded aluminium profile with 31mm height and 28mm width groove; with integrated power track profile for take off of supply voltage and DALI signal; surface anodised or powder coated; for installation in two MOVE IT 25 or 25 S profiles; profile can be installed and moved without tools by means of magnetic holders + locking; mount 360° rotatable and freely slidable on one end; light insets can be installed flexibly and without tools by means of magnetic holders+locking

DE Niedriges Aluminiumstrangpressprofil mit 31mm Höhe und 28mm Fugenbreite; mit integriertem Stromschienenprofil für Abnahme von Versorgungsspannung und DALI Signal; Oberfläche eloxiert bzw. pulverbeschichtet; zum Einsetzen in zwei MOVE IT 25 bzw. MOVE IT 25 S Profile; Profil mittels Magnethalter+Verriegelung werkzeuglos einsetz- und verschiebbar; Halterung 360° drehbar und an einem Ende beliebig verschiebbar; flexible und werkzeuglose Montage der Lichteinsätze durch Magnethalterung + Verriegelung

Quickinfo

non DIM, DALI-2

Types



Colours



Order options

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

| | |
|---|---|
| ● jet black RAL 9005 | 8 |
| ● traffic white 9016 / jet black 9005 P | |
| ● gold dust 260-M / jet black 9005 G | |
| ● special colours* | X |

*inside always in black

MOVE IT 25 S



FLEXTRACK

| L (mm) | ORDER CODE |
|--------|------------|
| 620 | 050-75120 |
| 920 | 050-75130 |
| 1220 | 050-75140 |
| 1520 | 050-75150 |
| 1820 | 050-75160 |

MOVE IT 25



FLEXTRACK

| L (mm) | ORDER CODE |
|--------|------------|
| 620 | 050-75020 |
| 920 | 050-75030 |
| 1220 | 050-75040 |
| 1520 | 050-75050 |
| 1820 | 050-75060 |



Quickinfo

2700 K, 3000 K, 4000 K, TW
 CRI ≥ 90, 3 SDCM
 up to 84 lm/W
 L90 @ 50 000h
 non DIM, DALI-2

Types



Colours



Light distributions



ARY rod
 decorative inset 25/25S



Order options

CABLE SUSPENSION

| | |
|--------------------|---|
| 1500 mm | 5 |
| 2000 mm with hook* | 6 |

*one ring included

COLOUR TEMPERATURE

| | |
|----------------------------|---|
| 2700 K | 4 |
| 3000 K | 5 |
| 4000 K | 6 |
| tunable white 2200–4000 K* | |

*DALI-2 DT8

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR


| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |
| ● special colours | X |

ACCESSORY COLOUR

| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |

BEAM ANGLE

| | |
|------------|---|
| medium 25° | M |
| flood 44° | F |



ARY rod



DOWNLIGHT


| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|-------------|--------------|---------------|-----------------|
| 14 W | 2700 K | 1050 lm | 050-0 3 2 1 |
| | 3000 K | 1100 lm | |
| | 4000 K | 1180 lm | |
| 5.4 W TW | 2200–4000 K | 284 lm | 050-0 3 2 1 D 3 |

ARY rod adjustable



SPOTLIGHT


| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|-------------|--------------|---------------|-----------------|
| 14 W | 2700 K | 1050 lm | 050-0 3 3 1 |
| | 3000 K | 1100 lm | |
| | 4000 K | 1180 lm | |
| 5.4 W TW | 2200–4000 K | 284 lm | 050-0 3 3 1 D 3 |



Mounting accessories

RING track mounted

| TYPE | Ø-H (mm) | ORDER CODE |
|--------------|----------|------------|
| MOVE IT 25 S | 50-70 | 050-151011 |
| MOVE IT 25 | 50-91 | 050-051011 |



RING ceiling mounted

| TYPE | Ø-H (mm) | ORDER CODE |
|----------------|----------|------------|
| MOVE IT 25S/25 | 50-88 | 050-051021 |






Quickinfo

2700 K, 3000 K, 4000 K, TW
 CRI ≥ 90, 3 SDCM
 up to 84 lm/W
 L90 @ 50 000h
 non DIM, DALI-2

Types



Colours



Light distributions



ARY cable
 decorative inset 25/25S





Quickinfo

2700 K, 3000 K, TW
 CRI ≥ 90, 3 SDCM
 up to 75 lm/W
 L80 @ 50 000 h
 non DIM, DALI-2

Types



Colours



Light distributions



TULA

decorative inset 25/25S



free positioning by
ring and hook



tunable white
2200 – 4000 K

Order options

HOUSING HEIGHT

| | |
|--------|---|
| 300 mm | 0 |
| 500 mm | 1 |

CABLE SUSPENSION

| | |
|--------------------|---|
| 1500 mm | 7 |
| 2000 mm with hook* | 8 |

*one ring included

COLOUR TEMPERATURE

| | |
|------------------------------|---|
| 2700 K | 4 |
| 3000 K | 5 |
| tunable white 2200 – 4000 K* | |

*DALI-2 DT8

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

| | |
|--------------------------|---|
| Ø chrome | 4 |
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |
| ● special colours | X |

ACCESSORY COLOUR

| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |

BEAM ANGLE

| | |
|------------|---|
| medium 25° | M |
| flood 44° | F |

Options on request

COLOUR TEMPERATURE

4000 K



TULA nano suspended



DOWNLIGHT

| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|-------------|--------------|---------------|------------|
| 11W | 2700K | 642lm | 050-L 11 1 |
| | 3000K | 688lm | |



TULA micro suspended



DOWNLIGHT

| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|-------------|--------------|---------------|--------------|
| 14W | 2700K | 998lm | 050-L 15 1 |
| | 3000K | 1048lm | |
| 5.4W | 2200 – 4000K | 254lm | 050-L 15 D 3 |

Mounting accessories

RING track mounted



| TYPE | Ø-H (mm) | ORDER CODE |
|--------------|----------|------------|
| MOVE IT 25 S | 50-70 | 050-151011 |
| MOVE IT 25 | 50-91 | 050-051011 |

RING ceiling mounted




| TYPE | Ø-H (mm) | ORDER CODE |
|----------------|----------|------------|
| MOVE IT 25S/25 | 50-88 | 050-051021 |



Quickinfo

2700 K, 3000 K
CRI \geq 90, 3 SDCM
up to 55 lm/W
L80 @ 50 000 h
non DIM, DALI-2

Types



Colours



Light distribution



opal

Order options

CABLE SUSPENSION

| | |
|--------------------|---|
| 1500 mm | 5 |
| 2000 mm with hook* | 6 |

*one ring included

COLOUR TEMPERATURE

| | |
|--------|---|
| 2700 K | 4 |
| 3000 K | 5 |

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

| | |
|-----------------------|---|
| ○ pure white RAL 9010 | 7 |
| ● jet black RAL 9005 | 8 |
| ● special colours | X |

ACCESSORY COLOUR

| | |
|-----------------------|---|
| ○ pure white RAL 9010 | 7 |
| ● jet black RAL 9005 | 8 |



PAL suspended



DOWNLIGHT

| INS. POWER | COLOUR TEMP. | LUM. FLUX | Ø (mm) | ORDER CODE |
|------------|--------------|-----------|--------|-------------|
| 9.1W | 2700K | 472lm | 80 | 050-1 8 1 1 |
| | 3000K | 498lm | | |
| 9.1W | 2700K | 472lm | 120 | 050-1 8 1 3 |
| | 3000K | 498lm | | |

Mounting accessories

RING track mounted

| TYPE | Ø-H (mm) | ORDER CODE |
|--------------|----------|------------|
| MOVE IT 25 S | 50-70 | 050-151011 |
| MOVE IT 25 | 50-91 | 050-051011 |



RING ceiling mounted

| TYPE | Ø-H (mm) | ORDER CODE |
|----------------|----------|------------|
| MOVE IT 25S/25 | 50-88 | 050-051021 |



INSET POWER in watts is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour white, glass

**Quickinfo**

2700 K
CRI ≥ 95, 3 SDCM
up to 72 lm/W
L90 @ 50 000h
non DIM, DALI-2

Types**Colours**

wästberg w201 Extra small pendant

Design by Claesson Koivisto Rune

Order options

| CABLE SUSPENSION | |
|-------------------|---|
| 3000 mm | 5 |
| 3000 mm with hook | 6 |

| COLOUR TEMPERATURE | |
|--------------------|--|
| 2700 K | |

| CONTROL | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

| MATERIAL COLOUR | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |


| ACCESSORY COLOUR | |
|-----------------------|---|
| ○ pure white RAL 9010 | 7 |
| ● jet black RAL 9005 | 8 |



w201 Extra small pendant s1




| DOWNLIGHT | INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|-----------|-------------|--------------|---------------|------------|
| | 7.9W | 2700 K | 544lm | 050-04814 |



w201 Extra small pendant s2



| DOWNLIGHT | INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|-----------|-------------|--------------|---------------|------------|
| | 7.9W | 2700 K | 572lm | 050-04824 |




w201 Extra small pendant s3



| DOWNLIGHT | INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|-----------|-------------|--------------|---------------|------------|
| | 7.9W | 2700 K | 572lm | 050-04834 |

Mounting accessories



| RING track mounted | | Ø-H (mm) | ORDER CODE |
|--------------------|--|----------|------------|
| TYPE | | | |
| MOVE IT 25 S | | 50-70 | 050-151011 |
| MOVE IT 25 | | 50-91 | 050-051011 |



| RING ceiling mounted | | Ø-H (mm) | ORDER CODE |
|----------------------|--|----------|------------|
| TYPE | | | |
| MOVE IT 25S/25 | | 50-88 | 050-051021 |

INSET POWER in watts is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI≥90, colour white



SPOT LINE / OPAL

linear inset 25

Quickinfo

2700 K, 3000 K, TW (opal)
 CRI ≥ 90, 3 SDCM
 SPOT LINE up to 80 lm/W
 OPAL up to 101 lm/W
 L80 @ 50 000 h
 non DIM, DALI-2

Types

MOVE IT 25

SPOT LINE



OPAL



Light distributions



tunable white
 1800–4000 K



CRI ≥ 98
 XPECTRUM

Order options

COLOUR TEMPERATURE

| | |
|----------------------------|---|
| 2700 K | 4 |
| 3000 K | 5 |
| tunable white 1800–4000 K* | L |

*only available for opal high performance inset | DALI-2 DT8

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

● jet black RAL 9005

Options on request

COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE

4000 K



LIGHT INSET 25



SPOT LINE

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|------------------------|
| 3 × 1.4 W | 2700 K | 309lm | 155 | 0 5 0 - 0 2 2 0 :: 8 M |
| | 3000 K | 336lm | | |
| 6 × 1.4 W | 2700 K | 618lm | 305 | 0 5 0 - 0 2 2 1 :: 8 M |
| | 3000 K | 672lm | | |
| 12 × 1.4 W | 2700 K | 1240lm | 605 | 0 5 0 - 0 2 2 2 :: 8 M |
| | 3000 K | 1340lm | | |



OPAL HIGH PERFORMANCE

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|------------------------|
| 5.3 W | 2700 K | 451lm | 305 | 0 5 0 - 0 2 1 1 :: 8 H |
| | 3000 K | 484lm | | |
| 10.6 W | 2700 K | 902lm | 605 | 0 5 0 - 0 2 1 2 :: 8 H |
| | 3000 K | 968lm | | |
| 21.3 W | 2700 K | 1800lm | 1205 | 0 5 0 - 0 2 1 4 :: 8 H |
| | 3000 K | 1940lm | | |
| 43 W | 2700 K | 3610lm | 2405 | 0 5 0 - 0 2 1 8 :: 8 H |
| | 3000 K | 3870lm | | |



LIGHT INSET 25 S



OPAL HIGH PERFORMANCE

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|------------------------|
| 5.3 W | 2700 K | 402lm | 305 | 0 5 0 - 1 2 1 1 :: 8 H |
| | 3000 K | 432lm | | |
| 10.6 W | 2700 K | 805lm | 605 | 0 5 0 - 1 2 1 2 :: 8 H |
| | 3000 K | 864lm | | |
| 21.3 W | 2700 K | 1610lm | 1205 | 0 5 0 - 1 2 1 4 :: 8 H |
| | 3000 K | 1730lm | | |
| 43 W | 2700 K | 3220lm | 2405 | 0 5 0 - 1 2 1 8 :: 8 H |
| | 3000 K | 3460lm | | |

canyon solution for MOVE IT 25

Light distribution



spot line

INSET POWER in watts is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour black



MOVE IT 25 SYSTEM



WALLWASHER

linear inset 25/25S


Quickinfo

2700 K, 3000 K
CRI \geq 90, 3 SDCM
WALLWASHER up to 81lm/W
WW flush up to 82lm/W
L80 @ 50 000 h
non DIM, DALI-2

Types

MOVE IT 25

WALLWASHER



WALLWASHER flush



MOVE IT 25 S


WALLWASHER flush



Light distribution



wall washer



CRi \geq 98
XPPECTRUM

Order options

| | |
|---------------------------|----|
| COLOUR TEMPERATURE | ☼☼ |
| 2700 K | 4 |
| 3000 K | 5 |

| | |
|----------------|------|
| CONTROL | ⬆️⬆️ |
| non DIM | 1 |
| DALI-2 | 3 |

| | |
|------------------------|--|
| MATERIAL COLOUR | |
| ● jet black RAL 9005 | |

Options on request

| | |
|-------------------------------|--|
| COLOUR RENDERING INDEX | |
| CRI ≥ 98 XPECTRUM | |

| | |
|---------------------------|--|
| COLOUR TEMPERATURE | |
| 4000 K | |



LIGHT INSET 25



WALLWASHER

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|------------------|
| 13 W | 2700 K | 983lm | 450 | 050-0232 ☼☼ 38 A |
| | 3000 K | 1050lm | | |



WALLWASHER FLUSH

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|-----------------|
| 5.6 W | 2700 K | 415lm | 305 | 050-0211 ☼☼ 8 A |
| | 3000 K | 454lm | | |
| 11.2 W | 2700 K | 829lm | 605 | 050-0212 ☼☼ 8 A |
| | 3000 K | 908lm | | |
| 22.3 W | 2700 K | 1660lm | 1205 | 050-0214 ☼☼ 8 A |
| | 3000 K | 1820lm | | |
| 45 W | 2700 K | 3320lm | 2405 | 050-0218 ☼☼ 8 A |
| | 3000 K | 3630lm | | |

Optical accessories

ANTI-GLARE GRID

| TYPE | L-W (mm) | ORDER CODE |
|------------------|----------|-------------|
| WALLWASHER FLUSH | 303-25 | 050-0230918 |

cluster solution to create anti-glare grid for all lengths



LIGHT INSET 25 S



WALLWASHER FLUSH

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|-----------------|
| 5.6 W | 2700 K | 415lm | 305 | 050-1211 ☼☼ 8 A |
| | 3000 K | 454lm | | |
| 11.2 W | 2700 K | 829lm | 605 | 050-1212 ☼☼ 8 A |
| | 3000 K | 908lm | | |
| 22.3 W | 2700 K | 1660lm | 1205 | 050-1214 ☼☼ 8 A |
| | 3000 K | 1820lm | | |
| 45 W | 2700 K | 3320lm | 2405 | 050-1218 ☼☼ 8 A |
| | 3000 K | 3630lm | | |

Light distributions



wallwasher



wallwasher flush

INSET POWER in watts is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour black



MOVE IT 25 SYSTEM

WALL GRAZER / BATWING

linear inset 25S

Quickinfo

2700 K, 3000 K
CRI \geq 90, 3 SDCM
WALL GRAZER up to 107lm/W
BATWING up to 104lm/W
L80 @ 50 000 h
non DIM, DALI-2

Types

MOVE IT 25 S

WALL GRAZER / BATWING



Light distributions



CRI \geq 98
XPECTRUM

Order options

| | |
|---------------------------|----|
| COLOUR TEMPERATURE | •• |
| 2700 K | 4 |
| 3000 K | 5 |

| | |
|----------------|---|
| CONTROL | ◆ |
| non DIM | 1 |
| DALI-2 | 3 |

| |
|------------------------|
| MATERIAL COLOUR |
| ● jet black RAL 9005 |

Options on request

| |
|-------------------------------|
| COLOUR RENDERING INDEX |
| CRI ≥ 98 XPECTRUM |

| |
|---------------------------|
| COLOUR TEMPERATURE |
| 4000 K |




LIGHT INSET 25 S



WALL GRAZER


| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|------------------------|
| 5.3 W | 2700 K | 525lm | 305 | 0 5 0 - 1 2 1 1 :: 8 S |
| | 3000 K | 564lm | | |
| 10.6 W | 2700 K | 1050lm | 605 | 0 5 0 - 1 2 1 2 :: 8 S |
| | 3000 K | 1130lm | | |
| 21.3 W | 2700 K | 2100lm | 1205 | 0 5 0 - 1 2 1 4 :: 8 S |
| | 3000 K | 2260lm | | |
| 43 W | 2700 K | 4200lm | 2405 | 0 5 0 - 1 2 1 8 :: 8 S |
| | 3000 K | 4510lm | | |




BATWING

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|------------------------|
| 5.3 W | 2700 K | 512lm | 305 | 0 5 0 - 1 2 1 1 :: 8 B |
| | 3000 K | 550lm | | |
| 10.6 W | 2700 K | 1020lm | 605 | 0 5 0 - 1 2 1 2 :: 8 B |
| | 3000 K | 1100lm | | |
| 21.3 W | 2700 K | 2050lm | 1205 | 0 5 0 - 1 2 1 4 :: 8 B |
| | 3000 K | 2200lm | | |
| 43 W | 2700 K | 4100lm | 2405 | 0 5 0 - 1 2 1 8 :: 8 B |
| | 3000 K | 4400lm | | |

Light distributions



wall grazer



batwing

INSET POWER in watts is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour black

MOVE IT 25 system

acoustic elements

EN Acoustic element made of high quality, self-supporting, recycled PET felt with sound absorbing properties; different versions: choice of square, rectangular or triangular design; high quality visual and tactile surface with embossed pattern; foreign fiber inclusions possible; absorption of direct sound and sound reflected from the ceiling; this creates high acoustic performance; for installation in the MOVE IT 25 suspended system composed of node connectors and profiles; subsequent insertion in already installed MOVE IT suspended system possible; installation without tools

DE Akustikelement aus hochwertigem, selbsttragendem, recyceltem PET-Filz mit schallabsorbierenden Eigenschaften; unterschiedliche Varianten: Bauform wahlweise quadratisch, rechteckig oder dreieckig; optisch und haptisch hochwertige Oberfläche mit Musterprägung; Fremdfasereinschlüsse möglich; Absorption des Direktschalls und des von der Decke reflektierten Schalls; dadurch hohe akustische Performance; zum Einlegen in das MOVE IT 25 suspended system aus Knotenverbindern und Profilen; nachträgliches Einlegen in bereits installiertes MOVE IT suspended system möglich; werkzeuglose Montage

Quickinfo

PET felt

♻️ from recycled material

🔥 available as B-s1, d0

Types



Colours



easy
mounting



sound absorption
by recycled PET


Order options

| MATERIAL COLOUR | | <input checked="" type="checkbox"/> |
|-----------------------------------|--|-------------------------------------|
| <input type="radio"/> white | | W |
| <input type="radio"/> marble grey | | D |
| <input type="radio"/> black | | L |

Options on request

MATERIAL COLOUR
 painted in custom colour _____

DIMENSIONS
 cut in custom dimensions _____



MOVE IT 25 acoustic suspended

PET
felt

ACOUSTIC ELEMENT

| TYPE | L-W-H (mm) | ORDER CODE |
|-------------------|--------------|--|
| square grid inlay | 1235-1235-25 | 050-231121 <input checked="" type="checkbox"/> |
| half grid inlay | 635-1235-25 | 050-231221 <input checked="" type="checkbox"/> |
| double grid inlay | 2435-1235-25 | 050-231321 <input checked="" type="checkbox"/> |
| triangle inlay | 1195-1035-25 | 050-231421 <input checked="" type="checkbox"/> |

mounting only in MOVE IT 25 system with NODE connector + track 1220 mm, 620 mm or 2420 mm

ACOUSTIC EXAMPLES

