

# ARY adjustable rod suspended canopy surface

049-5231418M 005-2602118



Projekt / Typ \_\_\_\_\_

Notizen \_\_\_\_\_

Anzahl / Datum \_\_\_\_\_



220-240V

220-240V

220-240V

X-PERT

**Allgemein**

Decke , Abgehängt \_\_\_\_\_

schwenkbar max. 90° \_\_\_\_\_

Rotierbarkeit 265° \_\_\_\_\_

Schwarz , RAL9005 <sup>1</sup> \_\_\_\_\_

Baldachin Tiefschwarz \_\_\_\_\_

IP20 \_\_\_\_\_

642 lm \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89 \_\_\_\_\_

MR 0.54 \_\_\_\_\_

MDER 0.49 \_\_\_\_\_

**Optisch**

medium \_\_\_\_\_

Ausstrahlwinkel 25° \_\_\_\_\_

**Elektrisch**

nicht dimmbar \_\_\_\_\_

11.2 W \_\_\_\_\_

SK2 220-240V \_\_\_\_\_

57 lm/W \_\_\_\_\_

**Abmessungen**

Pende 1500 mm mit Haken \_\_\_\_\_


Durchmesser 47 mm \_\_\_\_\_

Höhe 110 mm \_\_\_\_\_

0.5 kg \_\_\_\_\_


<sup>1</sup> RAL Code

## Lichtverteilung



medium 25°		
h (m)	E0° (lx)	ø (m)
1	2780	0.44
2	690	0.89
3	310	1.33
4	170	1.78
5	110	2.22

## Produktskizze



## Montage- anleitung



## Beleuchtungs- rechner

