

# ARY adjustable rod suspended canopy surface

049-5231417F 005-2602137



Projekt / Typ \_\_\_\_\_

Notizen \_\_\_\_\_

Anzahl / Datum \_\_\_\_\_



220-240V

265°

2700K

X-PERT

## Allgemein

Decke , Abgehängt \_\_\_\_\_

schwenkbar max. 90° \_\_\_\_\_

Rotierbarkeit 265° \_\_\_\_\_

Weiß , RAL9016 <sup>1</sup> \_\_\_\_\_

Baldachin Verkehrsweiß \_\_\_\_\_

IP20 \_\_\_\_\_

688 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89 \_\_\_\_\_

MR 0.54 \_\_\_\_\_

MDER 0.49 \_\_\_\_\_

## Optisch

flood \_\_\_\_\_

Ausstrahlwinkel 44° \_\_\_\_\_

## Elektrisch

DALI-2 \_\_\_\_\_

11.2 W \_\_\_\_\_

SK2 220-240V \_\_\_\_\_

61 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

## Abmessungen

Pende 1500 mm mit Haken \_\_\_\_\_


Durchmesser 47 mm \_\_\_\_\_

Höhe 110 mm \_\_\_\_\_

0.5 kg \_\_\_\_\_

<sup>1</sup> RAL Code


## Lichtverteilung



flood 44°

h (m)	E0° (lx)	ø (m)
1	1280	0.82
2	320	1.64
3	140	2.45
4	80	3.27
5	50	4.09

## Produktskizze



## Montage- anleitung



## Beleuchtungs- rechner

