



049-5231617F 005-2602137



Decke Abgehängt
schwenkbar max. 90°
Rotierbarkeit 265°
Verkehrsweiß RAL 9016 ¹
Baldachin Verkehrsweiß
IP20
791 lm


4000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 99 R _f : 89 R _{1-15} : 87
MR 0.81 MDER 0.73

flood | Ausstrahlwinkel 44°
PstLM ≤ 1.0^{2 3 4 5} | SVM ≤ 0.4^{2 3 4 5}

DALI-2 1 DALI Addr.
SK2 220-240 V
System 11.2 W Einsatz 8.4 W
Einsatz 94 lm/W ⁶
18 Vf 500 mA


Pende 1500 mm mit Haken
Durchmesser 47 mm | Höhe 110 mm
0.65 kg

Produktskizze



flood 44°

h (m)	E0° (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09



¹ RAL Code ² soft lens BO 45 007-1965980

³ wallwasher lens BO 45 007-1965780⁴ oval lens BO 45 007-1965880⁵ Wert von umgebendem Produkt bei Volllast (ungedimmt)⁶ inkl. Berücksichtigung von optischen & internen

Steuergeräteverlusten

Beleuchtungs- rechner

