

ARY adjustable rod suspended canopy surface

049-5131518M 005-2601138



Projekt / Typ _____

Notizen _____

Anzahl / Datum _____



220-240V

220-240V

220-240V

X-PERT

Allgemein

Decke , Abgehängt _____

schwenkbar max. 90° _____

Rotierbarkeit 265° _____

Schwarz , RAL9005 ¹ _____

Baldachin Tiefschwarz _____

IP20 _____

739 lm _____

LED

3000 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 100 , R_f: 90 , R_{f(1-15)}: 87 _____

MR 0.59 _____

MDER 0.54 _____

Optisch

medium _____

Ausstrahlwinkel 25° _____

Elektrisch

DALI-2 _____

11.2 W _____

SK2 220-240V _____

66 lm/W _____

1 DALI Addr. _____

Abmessungen

Pende 1500 mm _____

Durchmesser 47 mm _____

Höhe 110 mm _____

0.45 kg _____

¹ RAL Code _____

Lichtverteilung



h (m)	EO° (lx)	ø (m)
1	3200	0.44
2	800	0.89
3	360	1.33
4	200	1.78
5	130	2.22

Produktskizze



Montage- anleitung



Beleuchtungs- rechner

