

# ARY adjustable rod suspended canopy surface

049-5231517F 005-2602117



Projekt / Typ \_\_\_\_\_

Notizen \_\_\_\_\_

Anzahl / Datum \_\_\_\_\_



220-240V

265°

220-240V

X-PERT

**Allgemein**

Decke , Abgehängt \_\_\_\_\_

schwenkbar max. 90° \_\_\_\_\_

Rotierbarkeit 265° \_\_\_\_\_

Weiß , RAL9016 <sup>1</sup> \_\_\_\_\_

Baldachin Verkehrsweiß \_\_\_\_\_

IP20 \_\_\_\_\_

791 lm \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 90 , R<sub>f(1-15)</sub>: 87 \_\_\_\_\_

MR 0.59 \_\_\_\_\_

MDER 0.54 \_\_\_\_\_

**Optisch**

flood \_\_\_\_\_

Ausstrahlwinkel 44° \_\_\_\_\_

**Elektrisch**

nicht dimmbar \_\_\_\_\_

11.2 W \_\_\_\_\_

SK2 220-240V \_\_\_\_\_

71 lm/W \_\_\_\_\_

**Abmessungen**

Pende 1500 mm mit Haken \_\_\_\_\_

Durchmesser 47 mm \_\_\_\_\_

Höhe 110 mm \_\_\_\_\_

0.5 kg \_\_\_\_\_

<sup>1</sup> RAL Code

## Lichtverteilung



flood 44°

| h (m) | EO <sup>2</sup> (lx) | ø (m) |
|-------|----------------------|-------|
| 1     | 1470                 | 0.82  |
| 2     | 370                  | 1.64  |
| 3     | 160                  | 2.45  |
| 4     | 90                   | 3.27  |
| 5     | 60                   | 4.09  |

## Produktskizze



## Montage- anleitung



## Beleuchtungs- rechner

