

# ARY adjustable rod suspended canopy surface

049-5131518F 005-2601138



Projekt / Typ \_\_\_\_\_

Notizen \_\_\_\_\_

Anzahl / Datum \_\_\_\_\_



220-240V

265°

220-240V

X-PERT

## Allgemein

Decke , Abgehängt \_\_\_\_\_

schwenkbar max. 90° \_\_\_\_\_

Rotierbarkeit 265° \_\_\_\_\_

Schwarz , RAL9005 <sup>1</sup> \_\_\_\_\_

Baldachin Tiefschwarz \_\_\_\_\_

IP20 \_\_\_\_\_

791 lm \_\_\_\_\_

## LED

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 90 , R<sub>f(1-15)</sub>: 87 \_\_\_\_\_

MR 0.59 \_\_\_\_\_

MDER 0.54 \_\_\_\_\_

## Optisch

flood \_\_\_\_\_

Ausstrahlwinkel 44° \_\_\_\_\_

## Elektrisch

DALI-2 \_\_\_\_\_

11.2 W \_\_\_\_\_

SK2 220-240V \_\_\_\_\_

71 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

## Abmessungen

Pende 1500 mm \_\_\_\_\_


Durchmesser 47 mm \_\_\_\_\_

Höhe 110 mm \_\_\_\_\_

0.45 kg \_\_\_\_\_

<sup>1</sup> RAL Code

## Lichtverteilung



flood 44°

h (m)	EO° (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

## Produktskizze



## Montage- anleitung



## Beleuchtungs- rechner

