

# ARY adjustable rod suspended canopy surface

049-513141XM 005-2601197



Projekt / Typ \_\_\_\_\_

Notizen \_\_\_\_\_

Anzahl / Datum \_\_\_\_\_



220-240V

220-240V

220-240V

X-PERT

**Allgemein**

Decke , Abgehängt \_\_\_\_\_

schwenkbar max. 90° \_\_\_\_\_

Rotierbarkeit 265° \_\_\_\_\_

Spezialfarben \_\_\_\_\_

Baldachin Verkehrsweiß \_\_\_\_\_

IP20 \_\_\_\_\_

642 lm \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89 \_\_\_\_\_

MR 0.54 \_\_\_\_\_

MDER 0.49 \_\_\_\_\_

**Optisch**

medium \_\_\_\_\_

Ausstrahlwinkel 25° \_\_\_\_\_

**Elektrisch**

Casambi \_\_\_\_\_

11.2 W \_\_\_\_\_

SK2 220-240V \_\_\_\_\_

57 lm/W \_\_\_\_\_

**Abmessungen**


Pende 1500 mm \_\_\_\_\_

Durchmesser 47 mm \_\_\_\_\_

Höhe 110 mm \_\_\_\_\_


0.45 kg \_\_\_\_\_

## Lichtverteilung



| medium 25° |          |       |
|------------|----------|-------|
| h (m)      | EO° (lx) | ø (m) |
| 1          | 2780     | 0.44  |
| 2          | 690      | 0.89  |
| 3          | 310      | 1.33  |
| 4          | 170      | 1.78  |
| 5          | 110      | 2.22  |

## Produktskizze



## Montage- anleitung



## Beleuchtungs- rechner

