

# ARY adjustable rod suspended canopy surface

049-513141XF 005-2601118



Projekt / Typ \_\_\_\_\_

Notizen \_\_\_\_\_

Anzahl / Datum \_\_\_\_\_



220-240V

220-240V

220-240V

X-PERT

**Allgemein**

Decke , Abgehängt \_\_\_\_\_

schwenkbar max. 90° \_\_\_\_\_

Rotierbarkeit 265° \_\_\_\_\_

Spezialfarben \_\_\_\_\_

Baldachin Tiefschwarz \_\_\_\_\_

IP20 \_\_\_\_\_

688 lm \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89 \_\_\_\_\_

MR 0.54 \_\_\_\_\_

MDER 0.49 \_\_\_\_\_

**Optisch**

flood \_\_\_\_\_

Ausstrahlwinkel 44° \_\_\_\_\_

**Elektrisch**

nicht dimmbar \_\_\_\_\_

11.2 W \_\_\_\_\_

SK2 220-240V \_\_\_\_\_

61 lm/W \_\_\_\_\_

**Abmessungen**


Pende 1500 mm \_\_\_\_\_

Durchmesser 47 mm \_\_\_\_\_

Höhe 110 mm \_\_\_\_\_

0.45 kg \_\_\_\_\_

## Lichtverteilung



flood 44°			
h (m)	EO° (lx)	ø (m)	
1	1280	0.82	
2	320	1.64	
3	140	2.45	
4	80	3.27	
5	50	4.09	

## Produktskizze



## Montage- anleitung



## Beleuchtungs- rechner

