

ARY adjustable rod suspended canopy surface

049-5131618M 005-2601138



Projekt / Typ _____

Notizen _____

Anzahl / Datum _____



220-240V

220-240V

220-240V

220-240V

Allgemein

Decke , Abgehängt _____

schwenkbar max. 90° _____

Rotierbarkeit 265° _____

Schwarz , RAL9005 ¹ _____

Baldachin Tiefschwarz _____

IP20 _____

739 lm _____

LED

4000 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 , R_r: 89 , R_{t(1-5)}: 87 _____

MR 0.81 _____

MDER 0.73 _____

Optisch

medium _____

Ausstrahlwinkel 25° _____

Elektrisch

DALI-2 _____

11.2 W _____

SK2 220-240V _____

66 lm/W _____

1 DALI Addr. _____

Abmessungen

Pende 1500 mm _____


Durchmesser 47 mm _____

Höhe 110 mm _____

0.45 kg _____

¹ RAL Code _____

Lichtverteilung



medium 25°			
h (m)	EO° (lx)	ø (m)	
1	3200	0.44	
2	800	0.89	
3	360	1.33	
4	200	1.78	
5	130	2.22	

Produktskizze



Montage- anleitung



Beleuchtungs- rechner

