

# ARY adjustable rod suspended canopy surface

049-513151XM 005-2601198



Projekt / Typ \_\_\_\_\_

Notizen \_\_\_\_\_

Anzahl / Datum \_\_\_\_\_



220-240V

220-240V

220-240V

X-PERT

**Allgemein**

Decke , Abgehängt \_\_\_\_\_

schwenkbar max. 90° \_\_\_\_\_

Rotierbarkeit 265° \_\_\_\_\_

Spezialfarben \_\_\_\_\_

Baldachin Tiefschwarz \_\_\_\_\_

IP20 \_\_\_\_\_

739 lm \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 90 , R<sub>f(1-15)</sub>: 87 \_\_\_\_\_

MR 0.59 \_\_\_\_\_

MDER 0.54 \_\_\_\_\_

**Optisch**

medium \_\_\_\_\_

Ausstrahlwinkel 25° \_\_\_\_\_

**Elektrisch**

Casambi \_\_\_\_\_

11.2 W \_\_\_\_\_

SK2 220-240V \_\_\_\_\_

66 lm/W \_\_\_\_\_

**Abmessungen**


Pende 1500 mm \_\_\_\_\_

Durchmesser 47 mm \_\_\_\_\_

Höhe 110 mm \_\_\_\_\_

0.45 kg \_\_\_\_\_

## Lichtverteilung



h (m)	EO° (lx)	ø (m)
1	3200	0.44
2	800	0.89
3	360	1.33
4	200	1.78
5	130	2.22

## Produktskizze



## Montage- anleitung



## Beleuchtungs- rechner

