

# SASSO 100 square adjustable

semi-recessed

048-33016179F 002-90779



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke, Halbeinbau

schwenkbar max. 20°

Weiß, RAL9016/gold<sup>1</sup>

Innenfarbe Gold

IP20

1690 lm

## LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 97, R<sub>f</sub>: 90, R<sub>t(1-5)</sub>: 89

MR 0.81

MDER 0.74

## Optisch

flood

Ausstrahlwinkel 44°

UGR < 16, ≥ 65° < 3000 cd/m²

PstLM ≤ 1.0<sup>2</sup>

SVM ≤ 0.4<sup>2</sup>

## Elektrisch

DALI-2

20.2 W

SK2 220-240V

84 lm/W

1 DALI Addr.

## Abmessungen

Länge 100 mm

Breite 100 mm

Höhe 115 mm

0.13 kg

## Ausschnitt

Einbautiefe 100 mm

<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Volllast (ungedimmt)


## Montageanleitung



## Beleuchtungsrechner



## Lichtverteilung



## Produktskizze

