

# SASSO 100 square adjustable

semi-recessed

048-33016119S 002-90779



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke , Halbeinbau

schwenkbar max. 20°

Schwarz , RAL9005/gold <sup>1</sup>

Innenfarbe Gold

IP20

1510 lm

## LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 97 , R<sub>f</sub>: 90 , R<sub>(1-15)</sub>: 89

MR 0.81

MDER 0.74

## Optisch

spot

Ausstrahlwinkel 18°

UGR < 13 , ≥65° <3000 cd/m<sup>2</sup>

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Elektrisch

DALI-2

20.2 W

SK2 220-240V

75 lm/W

1 DALI Addr.

## Abmessungen

Länge 100 mm

Breite 100 mm

Höhe 115 mm

0.13 kg


## Ausschnitt

Einbautiefe 100 mm


<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

## Lichtverteilung



## Produktskizze



## Montageanleitung



## Beleuchtungsrechner

