



SASSO 60 base

ceiling

EN Cylindrical or square spotlight made of aluminium; light inset lacquered; housing powder coated; light inset rotatable and tiltable (cylindrical versions); choice of single lamp or double lamps (cylindrical versions); surface mounted housing in aluminium incl. converter; mounting plate with pre-assembled converter unit can be pre-mounted; luminaire housing can be attached without tools by interlock; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; luminaire for through wiring

IT Faretto cilindrico o quadrato in alluminio; inserto verniciato; housing verniciato a polvere; inserto luce girevole e orientabile (versioni cilindr.); a scelta a monoemissione o biemissione (versioni cilindr.); alloggiamento con montaggio a superficie in alluminio, convertitore incluso; piastra di montaggio preinstallabile con unità convertitore premontata; corpo illuminante montabile ad appoggio senza attrezzi tramite blocco di sicurezza; emissione precisa con ottica lenticolare di alta qualità; tecnologia COB (Chip on Board) per la massima efficienza; assenza di ombre multiple; LED efficienti con alta resa cromatica; apparecchio per cablaggio passante

Quickinfo

2700 K, 3000 K, 4000 K
 CRI ≥ 90, 2 SDCM
 SASSO round up to 90lm/W
 SASSO square up to 86lm/W
 L80 @ 50000h
 non DIM, DALI-2

Types



Housing colours



Inset colours



Light distributions



glare control
 (UGR ≤ 16)



easy mounting;
 no visible screws



CRI ≥ 95
 2 SDCM

Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL

non DIM	1
DALI-2	3

HOUSING COLOUR

<input type="radio"/> traffic white RAL 9016	7
<input checked="" type="radio"/> jet black RAL 9005	1

INSET COLOUR

<input type="radio"/> traffic white RAL 9016 (UGR \leq 22)	7
<input type="radio"/> matt silver (UGR \leq 19)	4
<input checked="" type="radio"/> jet black RAL 9005 (UGR \leq 16)	1
<input type="radio"/> gold dust RAL 260-M (UGR \leq 19)	9

BEAM ANGLE

spot 11°	S
medium 21°	M
flood 42°	F
wide flood 54°	W

Options on request

COLOUR RENDERING INDEX

CRI \geq 95, 2 SDCM

LIGHT DISTRIBUTION

wallwasher


wallwasher / floor



SASSO 60 base round



ADJUSTABLE 1 LAMP

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11.7 W	2700 K	816 lm	0 4 8 - 3 1 3 0 
	3000 K	882 lm	
	4000 K	948 lm	

ADJUSTABLE 2 LAMPS

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
21.6 W	2700 K	2 × 873 lm	0 4 8 - 3 1 4 0 
	3000 K	2 × 921 lm	
	4000 K	2 × 977 lm	

SASSO 60 base square



DOWNLIGHT 1 LAMP

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11.7 W	2700 K	865 lm	0 4 8 - 3 0 3 0 
	3000 K	936 lm	
	4000 K	1010 lm	