

# SASSO 100 square downlight

trim

048-2710511M 048-279731G 002-90776



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke, Einbau

Schwarz, RAL9005<sup>1</sup>

Montage Set Silber-grau

Vorderseite IP44, Rückseite IP20

1870 lm

## LED

3000 K

CRI  $\geq 90$

L80 / 50000 h

initial MacAdam  $\leq 2$  SDCM

R<sub>g</sub>: 100, R<sub>f</sub>: 91, R<sub>f(1-15)</sub>: 88

MR 0.59

MDER 0.53

## Optisch

medium

Ausstrahlwinkel 33°x34°

UGR  $< 16$ ,  $\geq 65^\circ < 3000$  cd/m<sup>2</sup>

PstLM  $\leq 1.0$ <sup>2</sup>

SVM  $\leq 0.4$ <sup>2</sup>

## Elektrisch

DALI-2

29.2 W

SK2 220-240V

64 lm/W

1 DALI Addr.

## Abmessungen

mit Rand

Länge 118 mm

Breite 118 mm

Höhe 75 mm

0.52 kg

## Ausschnitt

Länge 112 mm

Breite 112 mm

min. Deckenstärke 2 mm


max. Deckenstärke 25 mm

Einbautiefe 80 mm

<sup>1</sup> RAL Code



<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

## Lichtverteilung



## Produktskizze

80  
non DIM  
80  
DALI-2  
112 x 112



## Montage- anleitung



## Beleuchtungs- rechner

