

SASSO 100 round downlight

trim

048-2700411S 048-2796317 002-90779



Projekt / Typ

Notizen

Anzahl / Datum



Allgemein

Decke, Einbau

Schwarz, RAL9005¹

Montage Set Verkehrsweiß

Vorderseite IP44, Rückseite IP20

1310 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99, R_r: 91, R_{f(1-15)}: 89

MR 0.53

MDER 0.48

Optisch

spot

Ausstrahlwinkel 19°

UGR < 13 , $\geq 65^\circ < 3000$ cd/m²

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Elektrisch

DALI-2

20.2 W

Einsatz 17.2 W

36 V_f

500 mA

SK2 220-240V

65 lm/W

1 DALI Addr.

Abmessungen

mit Rand

Durchmesser 118 mm

Höhe 75 mm

0.5 kg

Ausschnitt

Durchmesser 108 mm

min. Deckenstärke 2 mm

max. Deckenstärke 25 mm

Einbautiefe 80 mm

¹ RAL Code

² Wert von umgebendem Produkt bei Vollast (ungedimmt)


Montage- anleitung



Beleuchtungs- rechner



Lichtverteilung



Produktskizze

